

DATOS TÉCNICOS

TECHNICAL DATA

Referencia de producto	1332
Product reference	1332
Descripción	Adaptador doble TT
Description	TT Dual Adapter
Peso neto (Kg)	0.063
Net weight	0.063
ETIM 9.0	EC000330
Intensidad (A)	16
IEC-Amperage (A)	16
Polos	2P+T
Poles	2P+T
Frecuencia	(50/60Hz)
Frequency	(50/60Hz)
Voltaje (V)	250
Voltage (V)	250
Color	Blanco
Colour	White
RAL	9003
Interruptor	No
Switch	No
Material	Termoplastico
Material	Thermoplastic
Grado de protección	IP20
Protection degree	IP20
Resistencia al impacto	IK07
Impact resistance	IK07
Uso	Interior
Use	Indoor
Prueba hilo incandescente	750°C Partes activas soportes / 650°C otras partes
Glow wire test	750°C Active Parts Supports / 650°C Other Parts
Ensayo de bola	125°C Partes activas soportes / 70°C otras partes
Ball pressure test	125°C active parts supports / 70°C other parts
Resistencia al aislamiento	5MΩ@500Vdc
Insulating resistance	5MΩ@500Vdc
Potencia max.	3680
Max. power	3680
Rigidez dieléctrica (kV)	2
Dielectric Strenght (kV)	2
Temperatura de funcionamiento	-5 / 40°C
Operating temperature	-5 / 40°C
Temperatura de transporte y almacenaje	-25°C/ 70°C
Transport and storage temperature	-25°C/ 70°C
Alto / High	77
Ancho / Width	92
Profundo / Deep	49



DATOS LOGÍSTICOS

LOGISTICS

Unidad mínima de venta	12
Minimum sales unit	12
EAN Unitario	8429760824008
EAN Unit	8429760824008
Cantidad estuche	12
Quantity inner box	12
EAN Estuche	18429760824005
EAN Inner box	18429760824005
Cantidad caja	72
Quantity master box	72
EAN Caja	28429760824002
EAN Master box	28429760824002
Partida arancelaria	85366990
HS code	85366990

NORMATIVAS Y CERTIFICACIONES

APPLIED AND CERTIFICATIONS

Normativa	UNE 20315-1-1, UNE 20315-1-2, UNE 20315-2-5 (IEC 60884-1)
Applied	UNE 20315-1-1, UNE 20315-1-2, UNE 20315-2-5 (IEC 60884-1)
Directiva baja tensión	-
Low Voltage Directive	-
Directiva Rohs	RoHS 2011/65/UE and modifications
Rohs Directive	RoHS 2011/65/UE and modifications
Certificado de producto	-
Product certificate	-