

DATOS TÉCNICOS TECHNICAL DATA

Referencia de producto	19089
Product reference	19089
Descripción	Pulsador de superficie 10A 250V IP55
Description	Surface push button 10A 250V IP55
Peso neto (Kg)	0.14
Net weight (Kg)	0.14
ETIM 9.0	EC000029
Intensidad (A)	10
Intensity (A)	10
Voltaje (V)	250
Voltage (V)	250
Frecuencia (Hz)	(50/60Hz)
Frequency (Hz)	(50/60Hz)
Material	Termoplástico
Material	Thermoplastic
Color	Gris claro / Gris antracita
Colour	Light gray / Anthracite gray
Grado de protección IP	IP55
Degree of protection IP	IP55
Uso	Exterior
Use	Outdoor
Tipo de instalación	Superficie
Type of installation	Surface
Resistencia de aislamiento	>5MΩ@500Vdc
Insulation resistance	>5MΩ@500Vdc
Regidez dieléctrica (kV)	2
Dielectric strength (kV)	2
Hilo incandescente	850°C soportes partes activas / 650°C otras partes
Glow wire	850°C active parts supports / 650°C other parts
Ensayo de bola	125°C soportes partes activas / 70°C otras partes
Ball pressure test	125°C housings active parts / 70°C other parts
Alto / Height	80
Ancho / Width	80
Profundo / Depth	59



DATOS LOGÍSTICOS LOGISTICS

Unidad mínima de venta	10
Minimum sales unit	10
EAN Unitario	8429760853794
EAN Unit	8429760853794
Cantidad estuche	10
Quantity inner box	10
EAN Estuche	18429760853791
EAN Inner box	18429760853791
Cantidad caja	80
Quantity master box	80
EAN Caja	28429760853798
EAN Master box	28429760853798
Partida arancelaria	85366990
HS code	85366990

NORMATIVAS Y CERTIFICACIONES APPLIED AND CERTIFICATIONS

Normativa	EN 60669-1
Applied	EN 60669-1
Directiva baja tensión	Low Voltage Directive 2014/35/UE
Low Voltage Directive	Low Voltage Directive 2014/35/UE
Directiva Rohs	RoHS 2011/65/UE and modifications
Rohs Directive	RoHS 2011/65/UE and modifications
Certificado de producto	-
Product certificate	-
Reglamento electrotécnico baja tensión	REBT 2002
Low voltage electrotechnical regulations	REBT 2002