

DATOS TÉCNICOS TECHNICAL DATA

Referencia de producto	19096V
Product reference	19096V
Descripción	Doble base schuko vertical de superficie 16A250V IP55
Description	Double surface vertical schuko base 16A250V IP55
Peso neto (Kg)	0.3
Net weight (Kg)	0.3
ETIM 9.0	EC000125
Intensidad (A)	16
Intensity (A)	16
Voltaje (V)	250
Voltage (V)	250
Frecuencia (Hz)	(50/60Hz)
Frequency (Hz)	(50/60Hz)
Material	Termoplástico
Material	Thermoplastic
Color	Gris claro / Gris antracita
Colour	Light gray / Anthracite gray
Grado de protección IP	IP55
Degree of protection IP	IP55
Uso	Exterior
Use	Outdoor
Tipo de instalación	Superficie
Type of installation	Surface
Resistencia de aislamiento	>5MΩ@500Vdc
Insulation resistance	>5MΩ@500Vdc
Regidez dieléctrica (kV)	2
Dielectric strength (kV)	2
Hilo incandescente	850°C soportes partes activas / 650°C otras partes
Glow wire	850°C active parts supports / 650°C other parts
Ensayo de bola	125°C soportes partes activas / 70°C otras partes
Ball pressure test	125°C housings active parts / 70°C other parts
Alto / Height	160
Ancho / Width	80
Profundo / Depth	59



DATOS LOGÍSTICOS LOGISTICS

Unidad mínima de venta	5
Minimum sales unit	5
EAN Unitario	8429760853831
EAN Unit	8429760853831
Cantidad estuche	5
Quantity inner box	5
EAN Estuche	18429760853838
EAN Inner box	18429760853838
Cantidad caja	40
Quantity master box	40
EAN Caja	28429760853835
EAN Master box	28429760853835
Partida arancelaria	85366990
HS code	85366990

NORMATIVAS Y CERTIFICACIONES APPLIED AND CERTIFICATIONS

Normativa	UNE 20315-1-1, UNE 20315-1-2, UNE 20315-2-7, IEC 60884-2-2)
Applied	UNE 20315-1-1, UNE 20315-1-2, UNE 20315-2-7, IEC 60884-2-2)
Directiva baja tensión	Low Voltage Directive 2014/35/UE
Low Voltage Directive	Low Voltage Directive 2014/35/UE
Directiva Rohs	RoHS 2011/65/UE and modifications
Rohs Directive	RoHS 2011/65/UE and modifications
Certificado de producto	-
Product certificate	-
Reglamento electrotécnico baja tensión	REBT 2002
Low voltage electrotechnical regulations	REBT 2002