

## DATOS TÉCNICOS TECHNICAL DATA

|                                   |                                                           |
|-----------------------------------|-----------------------------------------------------------|
| <b>Referencia de producto</b>     | <b>19101</b>                                              |
| Product reference                 | 19101                                                     |
| <b>Descripción</b>                | <b>Base abatible cargador EV modo 1 16A 250V IP55</b>     |
| Description                       | Flip base EV charger mode 1 16A 250V IP55                 |
| <b>Peso neto (Kg)</b>             | <b>0.32</b>                                               |
| Net weight (Kg)                   | 0.32                                                      |
| <b>ETIM 9.0</b>                   | <b>EC000125</b>                                           |
| <b>Intensidad (A)</b>             | <b>16</b>                                                 |
| Intensity (A)                     | 16                                                        |
| <b>Voltaje (V)</b>                | <b>250</b>                                                |
| Voltage (V)                       | 250                                                       |
| <b>Frecuencia (Hz)</b>            | <b>(50/60Hz)</b>                                          |
| Frequency (Hz)                    | (50/60Hz)                                                 |
| <b>Material</b>                   | <b>PC</b>                                                 |
| Material                          | PC                                                        |
| <b>Color</b>                      | <b>Gris claro / Gris antracita</b>                        |
| Colour                            | Light gray / Anthracite gray                              |
| <b>Grado de protección IP</b>     | <b>IP55</b>                                               |
| Degree of protection IP           | IP55                                                      |
| <b>Uso</b>                        | <b>Interior-Exterior</b>                                  |
| Use                               | Indoor / Outdoor                                          |
| <b>Tipo de instalación</b>        | <b>Superficie</b>                                         |
| Type of installation              | Surface                                                   |
| <b>Resistencia de aislamiento</b> | <b>&gt;5MΩ@500Vdc</b>                                     |
| Insulation resistance             | >5MΩ@500Vdc                                               |
| <b>Regidez dieléctrica (kV)</b>   | <b>2</b>                                                  |
| Dielectric strength (kV)          | 2                                                         |
| <b>Hilo incandescente</b>         | <b>850°C soportes partes activas / 650°C otras partes</b> |
| Glow wire                         | 850°C active parts supports / 650°C other parts           |
| <b>Ensayo de bola</b>             | <b>125°C soportes partes activas / 70°C otras partes</b>  |
| Ball pressure test                | 125°C housings active parts / 70°C other parts            |
| <b>Alto / Height</b>              | <b>184</b>                                                |
| <b>Ancho / Width</b>              | <b>94</b>                                                 |
| <b>Profundo / Depth</b>           | <b>102</b>                                                |



## DATOS LOGÍSTICOS LOGISTICS

|                               |                       |
|-------------------------------|-----------------------|
| <b>Unidad mínima de venta</b> | <b>1</b>              |
| Minimum sales unit            | 1                     |
| <b>EAN Unitario</b>           | <b>8429760855729</b>  |
| EAN Unit                      | 8429760855729         |
| <b>Cantidad estuche</b>       | <b>-</b>              |
| Quantity inner box            | -                     |
| <b>EAN Estuche</b>            | <b>-</b>              |
| EAN Inner box                 | -                     |
| <b>Cantidad caja</b>          | <b>24</b>             |
| Quantity master box           | 24                    |
| <b>EAN Caja</b>               | <b>28429760855723</b> |
| EAN Master box                | 28429760855723        |
| <b>Partida arancelaria</b>    | <b>85366990</b>       |
| HS code                       | 85366990              |

## NORMATIVAS Y CERTIFICACIONES APPLIED AND CERTIFICATIONS

|                                               |                                                                    |
|-----------------------------------------------|--------------------------------------------------------------------|
| <b>Normativa</b>                              | <b>UNE 20315-1-1, UNE 20315-1-2, UNE 20315-2-7, IEC 60884-2-2)</b> |
| Applied                                       | UNE 20315-1-1, UNE 20315-1-2, UNE 20315-2-7, IEC 60884-2-2)        |
| <b>Directiva baja tensión</b>                 | <b>Low Voltage Directive 2014/35/UE</b>                            |
| Low Voltage Directive                         | Low Voltage Directive 2014/35/UE                                   |
| <b>Directiva Rohs</b>                         | <b>RoHS 2011/65/UE and modifications</b>                           |
| Rohs Directive                                | RoHS 2011/65/UE and modifications                                  |
| <b>Certificado de producto</b>                | <b>-</b>                                                           |
| Product certificate                           | -                                                                  |
| <b>Reglamento electrotécnico baja tensión</b> | <b>REBT 2002</b>                                                   |
| Low voltage electrotechnical regulations      | REBT 2002                                                          |