

DATOS TÉCNICOS TECHNICAL DATA

Referencia de producto	1001-N
Product reference	1001-N
Descripción	Clavija móvil desmontable 10A sin toma de tierra IP20
Description	Detachable mobile plug 10A without earth connection IP20
Peso neto (Kg)	0.0185
Net weight	0.0185
ETIM 9.0	EC003545
Intensidad (A)	10
IEC-Amperage (A)	10
Polos	2P
Poles	2P
Frecuencia	50Hz
Frequency	50Hz
Voltaje (V)	250
Voltage (V)	250
Color	Negro
Colour	Black
RAL	9004
Interruptor	No
Switch	No
Material	ABS
Material	ABS
Grado de protección	IP20
Protection degree	IP20
Resistencia al impacto	IK06
Impact resistance	IK06
Uso	Interior
Use	Indoor
Prueba hilo incandescente	750°C Partes activas soportes / 650°C otras partes
Glow wire test	750°C Active Parts Supports / 650°C Other Parts
Ensayo de bola	125°C Partes activas soportes / 70°C otras partes
Ball pressure test	125°C active parts supports / 70°C other parts
Resistencia al aislamiento	5MΩ@500Vdc
Insulating resistance	5MΩ@500Vdc
Potencia max.	-
Max. power	-
Rigidez dieléctrica (kV)	2
Dielectric Strength (kV)	2
Temperatura de funcionamiento	-5°C/ 40°C
Operating temperature	-5°C/ 40°C
Temperatura de transporte y almacenaje	-25°C/ 70°C
Transport and storage temperature	-25°C/ 70°C
Alto / High	14
Ancho / Width	67
Profundo / Deep	35



DATOS LOGÍSTICOS LOGISTICS

Unidad mínima de venta	60
Minimum sales unit	60
EAN Unitario	8429760410027
EAN Unit	8429760410027
Cantidad estuche	60
Quantity inner box	60
EAN Estuche	8429760110026
EAN Inner box	8429760110026
Cantidad caja	720
Quantity master box	720
EAN Caja	8429760710028
EAN Master box	8429760710028
Partida arancelaria	85366990
HS code	85366990

NORMATIVAS Y CERTIFICACIONES APPLIED AND CERTIFICATIONS

Normativa	UNE 20315-1-1 / UNE 20315-1-2(IEC 60884-1)
Applied	UNE 20315-1-1 / UNE 20315-1-2(IEC 60884-1)
Directiva baja tensión	-
Low Voltage Directive	-
Directiva Rohs	RoHS 2011/65/UE and modifications
Rohs Directive	RoHS 2011/65/UE and modifications
Certificado de producto	DEKRA KEMA
Product certificate	DEKRA KEMA