

DATOS TÉCNICOS

TECHNICAL DATA

Referencia de producto	1133
Product reference	1133
Descripción	Clavija de goma desmontable 16A con toma de tierra IP20
Description	Detachable 16A rubber plug with IP20 earth connection
Peso neto (Kg)	0.036
Net weight	0.036
ETIM 9.0	EC000242
Intensidad (A)	16
IEC-Amperage (A)	16
Polos	2P+T
Poles	2P+T
Frecuencia	50Hz
Frequency	50Hz
Voltaje (V)	250
Voltage (V)	250
Color	Negro
Colour	Black
RAL	9004
Interruptor	No
Switch	No
Material	Rubber
Material	Rubber
Grado de protección	IP20
Protection degree	IP20
Resistencia al impacto	IK07
Impact resistance	IK07
Uso	Interior
Use	Indoor
Prueba hilo incandescente	750°C Partes activas soportes / 650°C otras partes
Glow wire test	750°C Active Parts Supports / 650°C Other Parts
Ensayo de bola	125°C Partes activas soportes / 70°C otras partes
Ball pressure test	125°C active parts supports / 70°C other parts
Resistencia al aislamiento	5MΩ@500Vdc
Insulating resistance	5MΩ@500Vdc
Potencia max.	-
Max. power	-
Rigidez dieléctrica (kV)	2
Dielectric Strength (kV)	2
Temperatura de funcionamiento	-5°C/ 40°C
Operating temperature	-5°C/ 40°C
Temperatura de transporte y almacenaje	-25°C/ 70°C
Transport and storage temperature	-25°C/ 70°C
Alto / High	48
Ancho / Width	118
Profundo / Deep	49



DATOS LOGÍSTICOS

LOGISTICS

Unidad mínima de venta	25
Minimum sales unit	25
EAN Unitario	8436019841709
EAN Unit	8436019841709
Cantidad estuche	25
Quantity inner box	25
EAN Estuche	8436019851708
EAN Inner box	8436019851708
Cantidad caja	150
Quantity master box	150
EAN Caja	8436019861707
EAN Master box	8436019861707
Partida arancelaria	85366990
HS code	85366990

NORMATIVAS Y CERTIFICACIONES

APPLIED AND CERTIFICATIONS

Normativa	UNE 20315-1-1 / UNE 20315-1-2(IEC 60884-1+CEE 7)
Applied	UNE 20315-1-1 / UNE 20315-1-2(IEC 60884-1+CEE 7)
Directiva baja tensión	-
Low Voltage Directive	-
Directiva Rohs	RoHS 2011/65/UE and modifications
Rohs Directive	RoHS 2011/65/UE and modifications
Certificado de producto	-
Product certificate	-