

DATOS TÉCNICOS

TECHNICAL DATA

Referencia de producto	1321
Product reference	1321
Descripción	Adaptador 1 toma USB-A+USB-C
Description	Adapter 1 USB-A+USB-C socket
Peso neto (Kg)	0.078
Net weight	0.078
ETIM 9.0	EC000330
Intensidad (A)	16/3.4
IEC-Amperage (A)	16/3.4
Polos	2P+T
Poles	2P+T
Frecuencia	(50/60Hz)
Frequency	(50/60Hz)
Voltaje (V)	250
Voltage (V)	250
Color	Blanco
Colour	White
RAL	9003
Interruptor	No
Switch	No
Material	Termoplastico
Material	Thermoplastic
Grado de protección	IP20
Protection degree	IP20
Resistencia al impacto	IK07
Impact resistance	IK07
Uso	Interior
Use	Indoor
Prueba hilo incandescente	750°C Partes activas soportes / 650°C otras partes
Glow wire test	750°C Active Parts Supports / 650°C Other Parts
Ensayo de bola	125°C Partes activas soportes / 70°C otras partes
Ball pressure test	125°C active parts supports / 70°C other parts
Resistencia al aislamiento	5MΩ@500Vdc
Insulating resistance	5MΩ@500Vdc
Potencia max.	3680
Max. power	3680
Rigidez dieléctrica (kV)	2
Dielectric Strenght (kV)	2
Temperatura de funcionamiento	-5 / 40°C
Operating temperature	-5 / 40°C
Temperatura de transporte y almacenaje	-25°C/ 70°C
Transport and storage temperature	-25°C/ 70°C
Alto / High	77
Ancho / Width	92
Profundo / Deep	49



DATOS LOGÍSTICOS

LOGISTICS

Unidad mínima de venta	12
Minimum sales unit	12
EAN Unitario	8429760829454
EAN Unit	8429760829454
Cantidad estuche	12
Quantity inner box	12
EAN Estuche	18429760829451
EAN Inner box	18429760829451
Cantidad caja	72
Quantity master box	72
EAN Caja	28429760829458
EAN Master box	28429760829458
Partida arancelaria	85366990
HS code	85366990

NORMATIVAS Y CERTIFICACIONES

APPLIED AND CERTIFICATIONS

Normativa	UNE 20315-1-1, IEC 60884-1, UNE 20315-1-2, UNE 20315- 2-7
Applied	UNE 20315-1-1, IEC 60884-1, UNE 20315-1-2, UNE 20315- 2-7
Directiva baja tensión	Low Voltage Directive 2014/35/UE
Low Voltage Directive	Low Voltage Directive 2014/35/UE
Directiva Rohs	RoHS 2011/65/UE and modifications
Rohs Directive	RoHS 2011/65/UE and modifications
Certificado de producto	-
Product certificate	-