

DATOS TÉCNICOS

TECHNICAL DATA

Referencia de producto	1333-N
Product reference	1333-N
Descripción	Adaptador triple TT con USB A + USB C Negro
Description	Triple TT adapter with USB A + USB C Black
Peso neto (Kg)	0.092
Net weight	0.092
ETIM 9.0	EC000330
Intensidad (A)	16
IEC-Amperage (A)	16
Polos	2P+T
Poles	2P+T
Frecuencia	(50/60Hz)
Frequency	(50/60Hz)
Voltaje (V)	250
Voltage (V)	250
Color	Negro
Colour	Black
RAL	9004
Interrupción	No
Switch	No
Material	Termoplastico
Material	Thermoplastic
Grado de protección	IP20
Protection degree	IP20
Resistencia al impacto	IK07
Impact resistance	IK07
Uso	Interior
Use	Indoor
Prueba hilo incandescente	750°C Partes activas soportes / 650°C otras partes
Glow wire test	750°C Active Parts Supports / 650°C Other Parts
Ensayo de bola	125°C Partes activas soportes / 70°C otras partes
Ball pressure test	125°C active parts supports / 70°C other parts
Resistencia al aislamiento	5MΩ@500Vdc
Insulating resistance	5MΩ@500Vdc
Potencia max.	3680
Max. power	3680
Rigidez dieléctrica (kV)	2
Dielectric Strength (kV)	2
Temperatura de funcionamiento	-5 / 40°C
Operating temperature	-5 / 40°C
Temperatura de transporte y almacenaje	-25°C/ 70°C
Transport and storage temperature	-25°C/ 70°C
Alto / High	77
Ancho / Width	136
Profundo / Deep	49



DATOS LOGÍSTICOS

LOGISTICS

Unidad mínima de venta	9
Minimum sales unit	9
EAN Unitario	8429760829997
EAN Unit	8429760829997
Cantidad estuche	9
Quantity inner box	9
EAN Estuche	18429760829994
EAN Inner box	18429760829994
Cantidad caja	54
Quantity master box	54
EAN Caja	28429760829991
EAN Master box	28429760829991
Partida arancelaria	85366990
HS code	85366990

NORMATIVAS Y CERTIFICACIONES

APPLIED AND CERTIFICATIONS

Normativa	UNE 20315-1-1, UNE 20315-1-2, UNE 20315-2-5 (IEC 60884-1)
Applied	UNE 20315-1-1, UNE 20315-1-2, UNE 20315-2-5 (IEC 60884-1)
Directiva baja tensión	-
Low Voltage Directive	-
Directiva Rohs	RoHS 2011/65/UE and modifications
Rohs Directive	RoHS 2011/65/UE and modifications
Certificado de producto	-
Product certificate	-