


DATOS TÉCNICOS TECHNICAL DATA

Referencia de producto	13354
Product reference	13354
Descripción	Clavija superficie acodada 90° 2P+T 16A 400V IP44 SpeedPRO
Description	Wall-mounted angled plug 90° 2P+E 16A IP44 SpeedPRO
Peso neto (g)	-
Net weight (g)	-
ETIM 9.0	EC001319
Intensidad (A)	16
IEC-Amperage (A)	16
Polos	2P+T
Poles	2P+T
Voltaje (V)	380-415
Voltage (V)	380-415
Horas	9h
Hour position	9h
Color	Rojo
Colour	Red
Tipo de conexión	Conexión por tornillo
Connection system	Screw connection
Material	ABS+PA6
Material	ABS+PA6
Material de contacto	Latón Niquelado
Contact material	Nickel-plated brass
Cable admitido	1-2,5mm²
Wire flexible	1-2,5mm²
Diámetro exterior de cable admisible	-
Permissible cable outside diameter	-
Longitud del cable	-
Cable length	-
Grado de protección	IP44
Protection degree	IP44
Resistencia al impacto	IK08
Impact resistance	IK08
Ensayo de bola	125°C soportes partes activas / 70°C otras partes
Ball pressure test	125°C housings active parts / 70°C other parts
Resistencia al aislamiento	>10MΩ@500Vdc
Insulating resistance	>10MΩ@500Vdc
Rigidez dieléctrica (kV)	2.5
Dielectric Strength (kV)	2.5
Temperatura de funcionamiento	-25°C/ 40°C
Operating temperature	-25°C/ 40°C
Temperatura de resistencia	-25°C/ 70°C
Temperature resistance	-25°C/ 70°C



DATOS LOGÍSTICOS LOGISTICS

Unidad mínima de venta	
Minimum sales unit	
EAN Unitario	
EAN Unit	
Cantidad estuche	
Quantity inner box	
EAN Estuche	
EAN Inner box	
Cantidad caja	
Quantity master box	
EAN Caja	
EAN Master box	
Partida arancelaria	
HS code	

NORMATIVAS Y CERTIFICACIONES APPLIED AND CERTIFICATIONS

Normativa	IEC/EN 60309-1, IEC/EN 60309-2
Applied	IEC/EN 60309-1, IEC/EN 60309-2
Directiva baja tensión	Low Voltage Directive 2014/35/UE
Low Voltage Directive	Low Voltage Directive 2014/35/UE
Directiva Rohs	RoHS 2011/65/UE and modifications
Rohs Directive	RoHS 2011/65/UE and modifications
Certificado de producto	
Product certificate	

