

DATOS TÉCNICOS TECHNICAL DATA

Referencia de producto	19077
Product reference	19077
Descripción	Pulsador de superficie estanco 10A 250V IP55 Serie Aquant 55
Description	Waterproof surface push button 10A 250V IP55 Aquant 55 Series
Peso neto (Kg)	0.14
Net weight (Kg)	0.14
ETIM 9.0	EC000029
Intensidad (A)	10
Intensity (A)	10
Voltaje (V)	250
Voltage (V)	250
Frecuencia (Hz)	(50/60Hz)
Frequency (Hz)	(50/60Hz)
Material	ABS+TPE
Material	ABS+TPE
Color	Gris
Colour	Grey
Grado de protección IP	IP55
Degree of protection IP	IP55
Uso	Exterior
Use	Outdoor
Tipo de instalación	Superficie
Type of installation	Surface
Resistencia de aislamiento	5MΩ@500Vdc
Insulation resistance	5MΩ@500Vdc
Regidez dieléctrica (kV)	2
Dielectric strength (kV)	2
Hilo incandescente	850°C soporte partes activas/ 650°C otras partes
Glow wire	850°C support active parts/ 650°C other parts
Ensayo de bola	125°C soporte partes activas/ 70°C otras partes
Ball pressure test	125°C supports active parts/ 70°C other parts
Alto / Height	81
Ancho / Width	76
Profundo / Depth	57



DATOS LOGÍSTICOS LOGISTICS

Unidad mínima de venta	10
Minimum sales unit	10
EAN Unitario	8429760244936
EAN Unit	8429760244936
Cantidad estuche	10
Quantity inner box	10
EAN Estuche	8429760254935
EAN Inner box	8429760254935
Cantidad caja	280
Quantity master box	280
EAN Caja	8429760264934
EAN Master box	8429760264934
Partida arancelaria	85365080
HS code	85365080

NORMATIVAS Y CERTIFICACIONES APPLIED AND CERTIFICATIONS

Normativa	EN 60669-1
Applied	EN 60669-1
Directiva baja tensión	Low Voltage Directive 2014/35/UE
Low Voltage Directive	Low Voltage Directive 2014/35/UE
Directiva Rohs	RoHS 2011/65/UE and modifications
Rohs Directive	RoHS 2011/65/UE and modifications
Certificado de producto	-
Product certificate	-
Reglamento electrotécnico baja tensión	REBT 2002
Low voltage electrotechnical regulations	REBT 2002