

DATOS TÉCNICOS TECHNICAL DATA

Referencia de producto	2106
Product reference	2106
Descripción	Base de goma desmontable 16A con toma de tierra IP20
Description	Detachable rubber base 16A with IP20 earth connection
Peso neto (Kg)	0.09
Net weight	0.09
ETIM 9.0	EC001320
Intensidad (A)	16
IEC-Amperage (A)	16
Polos	2P+T
Poles	2P+T
Frecuencia	(50/60Hz)
Frequency	(50/60Hz)
Voltaje (V)	250
Voltage (V)	250
Color	Negro
Colour	Black
RAL	9004
Interruptor	No
Switch	No
Material	Rubber
Material	Rubber
Grado de protección	IP20
Protection degree	IP20
Resistencia al impacto	IK07
Impact resistance	IK07
Uso	Interior
Use	Indoor
Prueba hilo incandescente	750°C Partes activas soportes / 650°C otras partes
Glow wire test	750°C Active Parts Supports / 650°C Other Parts
Ensayo de bola	125°C Partes activas soportes / 70°C otras partes
Ball pressure test	125°C active parts supports / 70°C other parts
Resistencia al aislamiento	5MΩ@500Vdc
Insulating resistance	5MΩ@500Vdc
Potencia max.	-
Max. power	-
Rigidez dieléctrica (kV)	2
Dielectric Strength (kV)	2
Temperatura de funcionamiento	-5°C/ 40°C
Operating temperature	-5°C/ 40°C
Temperatura de transporte y almacenaje	-25°C/ 70°C
Transport and storage temperature	-25°C/ 70°C
Alto / High	53
Ancho / Width	89
Profundo / Deep	54



DATOS LOGÍSTICOS LOGISTICS

Unidad mínima de venta	20
Minimum sales unit	20
EAN Unitario	8429760242628
EAN Unit	8429760242628
Cantidad estuche	20
Quantity inner box	20
EAN Estuche	8429760252627
EAN Inner box	8429760252627
Cantidad caja	120
Quantity master box	120
EAN Caja	8429760262626
EAN Master box	8429760262626
Partida arancelaria	85366990
HS code	85366990

NORMATIVAS Y CERTIFICACIONES APPLIED AND CERTIFICATIONS

Normativa	UNE 20315-1-1 / UNE 20315-1-2(IEC 60884-1+CEE 7)
Applied	UNE 20315-1-1 / UNE 20315-1-2(IEC 60884-1+CEE 7)
Directiva baja tensión	-
Low Voltage Directive	-
Directiva Rohs	RoHS 2011/65/UE and modifications
Rohs Directive	RoHS 2011/65/UE and modifications
Certificado de producto	-
Product certificate	-

