

DATOS TÉCNICOS

TECHNICAL DATA

Referencia de producto	2308
Product reference	2308
Descripción	Base unitaria de empotrar 25A con toma de tierra
Description	25A recessed unit base with earth
Peso neto (Kg)	0.106
Net weight	0.106
ETIM 9.0	EC000125
Intensidad (A)	25
IEC-Amperage (A)	25
Polos	2P+T
Poles	2P+T
Frecuencia	(50/60Hz)
Frequency	(50/60Hz)
Voltaje (V)	250
Voltage (V)	250
Color	Blanco
Colour	White
RAL	9003
Interrupción	No
Switch	No
Material	Termoplástico
Material	Termoplástico
Grado de protección	IP20
Protection degree	IP20
Resistencia al impacto	IK07
Impact resistance	IK07
Uso	Interior
Use	Indoor
Prueba hilo incandescente	850°C soporte partes activas/ 650°C otras partes
Glow wire test	850°C support active parts/ 650°C other parts
Ensayo de bola	125°C soporte partes activas/ 70°C otras partes
Ball pressure test	125°C supports active parts/ 70°C other parts
Resistencia al aislamiento	5MΩ@500Vdc
Insulating resistance	5MΩ@500Vdc
Potencia max.	-
Max. power	-
Rigidez dieléctrica (kV)	2
Dielectric Strength (kV)	2
Temperatura de funcionamiento	-5°C/ 40°C
Operating temperature	-5°C/ 40°C
Temperatura de transporte y almacenaje	-25°C/ 70°C
Transport and storage temperature	-25°C/ 70°C
Alto / High	58
Ancho / Width	85
Profundo / Deep	85



DATOS LOGÍSTICOS

LOGISTICS

Unidad mínima de venta	10
Minimum sales unit	10
EAN Unitario	8429760420118
EAN Unit	8429760420118
Cantidad estuche	10
Quantity inner box	10
EAN Estuche	8429760120117
EAN Inner box	8429760120117
Cantidad caja	60
Quantity master box	60
EAN Caja	8429760720119
EAN Master box	8429760720119
Partida arancelaria	85366990
HS code	85366990

NORMATIVAS Y CERTIFICACIONES

APPLIED AND CERTIFICATIONS

Normativa	UNE 20315-1-1 / UNE 20315-1-2(IEC 60884-1+CEE 7)
Applied	UNE 20315-1-1 / UNE 20315-1-2(IEC 60884-1+CEE 7)
Directiva baja tensión	-
Low Voltage Directive	-
Directiva Rohs	RoHS 2011/65/UE and modifications
Rohs Directive	RoHS 2011/65/UE and modifications
Certificado de producto	-
Product certificate	-