

DATOS TÉCNICOS TECHNICAL DATA

Referencia de producto	23312.4
Product reference	23312.4
Descripción	Envolverte de goma cableada 18 módulos con 5 tomas schuko + 2 tomas 3P+N+T 16A 380-440V + 1 toma 3P+N+T 32A 380-440V IP65 IMPACT
Description	18-module wired rubber enclosure with 5 Schuko sockets + 2 3P+N+E sockets 16A 380-440V + 1 3P+N+E socket 32A 380-440V IP65 IMPACT
Peso neto (Kg)	
Net weight (Kg)	
ETIM 9.0	EC000379
Módulos	18
Modules	18
Enlazable	No
Linkable	No
Tipo de instalación	Superficie
Installation	Surface
Compatible carril DIN	Sí
Compatible with DIN Rail	Yes
Puerta	Transparente
Door	Transparent
Ángulo apertura puerta (°)	-
Opening angle (°)	-
Precintable	-
Sealable	-
Uso	Interior-Exterior
Use	Indoor-Outdoor
Componentes incorporados	5 x 2P+TTL 16A 250V + 2 x 3P+T+N 16A 380-440V + 1 x 3P+N+T 32A
Built-in components	-
Accesorios	-
Optional accessories	-
Rigidez dieléctrica (kV)	3
Dielectric strength (kV)	3
Tensión de impulso (kV)	-
Impulse withstand voltage (kV)	-
Clase de aislamiento	Clase II
Insulation Class	Class II
Intensidad cortocircuito (kA)	-
Rated current	-
Capacidad de disipación térmica (W)	43
Thermal power dissipation capability	43
Grado de protección IP	IP65
IP Protection Degree	IP65
Resistencia al impacto IK	IK10
Impact Resistance IK	IK10
Material	Caucho butílico+Puerta PC
Material	Butyl rubber + PC door
Color	Negro
Colour	Black
RAL	-
Ensayo hilo incandescente	960°C
Glow wire test	960°C/960°C
Ensayo de bola / Ball pressure test	80°C
Material libre de halógenos	-
Halogen free materials	-
Resistencia UV / UV Resistant	-
Temperatura de funcionamiento (°C)	-
Ambient operating temperatura range	-
Temperatura de transporte y almacenaje	-
Transport and storage	-
Alto / Height	380
Ancho / Width	370
Profundo / Depth	170
Alto interior / Height inside	370
Ancho interior / Width inside	360
Profundo interior / Depth inside	160
Entrada superior / Top entries	-
Entrada inferior / Bottom entries	-
Entrada lateral / Lateral entries	-
Entrada posterior / Back entries	-



DATOS LOGÍSTICOS LOGISTICS

Unidad mínima de venta	1
Minimum sales unit	1
EAN Unitario	8429760277699
EAN Unit	8429760277699
Cantidad estuche	1
Quantity inner box	1
EAN Estuche	-
EAN Inner box	-
Cantidad caja	-
Quantity master box	-
EAN Caja	-
EAN Master box	-
Partida arancelaria	85371098
HS code	85371098

NORMATIVAS Y CERTIFICACIONES APPLIED AND CERTIFICATIONS

Normativa	IEC/EN 62208, IEC/EN 61439-1, IEC/EN 61439-3
Applied	IEC/EN 62208, IEC/EN 61439-1, IEC/EN 61439-3
Directiva baja tensión	Low Voltage Directive 2014/35/UE
Low Voltage Directive	Low Voltage Directive 2014/35/UE
Directiva Rohs	--
Rohs Directive	--
Certificado de producto	--
Product certificate	--
Reglamento electrotécnico baja tensión	-
Low voltage electrotechnical regulations	-

DIMENSIONES | DIMENSIONS

