


DATOS TÉCNICOS TECHNICAL DATA

Referencia de producto	24380
Product reference	24380
Descripción	Straight panel socket 2P+T 63A IP67 SpeedPRO
Description	Straight panel socket 2P+T 63A IP67 SpeedPRO
Peso neto (g)	-
Net weight (g)	-
ETIM 9.0	EC001317
Intensidad (A)	63
IEC-Amperage (A)	63
Polos	2P+T
Poles	2P+T
Voltaje (V)	380-415
Voltage (V)	380-415
Horas	9h
Hour position	9h
Color	Rojo
Colour	Red
Tipo de conexión	Conexión por tornillo
Connection system	Screw connection
Material	ABS+PA6
Material	ABS+PA6
Material de contacto	Latón
Contact material	Brass
Cable admitido	6-16mm²
Wire flexible	6-16mm ²
Diámetro exterior de cable admisible	-
Permissible cable outside diameter	-
Longitud del cable	-
Cable length	-
Grado de protección	IP67
Protection degree	IP67
Resistencia al impacto	IK08
Impact resistance	IK08
Ensayo de bola	125°C soporte partes activas/ 70°C otras partes
Ball pressure test	125°C supports active parts/ 70°C other parts
Resistencia al aislamiento	>10MΩ@500Vdc
Insulating resistance	>10MΩ@500Vdc
Rigidez dieléctrica (kV)	2.5
Dielectric Strength (kV)	2.5
Temperatura de funcionamiento	-25°C/ 40°C
Operating temperature	-25°C/ 40°C
Temperatura de resistencia	-25°C/ 70°C
Temperature resistance	-25°C/ 70°C



	63A		
Poles	3	4	5
A	100	100	100
B	100	100	100
C	80	80	80
D	80	80	80
F	100	100	100
G	28	28	28

DATOS LOGÍSTICOS LOGISTICS

Unidad mínima de venta	
Minimum sales unit	
EAN Unitario	
EAN Unit	
Cantidad estuche	
Quantity inner box	
EAN Estuche	
EAN Inner box	
Cantidad caja	
Quantity master box	
EAN Caja	
EAN Master box	
Partida arancelaria	
HS code	

NORMATIVAS Y CERTIFICACIONES APPLIED AND CERTIFICATIONS

Normativa	IEC/EN 60309-1, IEC/EN 60309-2
Applied	IEC/EN 60309-1, IEC/EN 60309-2
Directiva baja tensión	Low Voltage Directive 2014/35/UE
Low Voltage Directive	Low Voltage Directive 2014/35/UE
Directiva Rohs	RoHS 2011/65/UE and modifications
Rohs Directive	RoHS 2011/65/UE and modifications
Certificado de producto	
Product certificate	

