

DATOS TÉCNICOS TECHNICAL DATA

Referencia de producto	3762
Product reference	3762
Descripción	Armario de distribución de empotrar 4(ICP) + 14 módulos IP40 Nuova ICP
Description	Flush-mounted distribution enclosure 4(ICP) + 14 IP40 modules Nuova ICP
Peso neto	0.908
Net weight	0.908
ETIM 9.0	EC000214
Módulos	4(ICP) + 14
Modules	4(ICP) + 14
Enlazable	Sí
Linkable	Yes
Tipo de instalación	Empotrar
Installation	Flush-mounted
Compatible carril DIN	Sí
Compatible with DIN Rail	Yes
Puerta	Opaca
Door	Opaque
Ángulo apertura puerta (°)	90
Opening angle (°)	90
Precintable	Sí
Sealable	Yes
Uso	Interior
Use	Indoor
Componentes incorporados	Carril DIN 35mm-Tornillos fijación-3400B
Built-in components	DIN rail 35mm-Fixing screws
Accesorios	RG-04/SPTB-12/3300/3400B/3500
Optional accessories	RG-04/SPTB-12/3300/3400B/3500
Rigidez dieléctrica (kV)	3.75
Dielectric strength (kV)	3.75
Tensión de impulso (kV)	4
Impulse withstand voltage (kV)	4
Clase de aislamiento	Clase II
Insulation Class	Class II
Intensidad cortocircuito (kA)	10
Rated current	10
Capacidad de disipación térmica (W)	34
Thermal power dissipation capability	34
Grado de protección IP	IP40
IP Protection Degree	IP40
Resistencia al impacto IK	IK08
Impact Resistance IK	IK08
Material	ABS
Material	ABS
Color	Blanco
Colour	White
RAL	9003
Ensayo hilo incandescente	650°C
Glow wire test	650°C
Ensayo de bola	70°C
Ball pressure test	70°C
Material libre de halógenos	Sí
Halogen free materials	Yes
Resistencia UV / UV Resistant	- / -
Temperatura de funcionamiento (°C)	-25°C/ 40°C
Ambient operating temperatura range	-25°C/ 40°C
Temperatura de transporte y almacenaje	-25°C/ 70°C
Transport and storage	-25°C/ 70°C
Alto / Height	215
Ancho / Width	445
Profundo / Depth	110
Alto interior / Height inside	180
Ancho interior / Width inside	105
Profundo interior / Depth inside	75
Entrada superior / Top entries	4
Entrada inferior / Bottom entries	4
Entrada lateral / Lateral entries	2
Entrada posterior / Back entries	-



NORMATIVAS Y CERTIFICACIONES APPLIED AND CERTIFICATIONS

Normativa	EN 60670-1,EN 60670-24,IEC 61439-1,IEC 61439-3,IEC 62208
Applied	EN 60670-1,EN 60670-24,IEC 61439-1,IEC 61439-3,IEC 62208
Directiva baja tensión	Low Voltage Directive 2014/35/UE
Low Voltage Directive	Low Voltage Directive 2014/35/UE
Directiva Rohs	-
Rohs Directive	-
Certificado de producto	-
Product certificate	-
Reglamento electrotécnico baja tensión	REBT 2002
Low voltageelectrotechnical regulations	REBT 2002

