

## DATOS TÉCNICOS TECHNICAL DATA

|                                               |                                                                                                                           |
|-----------------------------------------------|---------------------------------------------------------------------------------------------------------------------------|
| <b>Referencia de producto</b>                 | <b>3958.4</b>                                                                                                             |
| Product reference                             | 3958.4                                                                                                                    |
| <b>Descripción</b>                            | <b>Envolvente cableada 9 módulos con 1 toma 3P+N+T 16A 400V + 2 tomas schuko + 1 toma 3P+N+T 32A 400V IP54 AcquaCOMBI</b> |
| Description                                   | AcquaCOMBI 9-module wired enclosure with 1 3P+N+E 16A 400V socket + 2 Schuko sockets + 1 3P+N+E 32A 400V socket IP54      |
| <b>Peso neto (Kg)</b>                         | <b>1.918</b>                                                                                                              |
| Net weight (Kg)                               | 1.918                                                                                                                     |
| <b>ETIM 9.0</b>                               | <b>EC000379</b>                                                                                                           |
| <b>Módulos</b>                                | <b>9</b>                                                                                                                  |
| Modules                                       | 9                                                                                                                         |
| <b>Enlazable</b>                              | <b>No</b>                                                                                                                 |
| Linkable                                      | No                                                                                                                        |
| <b>Tipo de instalación</b>                    | <b>Superficie</b>                                                                                                         |
| Installation                                  | Surface                                                                                                                   |
| <b>Compatible carril DIN</b>                  | <b>Sí</b>                                                                                                                 |
| Compatible with DIN Rail                      | Yes                                                                                                                       |
| <b>Puerta</b>                                 | <b>Transparente</b>                                                                                                       |
| Door                                          | Transparent                                                                                                               |
| <b>Ángulo apertura puerta (°)</b>             | <b>-</b>                                                                                                                  |
| Opening angle (°)                             | -                                                                                                                         |
| <b>Precintable</b>                            | <b>-</b>                                                                                                                  |
| Sealable                                      | -                                                                                                                         |
| <b>Uso</b>                                    | <b>Interior</b>                                                                                                           |
| Use                                           | Indoor                                                                                                                    |
| <b>Componentes incorporados</b>               | <b>1x3P+T+N 16A + 1x3P+T+N 32A + 2x2P+TTL 16A- Carril DIN-Tapones para obtener el grado IP65</b>                          |
| Built-in components                           | 1x3P+T+N 16A + 1x3P+T+N 32A + 2x2P+TTL 16A-Rail                                                                           |
| <b>Accesorios</b>                             | <b>-</b>                                                                                                                  |
| Optional accessories                          | -                                                                                                                         |
| <b>Rigidez dieléctrica (kV)</b>               | <b>2.5</b>                                                                                                                |
| Dielectric strength (kV)                      | 2.5                                                                                                                       |
| <b>Tensión de impulso (kV)</b>                | <b>-</b>                                                                                                                  |
| Impulse withstand voltage (kV)                | -                                                                                                                         |
| <b>Clase de aislamiento</b>                   | <b>Clase II</b>                                                                                                           |
| Insulation Class                              | Class II                                                                                                                  |
| <b>Intensidad cortocircuito (kA)</b>          | <b>-</b>                                                                                                                  |
| Rated current                                 | -                                                                                                                         |
| <b>Capacidad de disipación térmica (W)</b>    | <b>18</b>                                                                                                                 |
| Thermal power dissipation capability          | 18                                                                                                                        |
| <b>Grado de protección IP</b>                 | <b>IP54</b>                                                                                                               |
| IP Protection Degree                          | IP54                                                                                                                      |
| <b>Resistencia al impacto IK</b>              | <b>IK08</b>                                                                                                               |
| Impact Resistance IK                          | IK08                                                                                                                      |
| <b>Material</b>                               | <b>ABS+Puerta PC</b>                                                                                                      |
| Material                                      | ABS + PC Door                                                                                                             |
| <b>Color</b>                                  | <b>Gris</b>                                                                                                               |
| Colour                                        | Grey                                                                                                                      |
| <b>RAL</b>                                    | <b>7035</b>                                                                                                               |
| <b>Ensayo hilo incandescente</b>              | <b>850°C soportes partes activas / 650°C otras partes</b>                                                                 |
| Glow wire test                                | 850°C supports active parts / 650°C other parts                                                                           |
| <b>Ensayo de bola</b>                         | <b>-</b>                                                                                                                  |
| Ball pressure test                            | -                                                                                                                         |
| <b>Material libre de halógenos</b>            | <b>Sí</b>                                                                                                                 |
| Halogen free materials                        | Yes                                                                                                                       |
| <b>Resistencia UV / UV Resistant</b>          | <b>Sí / Yes</b>                                                                                                           |
| <b>Temperatura de funcionamiento (°C)</b>     | <b>-</b>                                                                                                                  |
| Ambient operating temperatura range           | -                                                                                                                         |
| <b>Temperatura de transporte y almacenaje</b> | <b>-</b>                                                                                                                  |
| Transport and storage                         | -                                                                                                                         |
| <b>Alto / Height</b>                          | <b>350</b>                                                                                                                |
| <b>Ancho / Width</b>                          | <b>215</b>                                                                                                                |
| <b>Profundo / Depth</b>                       | <b>150</b>                                                                                                                |
| <b>Alto interior / Height inside</b>          | <b>350</b>                                                                                                                |
| <b>Ancho interior / Width inside</b>          | <b>215</b>                                                                                                                |
| <b>Profundo interior / Depth inside</b>       | <b>150</b>                                                                                                                |
| <b>Entrada superior / Top entries</b>         | <b>-</b>                                                                                                                  |
| <b>Entrada inferior / Bottom entries</b>      | <b>-</b>                                                                                                                  |
| <b>Entrada lateral / Lateral entries</b>      | <b>-</b>                                                                                                                  |
| <b>Entrada posterior / Back entries</b>       | <b>-</b>                                                                                                                  |

Cajas 9 módulos IP44 / Boxes 9 modules IP44

| Ref. / Ref. | Tomas - IP44 |        |        | IP54 |        |        |
|-------------|--------------|--------|--------|------|--------|--------|
|             | 3P+T         | 3P+T+N | SCHUKO | 3P+T | 3P+T+N | 3P+T+N |
| 3958.1      | 1            | 2      | 2      | 1    | 2      | 2      |
| 3958.2      | 2            | 2      | 2      | 2    | 2      | 2      |
| 3958.3      | 2            | 2      | 2      | 2    | 2      | 2      |
| 3958.4      | 2            | 2      | 2      | 2    | 2      | 2      |
| 3958.5      | 2            | 2      | 2      | 2    | 2      | 2      |

Names / Nombres: EN60529  
 Other configurations consult us / For other configurations, please contact us.

Ref. Item 3958      Ref. Item 3958.1

## NORMATIVAS Y CERTIFICACIONES APPLIED AND CERTIFICATIONS

|                                               |                                                   |
|-----------------------------------------------|---------------------------------------------------|
| <b>Normativa</b>                              | <b>IEC/EN 62208,IEC/EN 61439-1,IEC/EN 61439-3</b> |
| Applied                                       | IEC/EN 62208,IEC/EN 61439-1IEC/EN 61439-3         |
| <b>Directiva baja tensión</b>                 | <b>Low Voltage Directive 2014/35/UE</b>           |
| Low Voltage Directive                         | Low Voltage Directive 2014/35/UE                  |
| <b>Directiva Rohs</b>                         | -                                                 |
| Rohs Directive                                | -                                                 |
| <b>Certificado de producto</b>                | -                                                 |
| Product certificate                           | -                                                 |
| <b>Reglamento electrotécnico baja tensión</b> | -                                                 |
| Low voltage electrotechnical regulations      | -                                                 |

