

DATOS TÉCNICOS
TECHNICAL DATA

Referencia de producto	5103-N
Product reference	5103-N
Descripción	Doble interruptor de superficie estanco 10A 250V IP54 Serie Pool 54
Description	Double waterproof surface switch 10A 250V IP54 Serie Pool 54 Series
Peso neto (Kg)	0.082
Net weight (Kg)	0.082
ETIM 9.0	EC000029
Intensidad (A)	10
Intensity (A)	10
Voltaje (V)	250
Voltage (V)	250
Frecuencia (Hz)	(50/60Hz)
Frequency (Hz)	(50/60Hz)
Material	Termoplástico
Material	Thermoplastic
Color	Negro
Colour	Black
Grado de protección IP	IP54
Degree of protection IP	IP54
Uso	Exterior
Use	Outdoor
Tipo de instalación	Superficie
Type of installation	Surface
Resistencia de aislamiento	5MΩ@500Vdc
Insulation resistance	5MΩ@500Vdc
Regidez dieléctrica (kV)	2
Dielectric strength (kV)	2
Hilo incandescente	850°C soporte partes activas/ 650°C otras partes
Glow wire	850°C support active parts/ 650°C other parts
Ensayo de bola	125°C soporte partes activas/ 70°C otras partes
Ball pressure test	125°C supports active parts/ 70°C other parts
Alto / Height	65
Ancho / Width	75
Profundo / Depth	46



DATOS LOGÍSTICOS
LOGISTICS

Unidad mínima de venta	12
Minimum sales unit	12
EAN Unitario	8429760820802
EAN Unit	8429760820802
Cantidad estuche	12
Quantity inner box	12
EAN Estuche	18429760820809
EAN Inner box	18429760820809
Cantidad caja	-
Quantity master box	-
EAN Caja	-
EAN Master box	-
Partida arancelaria	85365080
HS code	85365080

NORMATIVAS Y CERTIFICACIONES
APPLIED AND CERTIFICATIONS

Normativa	EN 60669-1
Applied	EN 60669-1
Directiva baja tensión	Low Voltage Directive 2014/35/UE
Low Voltage Directive	Low Voltage Directive 2014/35/UE
Directiva Rohs	RoHS 2011/65/UE and modifications
Rohs Directive	RoHS 2011/65/UE and modifications
Certificado de producto	-
Product certificate	-
Reglamento electrotécnico baja tensión	REBT 2002
Low voltage electrotechnical regulations	REBT 2002