

DATOS TÉCNICOS TECHNICAL DATA

Referencia de producto	6409
Product reference	6409
Descripción	Envolvente cableada 6 módulos con 1 toma 2P+T 16A 220V + 1 toma schuko + 1 toma 3P+N+T 32A 400V IP54 AcquaCOMBI
Description	AcquaCOMBI 6-module wired enclosure with 1 2P+E 16A 220V socket + 1 Schuko socket + 1 3P+N+E 32A 400V IP54 socket
Peso neto (Kg)	1.7499999
Net weight (Kg)	1.7499999
ETIM 9.0	EC000379
Módulos	6
Modules	6
Enlazable	No
Linkable	No
Tipo de instalación	Superficie
Installation	Surface
Compatible carril DIN	Sí
Compatible with DIN Rail	Yes
Puerta	Transparente
Door	Transparent
Ángulo apertura puerta (°)	-
Opening angle (°)	-
Precintable	-
Sealable	-
Uso	Interior
Use	Indoor
Componentes incorporados	1x2P+T 16A + 1x2P+TTL 16A + 1x3P+T+N 32A-Carril DIN-Tapones para obtener el grado IP65
Built-in components	1x2P+E 16A + 1x2P+TTL 16A + 1x3P+T+N 32A - DIN Rail
Accesorios	-
Optional accessories	-
Rigidez dieléctrica (kV)	2.5
Dielectric strength (kV)	2.5
Tensión de impulso (kV)	-
Impulse withstand voltage (kV)	-
Clase de aislamiento	Clase II
Insulation Class	Class II
Intensidad cortocircuito (kA)	-
Rated current	-
Capacidad de disipación térmica (W)	12
Thermal power dissipation capability	12
Grado de protección IP	IP54
IP Protection Degree	IP54
Resistencia al impacto IK	IK08
Impact Resistance IK	IK08
Material	ABS+Puerta PC
Material	ABS + PC Door
Color	Gris
Colour	Grey
RAL	7035
Ensayo hilo incandescente	850°C soportes partes activas / 650°C otras partes
Glow wire test	850°C supports active parts / 650°C other parts
Ensayo de bola	-
Ball pressure test	-
Material libre de halógenos	Sí
Halogen free materials	Yes
Resistencia UV / UV Resistant	Sí / Yes
Temperatura de funcionamiento (°C)	-
Ambient operating temperatura range	-
Temperatura de transporte y almacenaje	-
Transport and storage	-
Alto / Height	490
Ancho / Width	125
Profundo / Depth	107
Alto interior / Height inside	490
Ancho interior / Width inside	125
Profundo interior / Depth inside	107
Entrada superior / Top entries	1
Entrada inferior / Bottom entries	1
Entrada lateral / Lateral entries	-
Entrada posterior / Back entries	-

Cajas 6 módulos IP44 / Boxes 6 modules IP44

Ref. / Ref.	3 Tomas				IP44		
	2P+T	2P+N	2P+N+T	2P+N+TTL	2P+T	2P+N	2P+N+T
6401	1	1	1	1	1	1	1
6402	1	1	1	1	1	1	1
6403	1	1	1	1	1	1	1
6404	1	1	1	1	1	1	1
6405	1	1	1	1	1	1	1
6406	1	1	1	1	1	1	1
6407	1	1	1	1	1	1	1
6408	1	1	1	1	1	1	1
6409	1	1	1	1	1	1	1
6410	1	1	1	1	1	1	1

Norma / Norm: EN 60228. Otras configuraciones consultar / For other configurations, please contact us.



DATOS LOGÍSTICOS LOGISTICS

Unidad mínima de venta	1
Minimum sales unit	1
EAN Unitario	8429760219415
EAN Unit	8429760219415
Cantidad estuche	1
Quantity inner box	1
EAN Estuche	-
EAN Inner box	-
Cantidad caja	-
Quantity master box	-
EAN Caja	-
EAN Master box	-
Partida arancelaria	85371098
HS code	85371098

NORMATIVAS Y CERTIFICACIONES APPLIED AND CERTIFICATIONS

Normativa	IEC/EN 62208, IEC/EN 61439-1, IEC/EN 61439-3, UNE 20315-1-1, UNE 20315-1-2
Applied	IEC/EN 62208, IEC/EN 61439-1, IEC/EN 61439-3, UNE 20315-1-1, UNE 20315-1-2
Directiva baja tensión	Low Voltage Directive 2014/35/UE
Low Voltage Directive	Low Voltage Directive 2014/35/UE
Directiva Rohs	-
Rohs Directive	-
Certificado de producto	-
Product certificate	-
Reglamento electrotécnico baja tensión	-
Low voltage electrotechnical regulations	-

DIMENSIONES | DIMENSIONS

