

DATOS TÉCNICOS TECHNICAL DATA

Referencia de producto	6510
Product reference	6510
Descripción	Envolvente cableada 8 módulos con 1 tomas 2P+T 16A 220V + 1 toma 3P+T 16A 400V + 1 toma schuko IP54 AcquaCOMBI
Description	8-module wired enclosure with 1 2P+E 16A 220V socket + 1 3P+E 16A 400V socket + 1 Schuko socket IP54 AcquaCOMBI
Peso neto (Kg)	2.7299997
Net weight (Kg)	2.7299997
ETIM 9.0	EC000379
Módulos	8
Modules	8
Enlazable	Sí
Linkable	Yes
Tipo de instalación	Superficie
Installation	Surface
Compatible carril DIN	Sí
Compatible with DIN Rail	Yes
Puerta	Transparente
Door	Transparent
Ángulo apertura puerta (°)	-
Opening angle (°)	-
Precintable	-
Sealable	-
Uso	Interior
Use	Indoor
Componentes incorporados	2P+T 16A + 3P+T 16A + 2x2P+TTL 16A-Carril DIN- Tapones para obtener el grado IP65
Built-in components	2P+T 16A + 3P+T 16A + 2x2P+TTL 16A - DIN Rail
Accesorios	-
Optional accessories	-
Rigidez dieléctrica (kV)	2.5
Dielectric strength (kV)	2.5
Tensión de impulso (kV)	-
Impulse withstand voltage (kV)	-
Clase de aislamiento	Clase II
Insulation Class	Class II
Intensidad cortocircuito (kA)	-
Rated current	-
Capacidad de disipación térmica (W)	16
Thermal power dissipation capability	16
Grado de protección IP	IP54
IP Protection Degree	IP54
Resistencia al impacto IK	IK08
Impact Resistance IK	IK08
Material	ABS+Puerta PC
Material	ABS + PC Door
Color	Gris
Colour	Grey
RAL	7035
Ensayo hilo incandescente	850°C soportes partes activas / 650°C otras partes
Glow wire test	850°C supports active parts / 650°C other parts
Ensayo de bola	-
Ball pressure test	-
Material libre de halógenos	Sí
Halogen free materials	Yes
Resistencia UV / UV Resistant	Sí / Yes
Temperatura de funcionamiento (°C)	-
Ambient operating temperatura range	-
Temperatura de transporte y almacenaje	-
Transport and storage	-
Alto / Height	500
Ancho / Width	230
Profundo / Depth	155
Alto interior / Height inside	500
Ancho interior / Width inside	230
Profundo interior / Depth inside	155
Entrada superior / Top entries	2
Entrada inferior / Bottom entries	2
Entrada lateral / Lateral entries	2
Entrada posterior / Back entries	-

Cajas 8 módulos IP44 / Boxes 8 modules IP44

Ref. Item	4 Terminals				3P+N		
	2P+T 220V	3P+T 400V	3P+T+N 400V	3P+TTL 220V	2P+T 220V	3P+N 400V	3P+N+T+N 400V
6501	—	—	—	4	—	—	—
6502	2	—	—	2	—	—	—
6503	2	1	—	1	—	—	—
6504	—	1	—	2	—	1	—
6505	—	2	—	2	—	—	—
6506	—	—	—	2	—	2	—
6507	—	—	2	2	—	—	—
6508	—	—	—	2	—	—	2
6509	—	—	1	2	—	—	1
6510	1	1	—	2	—	—	—
6511	2	—	2	—	—	—	—
6512	2	—	—	—	—	—	2

Nota / Notes: EN60528. Check configurations carefully. For other configurations, please contact us.

Ref. Item 3961

Ref. Item 6504

DATOS LOGÍSTICOS
LOGISTICS

Unidad mínima de venta	1
Minimum sales unit	1
EAN Unitario	8429760212447
EAN Unit	8429760212447
Cantidad estuche	1
Quantity inner box	1
EAN Estuche	-
EAN Inner box	-
Cantidad caja	-
Quantity master box	-
EAN Caja	-
EAN Master box	-
Partida arancelaria	85371098
HS code	85371098

NORMATIVAS Y CERTIFICACIONES

Normativa	IEC/EN 62208,IEC/EN 61439-1,IEC/EN 61439-3
Applied	IEC/EN 62208,IEC/EN 61439-1IEC/EN 61439-3
Directiva baja tensión	Low Voltage Directive 2014/35/UE
Low Voltage Directive	Low Voltage Directive 2014/35/UE
Directiva Rohs	-
Rohs Directive	-
Certificado de producto	-
Product certificate	-
Reglamento electrotécnico baja tensión	-
Low voltage electrotechnical regulations	-

DIMENSIONES | DIMENSIONS

