

DATOS TÉCNICOS

TECHNICAL DATA

Referencia de producto	9/416
Product reference	9/416
Descripción	Base Múltiple 6 salidas sin cable
Description	Multiplesocket 6 Schuko outlets without cable
Peso neto (Kg)	0.282
Net weight	0.282
ETIM 9.0	EC000030
Intensidad (A)	16
IEC-Amperage (A)	16
Polos	2P+T
Poles	2P+T
Frecuencia	(50/60Hz)
Frequency	(50/60Hz)
Voltaje (V)	250
Voltage (V)	250
Color	Blanco
Colour	White
RAL	9003
Interruptor	No
Switch	No
Material	Termoplástico
Material	Thermoplastic
Grado de protección	IP20
Protection degree	IP20
Resistencia al impacto	IK07
Impact resistance	IK07
Uso	Interior
Use	Indoor
Prueba hilo incandescente	850°C soportes partes activas / 650°C otras partes
Glow wire test	850°C supports active parts / 650°C other parts
Ensayo de bola	125°C Partes activas soportes / 70°C otras partes
Ball pressure test	125°C active parts supports / 70°C other parts
Resistencia al aislamiento	5MΩ@500Vdc
Insulating resistance	5MΩ@500Vdc
Potencia max.	3680
Max. power	3680
Rigidez dieléctrica (kV)	2
Dielectric Strenght (kV)	2
Temperatura de funcionamiento	-5°C/ 40°C
Operating temperature	-5°C/ 40°C
Temperatura de transporte y almacenaje	-25°C/ 70°C
Transport and storage temperature	-25°C/ 70°C
Alto / High	100
Ancho / Width	160
Profundo / Deep	41



DATOS LOGÍSTICOS

LOGISTICS

Unidad mínima de venta	5
Minimum sales unit	5
EAN Unitario	8429760846055
EAN Unit	8429760846055
Cantidad estuche	5
Quantity inner box	5
EAN Estuche	18429760846052
EAN Inner box	18429760846052
Cantidad caja	30
Quantity master box	30
EAN Caja	28429760846059
EAN Master box	28429760846059
Partida arancelaria	85366990
HS code	85366990

NORMATIVAS Y CERTIFICACIONES

APPLIED AND CERTIFICATIONS

Normativa	UNE 20315-1-1, UNE 20315-1-2, IEC 60884-1 CEE7 SS III
Applied	UNE 20315-1-1, UNE 20315-1-2, IEC 60884-1 CEE7 SS III
Directiva baja tensión	-
Low Voltage Directive	-
Directiva Rohs	RoHS 2011/65/UE and modifications
Rohs Directive	RoHS 2011/65/UE and modifications
Certificado de producto	-
Product certificate	-