

DATOS TÉCNICOS TECHNICAL DATA

Referencia de producto	9210
Product reference	9210
Descripción	Pulsador de empotrar 10A 250V Aluminio Serie Habitat 15
Description	Flush-mounted push button 10A 250V Aluminum Habitat 15 Series
Peso neto (Kg)	0.102
Net weight (Kg)	0.102
ETIM 9.0	EC000029
Intensidad (A)	10
Intensity (A)	10
Voltaje (V)	250
Voltage (V)	250
Frecuencia (Hz)	(50/60Hz)
Frequency (Hz)	(50/60Hz)
Material	Termoplástico
Material	Thermoplastic
Color	Aluminio
Colour	Aluminium
Grado de protección IP	IP20
Degree of protection IP	IP20
Uso	Interior
Use	Indoor
Tipo de instalación	Empotrar
Type of installation	Flush-mounted
Resistencia de aislamiento	5MΩ@500Vdc
Insulation resistance	5MΩ@500Vdc
Regidez dieléctrica (kV)	2
Dielectric strength (kV)	2
Hilo incandescente	850°C soporte partes activas/ 650°C otras partes
Glow wire	850°C support active parts/ 650°C other parts
Ensayo de bola	125°C soporte partes activas/ 70°C otras partes
Ball pressure test	125°C supports active parts/ 70°C other parts
Alto / Height	86
Ancho / Width	86
Profundo / Depth	45



DATOS LOGÍSTICOS LOGISTICS

Unidad mínima de venta	6
Minimum sales unit	6
EAN Unitario	8429760276074
EAN Unit	8429760276074
Cantidad estuche	6
Quantity inner box	6
EAN Estuche	8429760286073
EAN Inner box	8429760286073
Cantidad caja	180
Quantity master box	180
EAN Caja	8429760296072
EAN Master box	8429760296072
Partida arancelaria	85365080
HS code	85365080

NORMATIVAS Y CERTIFICACIONES APPLIED AND CERTIFICATIONS

Normativa	EN 60669-1
Applied	EN 60669-1
Directiva baja tensión	Low Voltage Directive 2014/35/UE
Low Voltage Directive	Low Voltage Directive 2014/35/UE
Directiva Rohs	RoHS 2011/65/UE and modifications
Rohs Directive	RoHS 2011/65/UE and modifications
Certificado de producto	-
Product certificate	-
Reglamento electrotécnico baja tensión	REBT 2002
Low voltage electrotechnical regulations	REBT 2002