

Pipe Clip – Stainless Steel



Applications

- ✓ Securely fastens pipes in domestic and commercial plumbing systems, ensuring reliable water flow and pressure management
- ✓ Hydronic heating systems, providing robust support for pipes while minimising noise transmission
- ✓ HVAC pipework, facilitating efficient installation and maintenance of heating and cooling systems
- ✓ Fire sprinkler systems, maintaining pipe alignment and integrity under high-pressure conditions
- ✓ Mechanical services risers, ensuring vertical pipe stability in multi-storey buildings
- ✓ Mining infrastructure, withstanding harsh environmental conditions and heavy-duty applications

Specification Sheet

Ultramax Code	Clamping / Size Range (mm)	Internal Thread	Steel Band b×s (mm)	EPDM Lining (mm)	Locking Screw	Min. Torque (Nm)	Load Frad (kN)	Box Qty
SSCL15	13 - 14	M8/M10	20 x 1.2	20 x 3.5	M6 x 16	60	1.1	150
SSCL20	15 - 19	M8/M10	20 x 1.2	20 x 3.5	M6 x 16	60	1.1	150
SSCL25	19 - 25	M8/M10	20 x 1.2	20 x 3.5	M6 x 16	60	1.1	100
SSCL28	25 - 30	M8/M10	20 x 1.2	20 x 3.5	M6 x 16	60	1.1	100
SSCL32	32 - 37	M8/M10	20 x 1.2	20 x 3.5	M6 x 16	60	1.1	100
SSCL40	40 - 43	M8/M10	20 x 1.2	20 x 3.5	M6 x 20	60	1.1	50
SSCL50	50 - 56	M8/M10	20 x 1.5	20 x 4.5	M6 x 20	60	1.2	50
SSCL66	60 - 64	M8/M10	20 x 1.5	20 x 4.5	M6 x 20	60	1.2	50
SSCL73	68 - 73	M8/M10	20 x 1.5	20 x 4.5	M6 x 20	60	1.2	50
SSCL80	75 - 80	M8/M10	20 x 1.5	20 x 4.5	M6 x 20	60	1.2	50
SSCL90	83 - 91	M8/M10	20 x 1.5	20 x 4.5	M6 x 20	60	1.2	50
SSCL100	95 - 103	M8/M10	25 x 2.0	25 x 4.5	M8 x 25	70	1.5	25
SSCL110	108 - 114	M8/M10	25 x 2.0	25 x 4.5	M8 x 25	70	1.5	25
SSCL160	159 - 162	M8/M10	25 x 2.0	25 x 5.5	M8 x 30	70	2.5	20
SSCL168	165 - 168	M8/M10	25 x 2.0	25 x 5.5	M8 x 30	70	2.5	20

Description

The Ultramax Stainless Steel Acoustic Pipe Clip (M8/M10 dual thread nut) is a range of 15 stainless steel acoustic pipe clips supplied under Ultramax codes SSCL15 to SSCL168, covering clamping ranges from 13 mm to 168 mm. The clips are constructed from high-grade stainless steel for corrosion resistance and use a dual thread (M8/M10) boss for flexible installation, with rubber or EPDM lining to reduce vibration and noise transmission. They suit copper, steel, plastic and composite pipe, and integrate with support channel, threaded rod and structural framing.

Features

- ✓ Constructed from high-grade stainless steel for enhanced durability and corrosion resistance
- ✓ Dual thread nut configuration (M8/M10) for versatile installation options
- ✓ Available with rubber or EPDM lining to minimise vibration and noise transmission
- ✓ Designed for compatibility with standard pipe diameters, ensuring a secure fit
- ✓ Single and double clip configurations to accommodate various installation needs
- ✓ Threaded fixing or backplate mounting options for flexible installation methods
- ✓ Vibration-dampening design to reduce wear and prolong system lifespan
- ✓ Compatible with strut and rod supports for easy integration into existing frameworks