6" Steam Series Exhaust Muffler with Relief Valve

U125060



Image for illustration only

Description

The Steam Series Exhaust Muffler with Relief Valve reduces noise from steam exhaust outlets during boiler start-up and testing. It is a lower-cost muffler for temporary duty and is not designed for permanent installation on boilers. Corrosion-resistant materials and epoxy-coated end caps suit high-alkali conditions, and the replaceable elements can be reused. A relief valve sits in the base. It is rated to 125 psi (8.6 bar). This model has a 6" BSP connection and a rated flow of 34,400 scfm.

Features

- For boiler start-up and testing, temporary duty
- Relief valve on the base
- Corrosion-resistant materials with epoxy-coated end caps for high-alkali conditions
- Replaceable elements for reuse
- Peripheral openings disperse exhaust evenly over 360 degrees to reduce exhaust noise

Applications

- Boiler start-up and testing
- Low-pressure food processing and similar applications

Specifications

Ultramax Product Code	U125060
Port Size	6" BSP
Flow (scfm)	34,400
Maximum Working Pressure	125 psi (8.6 bar)
Materials	Corrosion-resistant materials, epoxy-coated end caps
Elements per Unit	4

Not designed for permanent installation on boilers. Do not use where pressure exceeds 125 psi (8.6 bar).

Maximum temperature is not stated by the source. Confirm temperature suitability with Ultramax Systems before ordering.

6" Steam Series Exhaust Muffler with Relief Valve

U125060

Technical Drawing



Dimensions in mm

A (Overall Length) (mm)	785
B (Diameter / Width) (mm)	279