

KENSINGTON

WIXOM COLLECTION

Northern
WIDE PLANK



AS COLOURFUL AS THE BACK STREETS THAT ENTHRALLED THE ELITE, WIXOM COBBLED OAK WIDE PLANK FLOORS DEFINE AN ERA THAT GAVE RISE TO BOTH CREATIVE FREEDOM AND ELEGANT SIMPLICITY. HANDCRAFTED TO EXACTING STANDARDS, EACH PLANK PERSONIFIES A DISTRESSED AGING WITH AN EXTRAORDINARY LOOK AND FEEL. MILLED TO EXACTING STANDARDS, PERFORMANCE AND FUNCTIONALITY ARE SYNONYMOUS WITH THIS EXCLUSIVE OAK FLOOR.

KENSINGTON HAS DEFINING COLOUR STREAKS AND VARIATIONS THAT EXTENUATE ITS DISTINCT BROWN SMOKY TONES.

SPECIFICATIONS

MANUFACTURED:	MADE IN EUROPE
ORIGIN:	EUROPE
SPECIES:	EUROPEAN OAK
GRADE:	CHARACTER
SHADE:	BROWN
SURFACE:	DISTRESSED
EDGES:	MICROBEVELLED (PLANK - LONG SIDES ONLY)
THICKNESS:	20 MM (3/4")
SUBSTRATE:	WBP BALTIC BIRCH PLYWOOD
FINISH:	HARDWAX OIL (UV CURED)
PLANK WIDTHS:	180 MM / 220 MM / 260 MM (7-1/8" / 8-5/8" / 10-1/4")
PLANK LENGTHS:	1950 MM / 2400 MM (76-3/4" / 94-1/2")**
	**WITH SOME NESTED LENGTHS
HERRINGBONE DIMENSIONS:	120 MM X 600 MM (4-3/4" X 23-5/8")
CHEVRON DIMENSIONS:	120 MM X 525 MM (4-3/4" X 20-11/16")
COLOUR VARIATION:	V3 - SUBSTANTIAL VARIATION
CERTIFICATIONS:	



FSC® AVAILABLE UPON REQUEST

MAINTENANCE AND CARE

REFER TO NWP MAINTENANCE & CARE FOR HARDWAX OIL FINISHED WOOD FLOORS.

PROCEDURE	RESIDENTIAL	COMMERCIAL
Initial After Care	Optional application, NWP Specialty Hardwax Oil	Mandatory application, NWP Specialty Hardwax Oil
Regular cleaning	Vacuum, damp mop with NWP Floor Soap	Vacuum, damp mop with NWP Floor Soap (daily if required)

INSTALLATION

TYPE	RECOMMENDATION
Full Glue Down	Yes - Recommended
Nail Down	Yes - With Glue Assist
Floating	Not Recommended
Over Underfloor Heating	Yes - Refer to NWP Radiant Heat Guide

*APPLICATIONS: Floors, Walls and Ceilings.
Stair Treads and Vents Also Available

TECHNICAL PERFORMANCE

ESSENTIAL CHARACTERISTICS PERFORMANCE

Reaction to fire	Cfl-s1
Emission of Formaldehyde	E1 / CARB 2 compliant
Janka Hardness Rating	1,120 lbf (4,980N)
Post Consumer Recycled Content %	0