


# CAPE COD

## ICONIC COLLECTION

**Northern**  
WIDE PLANK



SUMMERS IN MASSACHUSETTS ARE DEFINED BY A HOOKED SANDY PENINSULA DOTTED WITH LIGHTHOUSES. INDIVIDUALLY HAND SANDED, CAPE COD PLANKS BRING THIS MARITIME CHARACTER INTO LIVING SPACES WITH ITS SUBTLE UNEVEN BLEACHED SURFACES, WHITE-FILLED KNOTS, AND WORN, WHITE HUE. YOU CAN ALMOST HEAR THE TALES OF THE SEA.

## SPECIFICATIONS

MANUFACTURED:	MADE IN CANADA
WOOD ORIGIN:	NORTH EASTERN/CENTRAL USA
WOOD SPECIES:	WHITE OAK
GRADE:	AVAILABLE IN CHARACTER OR SELECT
SHADE:	LIGHT
SURFACE:	FOUNDRY
EDGES:	MICROBEVELLED (PLANK - LONG SIDES ONLY)
THICKNESS:	3/4" (20 MM)
SUBSTRATE:	WBP BALTIC BIRCH PLYWOOD
FINISH:	HARDWAX OIL (UV CURED)
PLANK WIDTHS:	7" / 9" / 11" (178 MM / 229 MM / 280 MM)
PLANK LENGTHS:	70" - 141" (1800 MM - 3600 MM)**
	**WITH SOME NESTED LENGTHS
HERRINGBONE DIMENSIONS:	4" X 20" (101.6 MM X 508 MM)
CHEVRON DIMENSIONS:	4" X 16" (101.6 MM X 406.4 MM)
COLOUR VARIATION:	V2 - MODERATE VARIATION
CERTIFICATIONS:	



FSC® AVAILABLE UPON REQUEST

## MAINTENANCE AND CARE

REFER TO NWP MAINTENANCE & CARE FOR HARDWAX OIL FINISHED WOOD FLOORS.

PROCEDURE	RESIDENTIAL	COMMERCIAL
Initial After Care	Optional application, NWP Specialty Hardwax Oil	Mandatory application, NWP Specialty Hardwax Oil
Regular cleaning	Vacuum, damp mop with NWP Floor Soap	Vacuum, damp mop with NWP Floor Soap (daily if required)

## INSTALLATION

TYPE	RECOMMENDATION
Full Glue Down	Yes - Recommended
Nail Down	Yes - With Glue Assist
Floating	Not Recommended
Over Underfloor Heating	Yes - Refer to NWP Radiant Heat Guide

\*APPLICATIONS: Floors, Walls and Ceilings.  
Stair Treads and Vents Also Available

## TECHNICAL PERFORMANCE

ESSENTIAL CHARACTERISTICS PERFORMANCE	
Reaction to fire	ASTM E 648-17 Class II
Emission of Formaldehyde	E1 / CARB 2 compliant
Janka Hardness Rating	1,360 lbf (6,000 N)
Post Consumer Recycled Content %	NA