

# DOVER

## WIXOM COLLECTION

# Northern

## WIDE PLANK



VIRTUALLY NOTHING SAYS NATURAL WOOD LIKE WIXOM PLANED OAK FLOORS. FOLLOWING IN THE FOOTSTEPS OF THE INDUSTRIAL AGE, THESE PLANKS DELIVER A STUNNING LOOK WITH SMOOTHED OUT SURFACES THAT EXPOSE ROUGH GRAIN AND KNOTS, LEAVING A NATURAL YET LIGHTLY DISTRESSED FINISH.

DOVER BRINGS TO LIFE THE AMAZING CLIFFS OF THE ENGLISH COAST WITH COOL TINTS AND SUBTLE WHITE SHADES OF COLOUR.

## SPECIFICATIONS

|                         |                                                      |
|-------------------------|------------------------------------------------------|
| MANUFACTURED:           | MADE IN EUROPE                                       |
| ORIGIN:                 | EUROPE                                               |
| SPECIES:                | EUROPEAN OAK                                         |
| GRADE:                  | CHARACTER                                            |
| SHADE:                  | LIGHT                                                |
| SURFACE:                | PLANED                                               |
| EDGES:                  | MICROBEVELLED (PLANK - LONG SIDES ONLY)              |
| THICKNESS:              | 20 MM (3/4")                                         |
| SUBSTRATE:              | WBP BALTIC BIRCH PLYWOOD                             |
| FINISH:                 | HARDWAX OIL (UV CURED)                               |
| PLANK WIDTHS:           | 180 MM / 220 MM / 260 MM (7-1/8" / 8-5/8" / 10-1/4") |
| PLANK LENGTHS:          | 1950 MM / 2400 MM (76-3/4" / 94-1/2")**              |
|                         | **WITH SOME NESTED LENGTHS                           |
| HERRINGBONE DIMENSIONS: | 120 MM X 600 MM (4-3/4" X 23-5/8")                   |
| CHEVRON DIMENSIONS:     | 120 MM X 525 MM (4-3/4" X 20-11/16")                 |
| COLOUR VARIATION:       | V2 - MODERATE VARIATION                              |
| CERTIFICATIONS:         |                                                      |



FSC® AVAILABLE UPON REQUEST

## MAINTENANCE AND CARE

REFER TO NWP MAINTENANCE & CARE FOR HARDWAX OIL FINISHED WOOD FLOORS.

| PROCEDURE          | RESIDENTIAL                                     | COMMERCIAL                                               |
|--------------------|-------------------------------------------------|----------------------------------------------------------|
| Initial After Care | Optional application, NWP Specialty Hardwax Oil | Mandatory application, NWP Specialty Hardwax Oil         |
| Regular cleaning   | Vacuum, damp mop with NWP Floor Soap            | Vacuum, damp mop with NWP Floor Soap (daily if required) |

## INSTALLATION

| TYPE                    | RECOMMENDATION                        |
|-------------------------|---------------------------------------|
| Full Glue Down          | Yes - Recommended                     |
| Nail Down               | Yes - With Glue Assist                |
| Floating                | Not Recommended                       |
| Over Underfloor Heating | Yes - Refer to NWP Radiant Heat Guide |

\*APPLICATIONS: Floors, Walls and Ceilings.  
Stair Treads and Vents Also Available

## TECHNICAL PERFORMANCE

### ESSENTIAL CHARACTERISTICS PERFORMANCE

|                                  |                       |
|----------------------------------|-----------------------|
| Reaction to fire                 | Cfl-s1                |
| Emission of Formaldehyde         | E1 / CARB 2 compliant |
| Janka Hardness Rating            | 1,120 lbf (4,980N)    |
| Post Consumer Recycled Content % | 0                     |