MEUSE

TANNIC

Northern
WIDE PLANK

THE ANCIENT MEUSE RIVER IS AN UNIMPEDED AND ELEGANT FORCE; THIS BALANCE OF STRENGTH AND FLOW IS THE COMMON THREAD WHICH GIVES MEUSE WIDE PLANK ITS NAME—ITS NATURAL LIGHT GREY AND WHITE TONALITY REMINISCENT OF DRIFTWOOD FOUND ALONG RIVERBEDS. MADE FROM GENUINE FRENCH OAK, MEUSE IS A CULMINATION OF BOTH HISTORY AND PROGRESS, EXPERTLY BALANCED FOR A TIMELESS RESULT.

SPECIFICATIONS

MANUFACTURED:	MADE IN CANADA
WOOD ORIGIN:	FRANCE
WOOD SPECIES:	GENUINE FRENCH OAK
TYPE:	ENGINEERED
GRADE:	AVAILABLE IN CHARACTER OR SELECT
SHADE:	LIGHT
SURFACE:	SANDED
EDGES:	MICROBEVELLED (PLANK - LONG SIDES ONLY)
THICKNESS:	20 MM (3/4") WITH 6 MM WEAR LAYER*
CONSTRUCTION:	PURECRAFT - BALANCED HARDWOOD CORE
FINISH:	HARDWAX OIL (UV CURED)
PLANK WIDTHS:	178 MM / 229 MM / 280 MM (7" / 9" / 11")
PLANK LENGTHS:	1750 MM - 2350 MM (69" - 93")**
	**WITH SOME NESTED LENGTHS
HERRINGBONE DIMENSIONS:	101.6 MM X 508 MM (4" X 20")
CHEVRON DIMENSIONS:	101.6 MM X 406.4 MM (4" X 16")
COLOUR VARIATION:	V2 - MODERATE VARIATION
CERTIFICATIONS:	

FSC© AVAILABLE UPON REQUEST

CLEANING AND CARE

REFER TO NWP CLEANING & CARE FOR HARDWAX OIL FINISHED WOOD FLOORS.

PROCEDURE	RESIDENTIAL	COMMERCIAL
Initial After Care	Optional application, NWP Specialty Hardwax Oil	Mandatory application, NWP Specialty Hardwax Oil
Regular cleaning	Vacuum, damp mop with NWP Floor Soap	Vacuum, damp mop with NWP Floor Soap (daily if required)

INSTALLATION

TYPE	RECOMMENDATION
Full Glue Down	Yes - Recommended
Nail Down	Yes - With Glue Assist
Floating	Not Recommended
Over Underfloor Heating	Yes - Refer to NWP Radiant Heat Guide
*APPLICATIONS:	Floors, Walls and Ceilings. Stair Treads and Vents Also Available

TECHNICAL PERFORMANCE

ESSENTIAL CHARACTERISTICS PERFORMANCE	
Reaction to fire	ASTM E 648-17 Class II
Emission of Formaldehyde	E1 / CARB 2 compliant
Janka Hardness Rating	1,360 lbf (6,000 N)
Post Consumer Recycled Content %	NA

5930 LLOYDTOWN-AURORA ROAD, SCHOMBERG ON L0G 1T0 CANADA
NORTHERNWIDEPLANK.CA 877/763/6169