

PALOMAR

ICONIC COLLECTION

Northern

WIDE PLANK



INSPIRED BY THE ENERGY OF THE PENINSULAR MOUNTAINS IN NORTHERN SAN DIEGO, PALOMAR IS MADE FOR THOSE WHO CRAVE AN EARTHY, RUGGED EXPRESSION OF CALIFORNIA CHARM. SANDED BY HAND, BLEACHED AND BRUSHED WITH CARE, EACH PLANK FEELS GRACIOUSLY AGED AND WARM. WHETHER A TRADITIONAL OR MID-CENTURY DESIGN, PALOMAR IS ENDLESSLY VERSATILE AND UNDENIABLY COZY.

DUE TO THE NATURAL BEAUTY OF REAL WOOD, PRODUCT IMAGES AND SAMPLES DO NOT SHOW ALL THE VARIATIONS OF COLOUR, GRAIN AND CHARACTER. TO ENSURE THIS PRODUCT IS THE PERFECT MATCH FOR YOUR PROJECT, PLEASE CONSULT WITH A NORTHERN WIDE PLANK REPRESENTATIVE.

MAINTENANCE AND CARE

REFER TO NWP MAINTENANCE & CARE FOR HARDWAX OIL FINISHED WOOD FLOORS.

PROCEDURE	RESIDENTIAL	COMMERCIAL
Initial After Care	Optional application, NWP Specialty Hardwax Oil	Mandatory application, NWP Specialty Hardwax Oil
Regular cleaning	Vacuum, damp mop with NWP Floor Soap	Vacuum, damp mop with NWP Floor Soap (daily if required)

INSTALLATION

TYPE	RECOMMENDATION
Full Glue Down	Yes - Recommended
Nail Down	Yes - With Glue Assist
Floating	Not Recommended
Over Underfloor Heating	Yes - Refer to NWP Radiant Heat Guide

*APPLICATIONS: Floors, Walls and Ceilings.
Stair Treads and Vents Also Available

SPECIFICATIONS

MANUFACTURED:	MADE IN CANADA
WOOD ORIGIN:	NORTH EASTERN/CENTRAL USA
WOOD SPECIES:	WHITE OAK
GRADE:	CHARACTER
SHADE:	LIGHT
SURFACE:	FOUNDRY
EDGES:	MICROBEVELLED (PLANK - LONG SIDES ONLY)
THICKNESS:	3/4" (20 MM)
SUBSTRATE:	WBP BALTIC BIRCH PLYWOOD
FINISH:	HARDWAX OIL (UV CURED)
PLANK WIDTHS:	7" / 9" / 11" (178 MM / 229 MM / 280 MM)
PLANK LENGTHS:	70" - 141" (1800 MM - 3600 MM)**
	**WITH SOME NESTED LENGTHS
HERRINGBONE DIMENSIONS:	4" X 20" (101.6 MM X 508 MM)
CHEVRON DIMENSIONS:	4" X 16" (101.6 MM X 406.4 MM)
COLOUR VARIATION:	V2 - MODERATE VARIATION
CERTIFICATIONS:	



The mark of responsible forestry

FSC® AVAILABLE UPON REQUEST

TECHNICAL PERFORMANCE

ESSENTIAL CHARACTERISTICS PERFORMANCE	
Reaction to fire	ASTM E 648-17 Class II
Emission of Formaldehyde	E1 / CARB 2 compliant
Janka Hardness Rating	1,360 lbf (6,000 N)
Post Consumer Recycled Content %	NA