

SANTENAY

TANNIC

Northern
WIDE PLANK



AUTHENTICITY PERMEATES BOTH SANTENAY WIDE PLANK AND THE REGION FROM WHICH ITS NAME DERIVES; CHARACTERIZED BY A LIGHT, NATURAL FINISH, THESE GENUINE FRENCH OAK PLANKS ARE A TRIBUTE TO THE UNDERSTATED BEAUTY OF THE EVERYDAY. LIKE THE RUSTIC STYLE THAT THIS WINE REGION IS KNOWN FOR, SANTENAY INVITES YOU TO SIT AND RELAX WITH ITS FAMILIAR WARMTH.

SPECIFICATIONS

MANUFACTURED:	MADE IN CANADA
WOOD ORIGIN:	FRANCE
WOOD SPECIES:	GENUINE FRENCH OAK
TYPE:	ENGINEERED
GRADE:	AVAILABLE IN CHARACTER OR SELECT
SHADE:	LIGHT
SURFACE:	SANDED
EDGES:	MICROBEVELLED (PLANK - LONG SIDES ONLY)
THICKNESS:	20 MM (3/4") WITH 6 MM WEAR LAYER*
CONSTRUCTION:	PURECRAFT - BALANCED HARDWOOD CORE
FINISH:	HARDWAX OIL (UV CURED)
PLANK WIDTHS:	178 MM / 229 MM / 280 MM (7" / 9" / 11")
PLANK LENGTHS:	1750 MM - 2350 MM (69" - 93")**
	**WITH SOME NESTED LENGTHS
HERRINGBONE DIMENSIONS:	101.6 MM X 508 MM (4" X 20")
CHEVRON DIMENSIONS:	101.6 MM X 406.4 MM (4" X 16")
COLOUR VARIATION:	V2 - MODERATE VARIATION
CERTIFICATIONS:	



Declare.

FSC® AVAILABLE UPON REQUEST

CLEANING AND CARE

REFER TO NWP CLEANING & CARE FOR HARDWAX OIL FINISHED WOOD FLOORS.

PROCEDURE	RESIDENTIAL	COMMERCIAL
Initial After Care	Optional application, NWP Specialty Hardwax Oil	Mandatory application, NWP Specialty Hardwax Oil
Regular cleaning	Vacuum, damp mop with NWP Floor Soap	Vacuum, damp mop with NWP Floor Soap (daily if required)

INSTALLATION

TYPE	RECOMMENDATION
Full Glue Down	Yes - Recommended
Nail Down	Yes - With Glue Assist
Floating	Not Recommended
Over Underfloor Heating	Yes - Refer to NWP Radiant Heat Guide

*APPLICATIONS: Floors, Walls and Ceilings.
Stair Treads and Vents Also Available

TECHNICAL PERFORMANCE

ESSENTIAL CHARACTERISTICS PERFORMANCE

Reaction to fire	ASTM E 648-17 Class II
Emission of Formaldehyde	E1 / CARB 2 compliant
Janka Hardness Rating	1,360 lbf (6,000 N)
Post Consumer Recycled Content %	NA