

# SOLO

## DIMENSIONS COLLECTION

**Northern**  
WIDE PLANK



WHEN NOTHING LESS THAN THE EXTRAORDINARY WILL SUFFICE, DIMENSIONS DESIGN SERIES I IGNITES THE INNER EYE, BRINGING YOUR VISION TO LIFE. HANDCRAFTED FROM SLOW GROWN EUROPEAN OAK WITH ITS EXCEPTIONALLY FINE GRAIN PATTERNS, THESE FLOORS ARE THE PERFECT FUSION OF LEGENDARY STRENGTH AND UNCOMMON ELEGANCE. WITH AN URBAN CONTEMPORARY DESIGN APPROACH TO COLOUR AND TREATMENTS IN TREND-SETTING STYLES, DESIGN SERIES I FEATURES LIGHT HARMONIOUS TONES TO DARK FORMAL LOOKS.

HONEY-BROWN COLOUR SHADES CREATE A WARM, LIVELY PRESENCE IN ANY ENVIRONMENT.

## SPECIFICATIONS

MANUFACTURED:	MADE IN CANADA
WOOD ORIGIN:	EUROPE
WOOD SPECIES:	EUROPEAN OAK
GRADE:	AVAILABLE IN CHARACTER OR SELECT
SHADE:	NATURAL
SURFACE:	SANDED
EDGES:	MICROBEVELLED (PLANK - LONG SIDES ONLY)
THICKNESS:	20 MM (3/4")
SUBSTRATE:	WBP BALTIC BIRCH PLYWOOD
FINISH:	HARDWAX OIL (UV CURED)
PLANK WIDTHS:	180 MM / 220 MM / 260 MM (7-1/8" / 8-5/8" / 10-1/4"
PLANK LENGTHS:	1800 MM - 2400 MM (70-7/8" - 94-1/2")**
	**WITH SOME NESTED LENGTHS
HERRINGBONE DIMENSIONS:	120 MM X 600 MM (4-3/4" X 23-5/8")
CHEVRON DIMENSIONS:	120 MM X 525 MM (4-3/4" X 20-11/16")
COLOUR VARIATION:	V1 - SLIGHT VARIATION
CERTIFICATIONS:	



The mark of  
responsible forestry

FSC® AVAILABLE UPON REQUEST

## MAINTENANCE AND CARE

REFER TO NWP MAINTENANCE & CARE FOR HARDWAX OIL FINISHED WOOD FLOORS.

PROCEDURE	RESIDENTIAL	COMMERCIAL
Initial After Care	Optional application, NWP Specialty Hardwax Oil	Mandatory application, NWP Specialty Hardwax Oil
Regular cleaning	Vacuum, damp mop with NWP Floor Soap	Vacuum, damp mop with NWP Floor Soap (daily if required)

## INSTALLATION

TYPE	RECOMMENDATION
Full Glue Down	Yes - Recommended
Nail Down	Yes - With Glue Assist
Floating	Not Recommended
Over Underfloor Heating	Yes - Refer to NWP Radiant Heat Guide

\*APPLICATIONS: Floors, Walls and Ceilings.  
Stair Treads and Vents Also Available

## TECHNICAL PERFORMANCE

ESSENTIAL CHARACTERISTICS PERFORMANCE	
Reaction to fire	ASTM E 648-17 Class II
Emission of Formaldehyde	E1 / CARB 2 compliant
Janka Hardness Rating	1,120 lbf (4,980N)
Post Consumer Recycled Content %	NA