

TIDE

WIXOM COLLECTION

Northern
WIDE PLANK



VIRTUALLY NOTHING SAYS NATURAL WOOD LIKE WIXOM PLANED OAK FLOORS. FOLLOWING IN THE FOOTSTEPS OF THE INDUSTRIAL AGE, THESE PLANKS DELIVER A STUNNING LOOK WITH SMOOTHED OUT SURFACES THAT EXPOSE ROUGH GRAIN AND KNOTS, LEAVING A NATURAL YET LIGHTLY DISTRESSED FINISH.

TIDE HAS A TIMELESS QUALITY WITH LIGHT GREY-BROWN TONES AND AN EQUALLY REFINED FINISH.

SPECIFICATIONS

MANUFACTURED:	MADE IN EUROPE
ORIGIN:	EUROPE
SPECIES:	EUROPEAN OAK
GRADE:	CHARACTER
SHADE:	GREY
SURFACE:	PLANED
EDGES:	MICROBEVELLED (PLANK - LONG SIDES ONLY)
THICKNESS:	20 MM (3/4")
SUBSTRATE:	WBP BALTIC BIRCH PLYWOOD
FINISH:	HARDWAX OIL (UV CURED)
PLANK WIDTHS:	192 MM / 220 MM / 260 MM (7-1/8" / 8-5/8" / 10-1/4")
PLANK LENGTHS:	1950 MM / 2400 MM (76-3/4" / 94-1/2")**
	**WITH SOME NESTED LENGTHS
HERRINGBONE DIMENSIONS:	120 MM X 600 MM (4-3/4" X 23-5/8")
CHEVRON DIMENSIONS:	120 MM X 525 MM (4-3/4" X 20-11/16")
COLOUR VARIATION:	V3 - SUBSTANTIAL VARIATION
CERTIFICATIONS:	



FSC® AVAILABLE UPON REQUEST

MAINTENANCE AND CARE

REFER TO NWP MAINTENANCE & CARE FOR HARDWAX OIL FINISHED WOOD FLOORS.

PROCEDURE	RESIDENTIAL	COMMERCIAL
Initial After Care	Optional application, NWP Specialty Hardwax Oil	Mandatory application, NWP Specialty Hardwax Oil
Regular cleaning	Vacuum, damp mop with NWP Floor Soap	Vacuum, damp mop with NWP Floor Soap (daily if required)

INSTALLATION

TYPE	RECOMMENDATION
Full Glue Down	Yes - Recommended
Nail Down	Yes - With Glue Assist
Floating	Not Recommended
Over Underfloor Heating	Yes - Refer to NWP Radiant Heat Guide

*APPLICATIONS: Floors, Walls and Ceilings.
Stair Treads and Vents Also Available

TECHNICAL PERFORMANCE

ESSENTIAL CHARACTERISTICS PERFORMANCE	
Reaction to fire	Cfl-s1
Emission of Formaldehyde	E1 / CARB 2 compliant
Janka Hardness Rating	1,120 lbf (4,980N)
Post Consumer Recycled Content %	0