

AZUD FBC



Control units that manages the automated self-cleaning sequence of the AZUD HELIX AUTOMATIC filtration equipment, to guarantee a safe and autonomous operation of the system

Technical characteristics

- **No. of filtering stations:** 1 -12 stations
- **Supply voltage:** 220 V AC, 110 V AC y 12 V DC LATCH
- **Languages:** Spanish, english, french and german



Unique selling points



Simplicity

Intuitive and easy programming and operation



Safety

It includes the necessary protection elements for safe and trouble-free operation



Reliability

Efficient and stable long-term operation, with minimum maintenance requirements

Product range AZUD FBC 103-112

	103	112
Model		
No. of filtering stations	1 - 3	4 - 12
Supply voltage	220 or 110 V AC (50/60 Hz)	
Operating voltage	Solenoid valves 24 V AC	
Solenoids	3-way NC. Hydraulic command	
Self-cleaning activation	By time, pressure differential, manual and/or external electrical signal	
Extra output	Included for sustaining valve command. With additional relay, it allows the communication of the self-cleaning status of the equipmen	
Languages	English/Spanish or French/German	

Product range AZUD FBC 109T-209T

	109T	209T
Model		
No. of filtering stations	1 - 9	
Supply voltage	220 or 110 V AC (50/60 Hz)	12 V DC - Batteries 4 x 1,5 V Type D
Operating voltage	Solenoid valves 24 V AC	Solenoid valves 12 V DC LATCH
Solenoids	3-way NC. Hydraulic command	
Self-cleaning activation	By time, pressure differential and/or manual	
Extra output	Included for sustaining valve command. With additional relay, it allows the communication of the self-cleaning status of the equipmen	
Languages	English	

Product range AZUD FBC 101 AA-110 AA

	101 AA	110 AA
Model		
No. of filtering stations	1	2 - 10
Supply voltage	220 or 110 V AC (50/60 Hz)	
Operating voltage	Solenoid valves 24 V AC	
Solenoids	4/2 way. Pneumatic command	
Self-cleaning activation	By time, pressure differential, manual and/or external electrical signal	
Extra output	Included for sustaining valve command. With additional relay, it allows the communication of the self-cleaning status of the equipmen	
Languages	English/Spanish or French/German	

Related products



AZUD HELIX AUTOMATIC FT200 AA





AZUD HELIX AUTOMATIC 200





AZUD HELIX AUTOMATIC 4DCL

