

AZUD FIT



NUT FITTINGS

Nut fittings for thickness dripline

Technical characteristics

- **Connection:** Nut
- **Material:** Polypropylene
- **Designed for:** Heavywall, mediumwall and thickwall dripline thickness
- **Models:** Ø12, Ø16, Ø18, Ø20, Ø22 y Ø23
- **Thickness range:** 0.15 - 1.4 mm / 6 - 55 mil



Unique selling points



Safety

High attachment capacity avoiding disconnection
Ensures watertightness, preventing leaks



Savings

Designed to facilitate insertion of the fitting into the pipe
Quick installation, reducing the labor required



Durability

High mechanical resistance even under extreme working conditions, laboratory tested and with 5 years warranty
UV protection and resistance to irrigation chemicals

Nut fittings - Polypropylene - Heavywall thickness

Representative image	Model	Connection diameter	Thickness range	Un/Box	Un/Bag
		mm	mm		
	Straight connector	18	0.75-1.4	450	50
	Straight connector	20	0.75-1.4	350	50
	Straight connector	23	0.75-1.4	250	50
	Barb-nut straight connector	20-20	0.75-1.4	500	50
	Barb-nut straight connector	23-20	0.75-1.4	450	50
	T-connector	18	0.75-1.4	250	50
	T-connector	20	0.75-1.4	200	50
	T-connector	23	0.75-1.4	150	50
	Offtake connector*	20	0.75-1.4	600	100
	Offtake connector*	23	0.75-1.4	400	100
	Offtake connector for XL grommet	20	0.75-1.4	700	100
	Offtake connector for XL grommet	23	0.75-1.4	500	-
	Mixed connector	18-1/2"	0.75-1.4	600	50
	Mixed connector	18-3/4"	0.75-1.4	500	50

Nut fittings - Polypropylene - Heavywall thickness

Representative image	Model	Connection diameter	Thickness range	Un/Box	Un/Bag
		mm	mm		
	Mixed connector	20-1/2"	0.75-1.4	600	50
	Mixed connector	20-3/4"	0.75-1.4	450	50
	T mixed connector	18-1/2"	0.75-1.4	250	50
	T mixed connector	18-3/4"	0.75-1.4	250	50
	T mixed connector	20-1/2"	0.75-1.4	200	50
	T mixed connector	20-3/4"	0.75-1.4	200	50
	L mixed connector	18-1/2"	0.75-1.4	450	50
	L mixed connector	18-3/4"	0.75-1.4	450	50
	L mixed connector	20-1/2"	0.75-1.4	400	50
	L mixed connector	20-3/4"	0.75-1.4	400	50
	Mixed valve	18-1/2"	0.75-1.4	350	50
	Mixed valve	18-3/4"	0.75-1.4	300	50
	Mixed valve	20-1/2"	0.75-1.4	300	50
	Mixed valve	20-3/4"	0.75-1.4	250	50

Nut fittings - Polypropylene - Heavywall thickness

Representative image	Model	Connection diameter	Thickness range	Un/Box	Un/Bag
		mm	mm		
	Valve	18	0.75-1.4	250	50
	Valve	20	0.75-1.4	200	50
	Valve	23	0.75-1.4	200	50
	End plug	18	0.75-1.4	700	50
	End plug	20	0.75-1.4	650	50
	End plug	23	0.75-1.4	450	50

*For LDPE pipe, Ø18 drill bit recommended

Nut fittings - Polypropylene - Mediumwall/Thinwall thickness

Representative image	Model	Connection diameter	Thickness range	Un/Box	Un/Bag
		mm	mm		
	Straight connector	16	0.15-0.65	800	100
	Straight connector	22	0.15-0.65	300	50
	Barb-nut straight connector	16-16	0.15-0.65	1.000	100
	Barb-nut straight connector	22-20	0.15-0.65	450	50
	Reducing connector	22-16	0.15-0.65	350	50
	T-connector	16	0.15-0.65	250	50
	T-connector	22	0.15-0.65	150	50
	Mixed connector	16-1/2"	0.15-0.65	700	100
	Mixed connector	16-3/4"	0.15-0.65	500	100
	Mixed connector	22-1/2"	0.15-0.65	500	50
	Mixed connector	22-3/4"	0.15-0.65	400	50
	L-connector	16	0.15-0.65	400	50
	L-connector	22	0.15-0.65	250	50
	Offtake connector**	16	0.15-0.65	400	100
	Offtake connector***	22	0.15-0.65	500	100

Nut fittings - Polypropylene - Mediumwall/Thinwall thickness

Representative image	Model	Connection diameter	Thickness range	Un/Box	Un/Bag
		mm	mm		
	Offtake connector with XL grommet*	16	0.15-0.65	300	100
	Offtake connector for XL grommet	22	0.15-0.65	500	-
	T mixed connector	16-1/2"	0.15-0.65	300	50
	T mixed connector	16-3/4"	0.15-0.65	250	50
	T mixed connector	22-1/2"	0.15-0.65	200	50
	T mixed connector	22-3/4"	0.15-0.65	200	50
	L mixed connector	16-1/2"	0.15-0.65	550	50
	L mixed connector	16-3/4"	0.15-0.65	500	50
	L mixed connector	22-1/2"	0.15-0.65	400	50
	L mixed connector	22-3/4"	0.15-0.65	350	50
	Mixed valve	16-1/2"	0.15-0.65	350	50
	Mixed valve	16-3/4"	0.15-0.65	300	50
	Mixed valve	22-1/2"	0.15-0.65	300	50
	Mixed valve	22-3/4"	0.15-0.65	250	50

Nut fittings - Polypropylene - Mediumwall/Thinwall thickness

Representative image	Model	Connection diameter	Thickness range	Un/Box	Un/Bag
		mm	mm		
	Valve	16	0.15-0.65	300	50
	Valve	22	0.15-0.65	200	50
	Barb-nut valve	16-16	0.15-0.65	160	20
	Barb-nut valve	22-20	0.15-0.65	250	50
	Offtake valve for XL grommet**	22	0.15-0.65	350	100
	Offtake valve for XL grommet**	16	0.15-0.65	350	50
	End plug	16	0.15-0.65	200	50
	End plug	22	0.15-0.65	550	50

*For PVC, LDPE and HDPE, drill bit Ø15

**For LDPE pipe, Ø7 punch with extractor

***For LDPE pipe, Ø18 drill bit recommended