

AZUD FIT



PLUS

Safety barbed fittings for thickness dripline

Technical characteristics

- **Connection:** Safety barbed
- **Material:** Acetal
- **Designed for:** Heavywall dripline thickness
- **Models:** Ø16 and Ø20
- **Thickness range:** 0.9- 1.2 mm / 35 - 47mil



Unique selling points



Safety

High attachment capacity avoiding disconnection
Ensures watertightness, preventing leaks



Savings

Designed to facilitate insertion of the fitting into the pipe
Quick installation, reducing the labor required



Durability

High mechanical resistance even under extreme working conditions, laboratory tested and with 5 years warranty
UV protection and resistance to irrigation chemicals

Barbed fittings - Acetal - Heavywall thickness

Representative image	Model	Connection diameter	Thickness range	Un/Box	Un/Bag
		mm	mm		
	Straight connector	16	0.9-1.2	1.800	100
	Straight connector	17	0.9-1.2	1.800	100
	Straight connector	20	0.9-1.2	1.000	100
	Offtake connector*	16	0.9-1.2	2.400	100
	Offtake connector*	20	0.9-1.2	700	100
	Offtake connector with L grommet**	16	0.9-1.2	800	100
	Offtake connector with L grommet**	20	0.9-1.2	600	100
	Offtake connector with XL grommet***	16	0.9-1.2	1.100	100
	Offtake connector with XL grommet***	20	0.9-1.2	800	100
	Offtake connector for XL/B grommet	16	0.9-1.2	800	100
	Offtake connector for XL/B grommet	20	0.9-1.2	600	100
	Offtake connector with B grommet**	16	0.9-1.2	1.000	100
	L-Offtake connector	16	0.9-1.2	600	100
	L-Offtake connector with XL grommet***	16	0.9-1.2	400	100
	T-connector	16	0.9-1.2	800	50

Barbed fittings - Acetal - Heavywall thickness

Representative image	Model	Connection diameter	Thickness range	Un/Box	Un/Bag
		mm	mm		
	L-connector	16	0.9-1.2	600	100
	Cross connector	16	0.9-1.2	500	50
	Reducing connector	20-16	0.9-1.2	1.000	10
	Mixed connector	16-1/2"	0.9-1.2	600	100
	Mixed connector	16-3/4"	0.9-1.2	1.000	100
	T-male thread connector	16-1/2"	0.9-1.2	750	50
	T-male thread connector	16-3/4"	0.9-1.2	600	50
	L-male thread connector	16-1/2"	0.9-1.2	600	100
	L-male thread connector	16-3/4"	0.9-1.2	1.000	100
	Plug ring	16	0.9-1.2	2.000	100
	Plug ring	20	0.9-1.2	1.600	100
	Valve	12	0.9-1.2	400	50
	Valve	16	0.9-1.2	320	20
	Valve	20	0.9-1.2	270	15

*For LDPE pipe, Ø7 punch with extractor

**For PVC and HDPE pipe, Ø16 drill bit

***For PVC pipe, Ø16.5 drill bit and for LDPE and HDPE pipe, Ø16 drill bit

Barbed fittings - Acetal - Heavywall thickness

Representative image	Model	Connection diameter	Thickness range	Un/Box
		mm	mm	
	Y connector male thread	2x16 x 3/4"	0.9-1.2	100
	Y connector male thread	2x20 x 3/4"	0.9-1.2	100
	Star Y connector	16	0.9-1.2	300
	Star Y connector	20	0.9-1.2	100
	Three connector female thread	3x16 x 3/4"	0.9-1.2	50
	Three connector female thread	3x20 x 3/4"	0.9-1.2	50
	Four connector female thread	4x16 x 3/4"	0.9-1.2	50
	Four connector female thread	4x20 x 3/4"	0.9-1.2	50
	Six connector female thread	6x16 x 3/4"	0.9-1.2	40
	Six connector female thread	6x20 x 3/4"	0.9-1.2	30
	T-connector	20	0.9-1.2	100
	T-connector	16 x 20 x 16	0.9-1.2	200
	T-connector	20 x 16 x 20	0.9-1.2	100
	T-connector male thread	20 x 3/4" x 20	0.9-1.2	100
	L-connector male thread	20 x 3/4"	0.9-1.2	100
	Straight connector male thread	20 x 3/4"	0.9-1.2	200