

AZUD FIT



RING FITTINGS

Ring fittings for thickness dripline

Technical characteristics

- **Connection:** Ring
- **Material:** Polypropylene
- **Designed for:** Mediumwall/thickwall dripline thickness
- **Models:** Ø16 and Ø20
- **Thickness range:** 0.15 - 0.80 mm / 6 - 31 mil



Unique selling points



Safety

High attachment capacity avoiding disconnection
Ensures watertightness, preventing leaks



Savings

Designed to facilitate insertion of the fitting into the pipe
Quick installation, reducing the labor required



Durability

High mechanical resistance even under extreme working conditions, laboratory tested and with 5 years warranty
UV protection and resistance to irrigation chemicals

Ring fittings - Polypropylene - Mediumwall/Thinwall thickness

Representative image	Model	Connection diameter	Thickness range	Un/Box	Un/Bag
		mm	mm		
	Straight connector	16	0.15-0.50	1.000	100
	Straight connector	16	0.63-0.80	700	100
	Straight connector	22	0.20-0.65	450	50
	Barb-ring straight connector	16-16	0.15-0.50	1.200	100
	Barb-ring straight connector	16-16	0.63-0.80	1.000	100
	Barb-ring straight connector	22-20	0.20-0.65	600	50
	Reducing connector	22-16	0.15-0.65	600	100
	Offtake connector*	16	0.15-0.50	1.500	100
	Offtake connector***	16	0.63-0.80	1.200	100
	Offtake connector	22	0.20-0.65	700	100
	Offtake connector with L grommet**	16	0.15-0.50	1.300	100
	Offtake connector with L grommet**	16	0.63-0.80	1.000	100
	Offtake connector for XL grommet	22	0.20-0.65	700	100
	T-connector	16	0.15-0.65	350	50
	T-connector	22	0.20-0.65	200	50

Ring fittings - Polypropylene - Mediumwall/Thinwall thickness

Representative image	Model	Connection diameter	Thickness range	Un/Box	Un/Bag
		mm	mm		
	L-connector	16	0.15-0.65	600	100
	L-connector	22	0.20-0.65	350	50
	Mixed connector	16	0.15-0.65	900	100
	Mixed connector	22	0.20-0.65	550	50
	T mixed connector	16	0.15-0.65	350	50
	T mixed connector	22	0.20-0.65	250	50
	L mixed connector	16	0.15-0.65	550	50
	L mixed connector	22	0.20-0.65	450	50
	Ring straight valve	16	0.15-0.65	350	50
	Ring straight valve	22	0.20-0.65	250	50
	Barb-ring straight valve	16-16	0.15-0.65	400	50
	Offtake ring valve for XL grommet	22	0.20-0.65	350	50
	Offtake ring valve for XL grommet	16	0.15-0.65	350	50
	Barb-ring straight valve	22-20	0.20-0.65	250	50
	Ring plug	16	0.15-0.65	1400	100

Ring fittings - Polypropylene - Mediumwall/Thinwall thickness

Representative image	Model	Connection diameter	Thickness range	Un/Box	Un/Bag
		mm	mm		
	Ring plug	22	0.20-0.65	800	100

*For LDPE pipe, Ø7 punch with extractor

**For PVC and HDPE pipe, Ø16 drill bit

***For LDPE pipe, Ø18 drill bit recommended