

AZUD TUB



Heavywall irrigation pipe for irrigation with online dripper or water conduction.

Technical characteristics

- **Expected useful life:** More than 10 years
- **Topography:** Uneven terrain and Flat terrain
- **Type of installation:** Subsurface, On surface and Pots



Unique selling points



Reliability

AZUD manufacturing standard according to ISO 8779

Manufactured from high-quality raw material, laboratory tested UV protection and resistance to irrigation chemicals



Durability

High mechanical resistance to abrasion, rubbing, and impacts, reducing incidents and unscheduled maintenance



Safety

Designed to withstand operating pressure and even occasional pressure surges


Technical data

Type of Dripline	Model	Thickness	Max. Pressure
		mm	bar
AZUD TUB	12	1,0	2,5
		0,9	3,2
	16	1	3,2
		1,2	4
		1,4	4
		1,5	5
	18	1,2	4
		1,1	2,5
	20	1,2	3,2
		1,3	3,2
		1,4	3,2
AZUD TUB drill	16	1,2	4
	16	1,4	4
	20	1,3	3,2

*Available colors: Black - White

AZUD TUB drill: Drilled tube. Drill diameter: 2 mm

Available distance between drills: 0.20 - 1.50 m



Sales format	Model	Thickness	Coil Length	Coils/Pallet	Coils/container 40'HC	Coils/container 40'HC
		mm	m			
In bulk	12	1,0	500	-	480	480
	16	0,9	450	-	384	384
	16	1	400	-	384	384
	16	1,2	400	-	384	384
	16	1,4	400	-	384	384
	16	1,5	300	-	480	480
	18	1,2	300	-	384	384
	20	1,1	250	-	384	384
	20	1,2	250	-	384	384
	20	1,3	250	-	384	384
	20	1,4	250	-	384	384
Palletized	16	0,9	350	24	360	360
	16	1	350	24	360	360
	16	1,2	350	24	360	360
	16	1,4	350	24	360	360
	16	1,5	350	24	360	360
	18	1,2	300	24	360	360
	20	1,1	200	24	360	360
	20	1,2	200	24	360	360
	20	1,3	200	24	360	360
	20	1,4	200	24	360	360

Related products



AZUD TUB MICRO



AZUD GREENTEC
DRIPLINE



AZUD NAVIA

