

Model Name: P586ZVN01.0

Issue Date: 2025/05/28

() Preliminary Specifications

(*) Final Specifications

Customer Signature	Date	AUO	Date
Approved By _____		Approval By PM Director CT Wu _____	
Note		Reviewed By RD Director Lamy Chen _____	
		Reviewed By Project Leader Simon Chuang _____	
		Prepared By PM Kim Kuo _____	

Contents

1.	General Description	4
2.	Absolute Maximum Ratings	6
3.	Optical Specification	7
4.	Interface Specification	11
4.1	Input power	11
4.2	Input Connection	12
4.2.1	Connector Type	12
4.2.2	Connector Pin Assignment	12
4.3	Input Data Format	16
4.3.1	eDP Data Format	16
4.3.2	Color Input Data Reference	17
5.	Signal Timing Specification	18
5.1.1.	Timing table	18
5.1.2.	Input Timing Diagram	19
5.2	Input interface characteristics	20
5.4	Power Sequence for LCD	23
6.	Backlight Specification	25
6.1	Electrical specification	25
6.2	Input Pin Assignment	26
6.3	Power Sequence for Backlight	28
7.	Mechanical Characteristics	29
8.	Reliability Test Items	32
9.	International Standard	33
9.1	Safety	33
9.2	EMC	33
10.	Packing	34
10.1	Definition of Label	34
10.2	Packing Methods	35
10.3	Pallet and Shipment Information	36
11.	Precautions	37
11.1.	Mounting Precautions	37
11.2.	Operating Precautions	37
11.3.	Operating Condition for Public Information Display	38
11.4.	Electrostatic Discharge Control	38
11.5.	Precautions for Strong Light Exposure	39
11.6.	Storage	39
11.7.	Handling Precautions for Protection Film	39
11.8.	Dust Resistance	39

Record of Revision

[illegible]

1. General Description

This specification applies to the 58.6 inch Color TFT-LCD Module P586ZV01.0 This LCD module has a TFT active matrix type liquid crystal panel 5120 x 1440 pixels, and diagonal size of 58.6 inch. This module supports 1 5120 x 1440 mode. Each pixel is divided into Red, Green and Blue sub-pixels or dots which are arranged in vertical stripes. Gray scale or the brightness of the sub-pixel color is determined with a 10-bit scale signal for each dot.

P586ZV01.0 has been designed to apply eDP interface method. It is intended to support displays where high brightness, wide viewing angle, high color saturation, and high color depth are very important.

Special material applied into this model are:

1. Liquid crystal: Advanced wide temperature LC(-40°C ~110°C)
2. Polarizer: Wide temperature polarizer (95°C)

* General Information


Items	Specification	Unit	Note
Active Screen Size	58.6	inch	
Display Area	1431.71 (H) x 402.67 (V)	mm	
Outline Dimension	1459.51(H) x 430.47(V) x 27(D)	mm	D: front bezel to wall mount
Driver Element	a-Si TFT active matrix		
Display Colors	8 bit + FRC	Colors	
Number of Pixels	5120 *1440	Pixel	
Pixel Pitch	0.279 (H) x 0.279 (W)	mm	
Pixel Arrangement	RGB vertical stripe		
Display Operation Mode	Normally Black		
Surface Treatment	Anti-Glare 28%		
Rotate Function	Unachievable		Note 1
Display Orientation	Portrait/Landscape Enabled		Note 2
Operating Time	24/7		See Chapter 11.3 for details
Frame Rate	60	Hz	See Chapter 5.1 for details
MTBF	100K	hours	See Chapter 8 for details Note 3

Note 1: Rotate Function refers to LCD display could be able to rotate. This function does not work in this model.


Note 2:

- (1) Landscape Mode: The default placement is T-Con Side on the upper side and the image is shown upright via viewing from the front.
- (2) Portrait Mode: The default placement is that T-Con side has to be placed on the right side via viewing from the front.

Landscape (Front view)



Portrait (Front view)



Note 3: MTBF is a reference index, it is not representative of warranty. Thermal acceleration factor based on Arrhenius model with $eV = 0.6$ @ Ambient temp 25C/50%

2. Absolute Maximum Ratings

The followings are maximum values which, if exceeded, may cause faulty operation or damage to the unit


Item	Symbol	Min	Max	Unit	Conditions
Logic/LCD Drive Voltage	V _{DD}	-0.3	14	[Volt]	Note 1
Input Voltage of Signal	V _{in}	-0.3	4	[Volt]	Note 1
Operating Temperature	TOP	-20	60	[°C]	Note 2
Operating Humidity	HOP	10	90	[%RH]	Note 2
Storage Temperature	TST	-20	+60	[°C]	Note 2
Storage Humidity	HST	10	90	[%RH]	Note 2
Panel Surface Temperature	PST		65	[°C]	Note 3

Note 1: Duration:50 msec.

Note 2 : Maximum Wet-Bulb should be 39 °C and No condensation.

The relative humidity must not exceed 90% non-condensing at temperatures of 40°C or less. At temperatures greater than 40°C, the wet bulb temperature must not exceed 39 °C.


Note 3: Surface temperature is measured at 60 °C Dry condition



3. Optical Specification

Optical characteristics are determined after the unit has been 'ON' and stable for approximately 45 minutes in a dark environment at 25°C. The values specified are at an approximate distance 500 mm from the LCD surface at a viewing angle of ϕ and θ equal to 0°.

Fig.1 presents additional information concerning the measurement equipment and method.



Parameter		Symbol	Values			Unit	Notes
			Min.	Typ.	Max		
Contrast Ratio		CR	3200	4000	--		1
Surface Luminance (White)		L _{WH}	560	700	--	cd/m ²	2
Luminance Variation		$\delta_{\text{WHITE(9P)}}$	--	--	1.33		3
Response Time (G to G)		T _Y	--	16	24	ms	4
Color Gamut		NTSC	67.5	72		%	
Gamma		G _{ma}	1.9	2.2	2.5		
Color Coordinates							
	Red	R _X	Typ.-0.03	0.650	Typ.+0.03		
		R _Y		0.337			
	Green	G _X		0.325			
		G _Y		0.611			
	Blue	B _X		0.153			
		B _Y		0.077			
	White	W _X		0.313			
		W _Y		0.329			
Viewing Angle							5
	x axis, right($\phi=0^\circ$)	θ_r	85	89	--	degree	
	x axis, left($\phi=180^\circ$)	θ_l	85	89	--	degree	
	y axis, up($\phi=90^\circ$)	θ_u	85	89	--	degree	
	y axis, down ($\phi=270^\circ$)	θ_d	85	89	--	degree	

Note:

1. Contrast Ratio (CR) is defined mathematically as:

$$\text{Contrast Ratio} = \frac{\text{Surface Luminance of } L_{on5}}{\text{Surface Luminance of } L_{off5}}$$

2. Surface luminance is luminance value at point 5 across the LCD surface 50cm from the surface with all pixels displaying white. From more information see FIG 2. LED current I_F = typical value (without driver board), LED input $V_{DDB} = 24V$, I_{DDB} = Typical value (with driver board), $L_{WH} = L_{on5}$ where L_{on5} is the luminance with all pixels displaying white at center 5 location.

3. The variation in surface luminance, δ_{WHITE} is defined (center of Screen) as:

$$\delta_{WHITE(9P)} = \text{Maximum}(L_{on1}, L_{on2}, \dots, L_{on9}) / \text{Minimum}(L_{on1}, L_{on2}, \dots, L_{on9})$$

4. Response time T_Y is the average time required for display transition by switching the input signal for five luminance ratio (0%,25%,50%,75%,100% brightness matrix) and is based on Frame rate = 60Hz to optimize.

Measured Response Time		Target				
		0%	25%	50%	75%	100%
Start	0%		0% to 25%	0% to 50%	0% to 75%	0% to 100%
	25%	25% to 0%		25% to 50%	25% to 75%	25% to 100%
	50%	50% to 0%	50% to 25%		50% to 75%	50% to 100%
	75%	75% to 0%	75% to 25%	75% to 50%		75% to 100%
	100%	100% to 0%	100% to 25%	100% to 50%	100% to 75%	

T_Y is determined by 10% to 90% brightness difference of rising or falling period. (As illustrated)

The response time is defined as the following figure and shall be measured by switching the input signal for “any level of gray(bright) “ and “any level of gray(dark)”.






FIG. 2 Luminance



- Viewing angle is the angle at which the contrast ratio is greater than 10. The angles are determined for the horizontal or x axis and the vertical or y axis with respect to the z axis which is normal to the LCD surface. For more information see FIG3.

FIG.3 Viewing Angle



4. Interface Specification

4.1 Input power

The P586ZVN01.0 module requires power inputs which are employed to power the LCD electronics and to drive the TFT array and liquid crystal.


Item		Symbol	Min.	Typ.	Max	Unit	Note
Power Supply Input Voltage		V_{DD}	10.8	12	13.2	V	1
Power Supply Input Current	Black pattern	I_{DD}	-	0.71	0.85	A	2
	White pattern		-	0.72	0.87	A	
	H-strip pattern		-	1.2	1.44	A	
Power Consumption	Black pattern	P_C	-	8.51	10.22	Watt	
	White pattern		-	8.61	10.34	Watt	
	H-strip pattern		-	14.33	17.2	Watt	
Inrush Current		I_{RUSH}	--	--	4	A	3

Note1. The ripple voltage should be fewer than 5% of V_{DD} .



Note2. Test Condition:

- (1) $V_{DD} = 12.0V$, (2) $F_v = 60Hz$, (3) $F_{clk} = 74.25MHz$, (4) Temperature = 25 °C
(5) Power dissipation check pattern. (Only for power design)

a. Black pattern




b. White pattern



c. H-Strip pattern

Note3. Measurement condition : Rising time = 400us



4.2 Input Connection

4.2.1 Connector Type


TFT-LCD Connector	Manufacturer	P-TWO	JAE	STARCONN
	Part Number	187059-51221-1	FI-RTE51SZ-HF	115E51-0000RA-M3-R

4.2.2 Connector Pin Assignment

PIN #	Symbol	Description	Remark
1	VDD	Power +12V	1
2	VDD	Power +12V	
3	VDD	Power +12V	
4	VDD	Power +12V	
5	VDD	Power +12V	
6	VDD	Power +12V	
7	VDD	Power +12V	
8	VDD	Power +12V	
9	WP	Write Protection	3&5
10	SDA	SDA - I2C Serial Data	3&4
11	SCL	SCL - I2C Serial Clock	3&4
12	NC	No connection (for AUO test only. Do not connect)	2
13	NC	No connection (for AUO test only. Do not connect)	2
14	NC	No connection (for AUO test only. Do not connect)	2
15	NC	No connection (for AUO test only. Do not connect)	2
16	NC	No connection (for AUO test only. Do not connect)	2
17	GND	Ground	
18	1st Lane3_N	Negative eDP differential data input	
19	1st Lane3_P	Positive eDP differential data input	
20	GND	Ground	
21	1st Lane2_N	Negative eDP differential data input	
22	1st Lane2_P	Positive eDP differential data input	
23	GND	Ground	
24	1st Lane1_N	Negative eDP differential data input	
25	1st Lane1_P	Positive eDP differential data input	

26	GND	Ground	
27	1st Lane0_N	Negative eDP differential data input	
28	1st Lane0_P	Positive eDP differential data input	
29	GND	Ground	
30	1st AUX_CH_P	Positive AUX Channel differential data input	
31	1st AUX_CH_N	Negative AUX Channel differential data input	
32	GND	Ground	
33	NC	No connection (for AUO test only. Do not connect)	2
34	GND	Ground	
35	2nd Lane3_N	Negative eDP differential data input	
36	2nd Lane3_P	Positive eDP differential data input	
37	GND	Ground	
38	2nd Lane2_N	Negative eDP differential data input	
39	2nd Lane2_P	Positive eDP differential data input	
40	GND	Ground	
41	2nd Lane1_N	Negative eDP differential data input	
42	2nd Lane1_P	Positive eDP differential data input	
43	GND	Ground	
44	2nd Lane0_N	Negative eDP differential data input	
45	2nd Lane0_P	Positive eDP differential data input	
46	GND	Ground	
47	2nd AUX_CH_P	Positive AUX Channel differential data input	
48	2nd AUX_CH_N	Negative AUX Channel differential data input	
49	GND	Ground	
50	HPD	Hot plug detection	
51	NC	No connection (for AUO test only. Do not connect)	2

Note1. Pin number start from the left side as the following figure.



Note2. Please leave this pin unoccupied. It cannot be connected with any signal (Low/GND/High...).


Note3. Input control signal threshold voltage definition

Item	Symbol	Min.	Typ.	Max.	Unit
Input High Threshold Voltage	V _{IH}	2.7	-	3.6	V
Input Low Threshold Voltage	V _{IL}	0	-	0.6	V

Note4. I2C Data and Clock

I2C Data and Clock timing

Parameter		Symbol	Min.	Typ.	Max	Unit
I2C	SCL clock frequency	f _{SCL}	-	-	400	kHz
	Clock Pulse Width Low	t _{LOW}	1.3	-	-	us
	Clock Pulse Width High	t _{HIGH}	0.6	-	-	us
	Clock Low to Data Output Valid	t _{AA}	-	-	1.1	us
	Start Setup Time	t _{STASU}	0.6	-	-	us
	Start Hold Time	t _{STAHD}	0.6	-	-	us
	Stop Setup Time	t _{STOSU}	0.6	-	-	us
	Data In Setup Time	t _{DSU}	0.2	-	-	us
	Data In Hold Time	t _{DHD}	0	-	-	us
	SCL/SDA Rise Time	t _R	-	-	0.3	us
	SCL/SDA Fall Time	t _F	-	-	0.3	us




Input equivalent impedance of SDA/SCL pin

Note5. Write Protection

Mode selection

WP	Note
L or OPEN	Protection
H	Writable

Input equivalent impedance of WP pin



4.3 Input Data Format

4.3.1 eDP Data Format

1st Lane0	1st Lane1	1st Lane2	1st Lane3
R1-9:2	R2-9:2	R3-9:2	R4-9:2
R1-1:0IG1-9:4	R2-1:0IG2-9:4	R3-1:0IG3-9:4	R4-1:0IG4-9:4
G1-3:0IB1-9:6	G2-3:0IB2-9:6	G3-3:0IB3-9:6	G4-3:0IB4-9:6
B1-5:0IR5-9:8	B2-5:0IR6-9:8	B3-5:0IR7-9:8	B4-5:0IR8-9:8
R5-7:0	R6-7:0	R7-7:0	R8-7:0
G5-9:2	G6-9:2	G7-9:2	G8-9:2
G5-1:0IB5-9:4	G6-1:0IB6-9:4	G7-1:0IB7-9:4	G8-1:0IB8-9:4
B5-3:0IR9-9:6	B6-3:0IR10-9:6	B7-3:0IR11-9:6	B8-3:0IR12-9:6
R9-5:0IG9-9:8	R10-5:0IG10-9:8	R11-5:0IG11-9:8	R12-5:0IG12-9:8
G9-7:0	G10-7:0	G11-7:0	G12-7:0
B9-9:2	B10-9:2	B11-9:2	B12-9:2
B9-1:0IR13-9:4	B10-1:0IR14-9:4	B11-1:0IR15-9:4	B12-1:0IR16-9:4
R13-3:0IG13-9:6	R14-3:0IG14-9:6	R15-3:0IG15-9:6	R16-3:0IG16-9:6
G13-5:0IB13-9:8	G14-5:0IB14-9:8	G15-5:0IB15-9:8	G16-5:0IB16-9:8
B13-7:0	B14-7:0	B15-7:0	B16-7:0
.	.	.	.
.	.	.	.
.	.	.	.
.	.	.	.

2nd Lane0	2nd Lane1	2nd Lane2	2nd Lane3
R1921-9:2	R1922-9:2	R1923-9:2	R1924-9:2
R1921-1:0IG1921-9:4	R1922-1:0IG1922-9:4	R1923-1:0IG1923-9:4	R1924-1:0IG1924-9:4
G1921-3:0IB1921-9:6	G1922-3:0IB1922-9:6	G1923-3:0IB1923-9:6	G1924-3:0IB1924-9:6
B1921-5:0IR1925-9:8	B1922-5:0IR1926-9:8	B1923-5:0IR1927-9:8	B1924-5:0IR1928-9:8
R1925-7:0	R1926-7:0	R1927-7:0	R1928-7:0
G1925-9:2	G1926-9:2	G1927-9:2	G1928-9:2
G1925-1:0IB1925-9:4	G1926-1:0IB1926-9:4	G1927-1:0IB1927-9:4	G1928-1:0IB1928-9:4
B1925-3:0IR1929-9:6	B1926-3:0IR1930-9:6	B1927-3:0IR1931-9:6	B1928-3:0IR1932-9:6
R1929-5:0IG1929-9:8	R1930-5:0IG1930-9:8	R1931-5:0IG1931-9:8	R1932-5:0IG1932-9:8
G1929-7:0	G1930-7:0	G1931-7:0	G1932-7:0
B1929-9:2	B1930-9:2	B1931-9:2	B1932-9:2
B1929-1:0IR1933-9:4	B1930-1:0IR1934-9:4	B1931-1:0IR1935-9:4	B1932-1:0IR1936-9:4
R1933-3:0IG1933-9:6	R1934-3:0IG1934-9:6	R1935-3:0IG1935-9:6	R1936-3:0IG1936-9:6
G1933-5:0IB1933-9:8	G1934-5:0IB1934-9:8	G1935-5:0IB1935-9:8	G1936-5:0IB1936-9:8
B1933-7:0	B1934-7:0	B1935-7:0	B1936-7:0
.	.	.	.
.	.	.	.
.	.	.	.
.	.	.	.

4.3.2 Color Input Data Reference

The following table is for color versus input data (10bits). The higher the gray level, the brighter the color.10bits

Color	Gary Level	Color Input Data																												Remark			
		RED data (MSB:R9,LSB:R0)										GREEN data (MSB:G9,LSB:G0)										BLUE data (MSB:B9,LSB:B0)											
		R9	R8	R7	R6	R5	R4	R3	R2	R1	R0	G9	G8	G7	G6	G5	G4	G3	G2	G1	G0	B9	B8	B7	B6	B5	B4	B3	B2		B1	B0	
Black	-	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		
White	-	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	
L511	-	0	1	1	1	1	1	1	1	1	1	0	1	1	1	1	1	1	1	1	1	0	1	1	1	1	1	1	1	1	1	1	
Red	L0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	Black	
	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	
	L1023	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
Green	L0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	Black	
	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	
	L1023	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	
Blue	L0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	Black	
	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	
	L1023	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	1	

5. Signal Timing Specification

This is the signal timing required at the input of the user connector. All of the interface signal timing should be satisfied with the following specifications for its proper operation.

5.1.1. Timing table

The input timing is shown as the following table.

Symbol	Description		Min.	Typ.	Max.	Unit	Remark
Tv	Vertical Section	Period	1460	1530	1940	Th	
Tdisp (v)		Active	1440	1440	1440	Th	
Tblk (v)		Blanking	20	90	500	Th	
Fv		Frequency	47	60	63	Hz	Note 3-4 Note 3-7
Th	Horizontal Section	Period	2720	2800	2880	Tclk	
Tdisp (h)		Active	2560	2560	2560	Tclk	
Tblk (h)		Blanking	160	240	320	Tclk	
Fh		Frequency	89.7	91.8	97.2	kHz	Note 3-5
Tclk	Pixel Clock	Period	3.78	3.89	4.098	ns	1/Fclk
Fclk		Frequency	244	257	264.5	MHz	Note 3-6
Link Rate per Lane			2.7			Gbps	

Note 3-4: The optimal Vertical Frequency is 60 ~ 63 Hz for best picture quality.

Note 3-5: The equation is listed as following. Please don't exceed the above recommended value.

$$Fh (\text{Min.}) = Fclk (\text{Min.}) / Th (\text{Min.})$$

$$Fh (\text{Typ.}) = Fclk (\text{Typ.}) / Th (\text{Typ.})$$

$$Fh (\text{Max.}) = Fclk (\text{Max.}) / Th (\text{Min.})$$

Note 3-6: The equation is listed as following. Please don't exceed the above recommended value.

$$1\text{st Lane N \& 2nd Lane N skew} < 200\text{ns}$$


$$Fclk (\text{Typ.}) = Fv (\text{Typ.}) \times Th (\text{Typ.}) \times Tv (\text{Typ.})$$

$$Fclk (\text{Min.}) \leq Fv \times Th \times Tv \leq Fclk (\text{Max.})$$

Note 3-7: The equation is listed as following. Please don't exceed the above recommended value.

$$F_v = F_{clk}(Typ.) / (T_v \times T_h)$$

5.1.2. Input Timing Diagram




5.2 Input interface characteristics


eDP Specification (Follow as VESA DisplayPort Standard Version 1.2)

a. DisplayPort main link signal:

DisplayPort main link					
		Min	Typ	Max	unit
Frequency	Main link Frequency	-	2.7	-	Gbps
UI	Unit Interval	-	370	-	ps
VCM	RX input DC Common Mode Voltage	-	0	-	V
VDiff _{P-P}	Peak-to-peak Voltage at a receiving Device	150	-	-	mV
Down_Spread_Freq	Link clock down spread frequency	30	-	33	KHz
Down_Spread_Amplitude	Link clock down spread amplitude	-	-	0.5	%

Point	Time(UI)	Voltage
1	0.245	0
2	0.5	75mV
3	0.755	0
4	0.5	-75mV






b. DisplayPort AUX_CH signal:

DisplayPort AUX_CH					
		Min	Typ	Max	unit
VCM	AUX DC Common Mode Voltage	0	-	2.0	V
VDiff _{P-P}	AUX Peak-to-peak voltage at a receiving device	0.27	-	1.36	V

Differential AUX+ , AUX-
Which is Display port AUX_CH



c. DisplayPort VHPD signal:

DisplayPort VHPD					
		Min	Typ	Max	unit
VHPD	HPD Voltage	2.25	-	3.6	V

d. Intra-Pair skew


LRX-SKEW-INTRA_PAIR					
		Min	Typ	Max	unit
LRX-SKEW-INTRA_PAIR	Lane Intra-pair Skew Tolerance	-	-	50	ps

e. Inter-Pair Skew

LRX-SKEW-INTER_PAIR					
		Min	Typ	Max	unit
LRX-SKEW-INTER_PAIR	Lane-to-Lane Skew at RX package pins	-	-	5200	ps

5.4 Power Sequence for LCD

VDD power, eDP signal and backlight on/off sequence are as following. eDP signals from any system shall be Hi-Z state when VDD is off.



Power Sequence Timing

Symbol	Value			Unit	Remark
	Min.	Typ.	Max.		
T1	0.5	-	10	[ms]	
T2	0	-	550	[ms]	Sink device AUX CH must be operational upon HPD high.
T3	0	-	-	[ms]	Note 1
T4	500	-	-	[ms]	
T5	100	-	-	[ms]	
T6	0		200	[ms]	Note 2 Note 3
T7	0	-	200	[ms]	Note 3 Note 4

Note 1 During T3 period , eDP link training time by customer's system.

Note 2: Recommend setting T6 = 0ms to avoid electronic noise when VDD is off.

Note 3: During T6 and T7 period , please keep the level of input eDP signals with Hi-Z state.

Note 4: Voltage of VDD must decay smoothly after power-off.(customer system decide this value)

AUO Display Plus Confidential
For AVNET_EU Internal Use Only
20250612 19:46:24

AUO Display Plus Confidential
For AVNET_EU Internal Use Only
20250612 19:46:24

AUO Display Plus Confidential
For AVNET_EU Internal Use Only
20250612 19:46:24

AUO Display Plus Confidential
For AVNET_EU Internal Use Only
20250612 19:46:24


6. Backlight Specification

6.1 Electrical specification

	Item	Symbol	Condition	Min	Typ	Max	Unit	Note
1	Power Supply Input Voltage	V _{DDB}	-	22.8	24	25.2	V	-
2	Power Supply Input Current	I _{DDB}	V _{DDB} =24V		4.7	5.24	A	1
3	Power Consumption	P _{DDB}	V _{DDB} =24V		112.8	125.8	Watt	1
4	Inrush Current	I _{RUSH}	V _{DDB} =24V			16.3	A	2
5	Control signal voltage	V _{Signal}	V _{DDB} =24V	2	-	3.3	V	-
				0	-	0.8		3
6	Control signal current	I _{Signal}	V _{DDB} =24V	-	-	1.5	mA	-
7	External PWM Duty ratio (input duty ratio)	D_EPWM	V _{DDB} =24V	5	-	100	%	4
8	External PWM Frequency	F_EPWM	V _{DDB} =24V	120	-	960	Hz	4
9	DET status signal	DET	V _{DDB} =24V	Open Collector			V	5
				0	-	0.8	V	5
10	Input Impedance	R _{in}	V _{DDB} =24V	300			Kohm	-
11	LED MTTF	LTLED	-		50,000	-	Hr	6

Note 1: Dimming ratio= 100%, (Ta=25±5℃, Turn on for 45minutes)

Note 2: MAX input current while DB turn on, measurement condition V_{DDB} rising time=20ms(V_{DDB}: 10%~90%)



Note 3: When BLU off (V_{DDB} = 24V , V_{BLON} = 0V) , I_{DDB} (max) = 0.1A

Note 4: Less than 5% dimming control is functional well and no backlight shutdown happened

Note 5: Normal: 0~0.8V ; Abnormal : Open collector

Note 6: The lifetime (MTTF) is defined as the time which luminance of LED is 50% compared to its original value.

[Operating condition: Continuous operating at Ta = 25±2℃ , for single LED only]

MTTF is a reference index, it is not representative of warranty

6.2 Input Pin Assignment

The P586ZV01.0 module requires [1 power input (14-pin)]

LED DB connector: CI0114M1HRL-NH(CviLux)

Pin	Symbol	Description	Note
1	VDDDB	Power Supply Input Voltage	
2	VDDDB	Power Supply Input Voltage	
3	VDDDB	Power Supply Input Voltage	
4	VDDDB	Power Supply Input Voltage	
5	VDDDB	Power Supply Input Voltage	
6	GND	Ground	
7	GND	Ground	
8	GND	Ground	
9	GND	Ground	
10	GND	Ground	
11	DET	BLU status detection:	1
12	VBLON	BLU On-Off control:	2,3
13	NC	NC	4
14	PDIM	External PWM	2, 5

Note1. DET status

DET	BLU status
0 ~ 0.8V	Normal
Open collector	Abnormal

Recommend pull high R > 10K ohm, pull high voltage VDD = 3.3V

Note2. input control signal threshold voltage definition

Item	Symbol	Min.	Typ.	Max.	Unit
Input High Threshold Voltage	VIH	2	-	3.3	V
Input Low Threshold Voltage	VIL	0	-	0.8	V

Note3. VBLON


Mode selection

VBLON	Note
H or OPEN	BL On
L	BL Off

Note4. Please leave this pin unoccupied. It cannot be connected by any signal (Low/GND/High).

Note5. PDIM


PWM Dimming range:




External PWM function dimming ratio 0%~100%, Judge condition as below:

- (1) Backlight module must be lighted ON normally.
- (2) All protection function must work normally.
- (3) Uniformity and flicker could be guaranteed at External PWM function dimming ratio 5%~100%

6.3 Power Sequence for Backlight



Dip condition



Parameter	Min	Typ	Max	Units
T1	20	-	-	ms ^{*1}
T2	0	-	-	ms
T3	300	-	-	ms
T4	300	-	-	ms
T5	0	-	-	ms
T6		-	1000	ms ^{*2}


Note:1. T6 describes VDDDB dip condition and VDDDB couldn't lower than 10% VDDDB.

7. Mechanical Characteristics

The contents provide general mechanical characteristics for the model P586ZV01.0. In addition, the figures in the next page are detailed mechanical drawing of the LCD.


Item		Dimension	Unit	Note
Outline Dimension	Horizontal	1459.51	mm	
	Vertical	430.47	mm	
	Depth (Dmin)	10.7	mm	Front bezel to Back Bezel
	Depth (Dmax)	27	mm	Front Bezel to BOSS
	Bezel opening	1434.7x405.67	mm	
	Bezel Width	12.4/12.4/12.4/12.4	mm	U/D/L/R
	Display Area	1431.71 (H) x 402.67 (V)	mm	
Weight	9.05		Kg	

Front View



Back View

This Drawing is subject to be changed after project kicking off.



8. Reliability Test Items

	Test Item	Q'ty	Condition
1	High temperature storage test	3	60°C, 500hrs
2	Low temperature storage test	3	-20°C, 500hrs
3	High temperature operation test	3	60°C, 500hrs
4	Low temperature operation test	3	-20°C, 500hrs
5	Vibration test (With carton)	1(PKG)	Random wave (1.04Grms 2~200Hz) Duration : X,Y,Z 20min per axes
6	Drop test (With carton)	1(PKG)	Height: 20.0cm Direction: Bottom flat two times ° (ASTMD4169-I)
7	MTBF	12	50°C/80%, 1300hrs, 90% confidence level

9. International Standard

9.1 Safety

- (1) UL 62368-1 : Audio/video, information and communication technology equipment – Part 1: Safety requirements
- (2) IEC 62368-1 : Audio/video, information and communication technology equipment –Part 1: Safety requirements
- (3) EN 62368-1 : Audio/video, information and communication technology equipment –Part 1: Safety requirements



9.2 EMC

- (1) ANSI C63.4 “Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electrical Equipment in the Range of 9kHz to 40GHz. “American National standards Institute(ANSI), 1992
- (2) C.I.S.P.R “Limits and Methods of Measurement of Radio Interface Characteristics of Information Technology Equipment.” International Special committee on Radio Interference.
- (3) EN 55022 “Limits and Methods of Measurement of Radio Interface Characteristics of Information Technology Equipment.” European Committee for Electrotechnical Standardization. (CENELEC), 1998

10. Packing

10.1 Definition of Label

A. Panel Label:



Green mark description


(1) For Pb Free Product, AUO will add  for identification.

(2) For RoHs compatible products, AUO will add  for identification.

Note: The green Mark will be present only when the green documents have been ready by AUO internal green team. (definition of green design follows the AUO green design checklist.)


B. Carton Label:

The label is on the carton as shown below: (Example)



10.2 Packing Methods


This following packing information is subject to be changed after project kicking off.



10.3 Pallet and Shipment Information

This following packing information is subject to be changed after project kicking off.

	Item	Specification			Packing Remark
		Qty.	Dimension	Weight (kg)	
1	Packing Box	8 pcs/box	1640(L)mm*545 (W)mm*535(H)mm	78.6	Panel 9.2kg
2	Pallet	1	1660(L)mm*1150(W)mm*145(H)mm	26	Pallet
3	Boxes per Pallet	2 boxes/Pallet (By Air) ; 2 Boxes/Pallet (By Sea)			
4	Panels per Pallet	16 pcs/Pallet(By Air) ; 16 pcs/Pallet (By Sea)			Air and Sea > Double pallet
5	Pallet	2pallet (by Air)	1660(L)mm*1150(W)mm*1370 (H)mm	366.4 (by Air)	Double pallet
	after packing	2pallet (by Sea)	1660(L)mm*1150(W)mm*1370(H)mm	366.4 (by Sea)	



11. Precautions

Please pay attention to the followings when you use this TFT LCD module.

11.1. Mounting Precautions

- (1) You must mount a module using holes arranged in four corners or four sides.
- (2) You should consider the mounting structure so that uneven force (ex. twisted stress) is not applied to module. And the case on which a module is mounted should have sufficient strength so that external force is not transmitted directly to the module.
- (3) Please attach the surface transparent protective plate to the surface in order to protect the polarizer. Transparent protective plate should have sufficient strength in order to resist external force.
- (4) You should adopt radiation structure to satisfy the temperature specification.
- (5) Acetic acid type and chlorine type materials for the cover case are not desirable because the former generates corrosive gas of attacking the polarizer at high temperature and the latter cause circuit broken by electro-chemical reaction.
- (6) Do not touch, push or rub the exposed polarizer with glass, tweezers or anything harder than HB pencil lead. And please do not rub with dust clothes with chemical treatment. Do not touch the surface of polarizer for bare hand or greasy cloth. (Some cosmetics are detrimental to the polarizer.)
- (7) When the surface becomes dusty, please wipe gently with absorbent cotton or other soft materials like chamois soaked with petroleum benzene. Normal-hexane is recommended for cleaning the adhesives used to attach front/ rear polarizer. Do not use acetone, toluene and alcohol because they cause chemical damage to the polarizer.
- (8) Wipe off saliva or water drops as soon as possible. Their long time contact with polarizer causes deformations and color fading.
- (9) Do not open the case because inside circuits do not have sufficient strength.

11.2. Operating Precautions

- (1) The spike noise causes the mis-operation of circuits. It should be lower than following voltage:
 $V = \pm 200\text{mV}$ (Over and under shoot voltage)
- (2) Response time depends on the temperature. (In lower temperature, it becomes longer.)
- (3) Brightness depends on the temperature. (In lower temperature, it may become lower.) And in lower temperature, response time (required time that brightness is stable after turned on) becomes longer.
- (4) Be careful for condensation at sudden temperature change. Condensation makes damage to polarizer or electrical contacted parts. And after fading condensation, smear or spot will occur.
- (5) When fixed patterns are displayed for a long time, remnant image is likely to occur.
- (6) Module has high frequency circuits. Sufficient suppression to the electromagnetic

interference shall be done by system manufacturers. Grounding and shielding methods may be important to minimize the interface.

- (7) The conductive material and signal cables are kept away from LED driver inductor to prevent abnormal display, sound noise and temperature rising.

11.3. Operating Condition for Public Information Display

The device listed in the product specification is designed and manufactured for PID (Public Information Display) application. To optimize module's lifetime and function, below operating usages are required.

(1) Normal operating condition

- A. Operating temperature: -20~60°C
- B. Operating humidity: 10~90%
- C. Display pattern: dynamic pattern (Real display).

Note) Long-term static display would cause image sticking.

(2) Operation usage to protect against image sticking due to long-term static display.

- A. Suitable operating time: under 24 hours a day
- B. Liquid Crystal refresh time is required. Cycling display between 5 minutes' information (static) display and 10 seconds' moving image.
- C. Periodically change background and character (image) color.
- D. Avoid combination of background and character with large different luminance.

(3) Periodically adopt one of the following actions after long time display.

- A. Running the screen saver (motion picture or black pattern)
- B. Power off the system for a while

(4) LCD system is required to place in well-ventilated environment. Adapting active cooling system is highly recommended.

(5) Product reliability and functions are only guaranteed when the product is used under right operation usages. If product will be used in extreme conditions, such as high temperature/ humidity, display stationary patterns, or long operation time etc..., it is strongly recommended to contact AUO for filed application engineering advice. Otherwise, its reliability and function may not be guaranteed. Extreme conditions are commonly found at airports, transit stations, banks, stock market and controlling systems.

11.4. Electrostatic Discharge Control

Since a module is composed of electronic circuits, it is not strong to electrostatic discharge. Make certain that treatment persons are connected to ground through wristband etc. And don't touch interface pin directly.

11.5. Precautions for Strong Light Exposure

- (1) Strong light exposure causes degradation of polarizer and color filter.
- (2) To keep display function well as a digital signage application, especially the component of TFT is very sensitive to sunlight, it is necessary to set up blocking device protecting panel from radiation of ambient environment.

11.6. Storage

When storing modules as spares for a long time, the following precautions are necessary.

- (1) Store them in a dark place. Do not expose the module to sunlight or fluorescent light. Keep the temperature between 5°C and 35°C at normal humidity.
- (2) The polarizer surface should not come in contact with any other object. It is recommended that they be stored in the container in which they were shipped.
- (3) Storage condition is guaranteed under packing conditions.
- (4) The phase transition of Liquid Crystal in the condition of the low or high storage temperature will be recovered when the LCD module returns to the normal condition.

11.7. Handling Precautions for Protection Film


- (1) The protection film is attached to the bezel with a small masking tape. When the protection film is peeled off, static electricity is generated between the film and polarizer. This should be peeled off slowly and carefully by people who are electrically grounded and with well ion-blown equipment or in such a condition, etc.
- (2) When the module with protection film attached is stored for a long time, sometimes there remains a very small amount of glue still on the bezel after the protection film is peeled off.
- (3) You can remove the glue easily. When the glue remains on the bezel or its vestige is recognized, please wipe them off with absorbent cotton waste or other soft material like chamois soaked with normal-hexane.

11.8. Dust Resistance

- (1) AUO module dust test is conducted with marked holes (see Figure 1) sealed to comply with JIS D0207.
- (2) Module users should design set with these holes used/sealed (if not used) or covered by set mechanism to prevent dust from entering. The AUO testing procedure cannot replicate all different real world scenarios, module users should apply set dust resistance solution to meet users' requirement.

Figure 1

Step1: to seal the holes and concerns on the position of red mark



Step2: to seal the slits around the front bezel and back cover on the position of brown mark.

