

Processors Units

DSP-4080A 4 In/8 Out fully configurable DSP, 9 full bandwidth parametric band EQ on each Channel, AudioCore equipped 1

DASnet-Rack

DASnet-Rack 99 Rack w/ 1 x DASnet-Patch-99 + 1 x DASnet-Patch-PowerCon + 32A power distro 2
 USB-485 KK Systems USB to RS-485 convertor 1

Speaker cabling

eCPK-20 20m CAT7 Integrated etherCON (Data + Audio) + powerCON TRUE1 cable 8
 eC-09 0.9m CAT7 etherCON (Data + Audio) link cable 20
 Plink1-09 0.9m powerCON TRUE1 link cable 20
 eCPK-1 1m CAT7 integrated etherCON (Data + Audio) + powerCON TRUE 1 cable link 8

Rigging frames

AX-Aero20 Rigging Bumper for aero 20A (max 20units) 2

Dollies


PL-UX218S Caster frame for stacking UX-218/UX-218A (max 3 units) 4
 PL-20S Metallic caster frame for stacking aero 20A (max 4 units) 6

Covers

FUN-4-AERO-20A Black protective transport cover for 4 units of aero 20A on PL-20Saero20 6
 FUN-3-UX-218 Black protective transport cover for 3 UX-218/UX-218A on PL-UX218S 4


Truck Configurations

Euro truck




243cm / 96"

American Truck 90" x 232"




228cm / 90"

American Truck 99" x 232"




251cm / 99"

DASnet-Rack 99 Connections



DASnet Rack 99



DASnet Rack 99