

## aero 20A

Powered, bi-amplified  
compact line array module



- » Bi-amplified 2-way system
- » 1200 W Class D power amplifier
- » Powerful DSP with Brickwall FIR Filters
- » Remote monitoring and control via DASnet™
- » New SERPIS BPS-1912 high frequency plane wave generator

The Aero 20A is a compact line array system which incorporates D.A.S.'s latest technical achievements in transducer design, power electronics and system management.

The low-mid range incorporates a new D.A.S. 12AN4 loudspeaker optimized to provide high output and reliability. High frequency response relies on a compression driver-waveguide assembly developed for the Aero 20A. The M-75N compression driver employs a powerful neodymium magnet structure, a titanium diaphragm and 75 mm (3") voice coil. The M-75N is attached to a new aluminum waveguide that has been designed to be free of resonances and provide a natural sound.

The Aero 20A incorporates the latest in digital signal processors. Brick wall FIR filters provide perfect alignment between ways achieving exceptionally uniform coverage all the way down to the crossover point.

Top-of-the-line AD/DA converters have been employed allowing for significant improvements in dynamics, lower distortion and ultra-low noise levels. Remote monitoring and control is provided by way of DASnet™.

A new captive rigging mechanism enhances ease-of-use by allowing angle selection to be made while stacked on the transport dolly.

### Technical Specifications

<b>Low-mid Frequency Power Amplifier</b>	1600 W <sub>peak</sub> - 800 W <sub>continuous</sub>
<b>High Frequency Power Amplifier</b>	800 W <sub>peak</sub> - 400 W <sub>continuous</sub>
<b>Input Type</b>	Balanced Differential Line
<b>Input Impedance</b>	Line: 20 kohms
<b>Sensitivity</b>	Line: 4.9 V (+16 dBu)
<b>On-axis Frequency Range (-10 dB)</b>	60 Hz - 20 kHz
<b>Maximum Peak SPL at 1 meter</b>	136 dB
<b>Nominal -6 dB Beamwidths</b>	90° Horizontal - Splay Dependent Vertical
<b>Enclosure Material</b>	Birch Plywood
<b>Finish</b>	Black/ISO-Flex Paint
<b>Transducers/Replacement Parts</b>	LF: 1 x 12AN4/GM 12AN4 HF: 1 x M-75N/GM M-75N
<b>Connectors</b>	Audio INPUT: Female XLR Audio LOOP THRU: Male XLR Audio + Data INPUT: etherCON Audio + Data LOOP THRU: etherCON AC INPUT: powerCON TRUE 1 AC OUTPUT: powerCON TRUE 1
<b>AC Power Requirements</b>	3.6 A, 115 V, 50 Hz/60 Hz 1.8 A, 230 V, 50 Hz/60 Hz
<b>Dimensions (H x W x D)</b>	31.7 x 64.7 x 44.3 cm; 12.4 x 25.2 x 17.3 in
<b>Weight</b>	33.1 kg (72.82 lb)
<b>Accessories (optional)</b>	AX-aero20 / AXS-aero20 / Pick-Up AX-aero20 / PL-20S / Fun-4aero20 / AX-combo2040

### Dimensions



