



SOUND WITH SOUL

event

series



www.dasaudio.com

DAS Audio Group, S.L.
C/ Islas Baleares, 24
46988. Fuente del Jarro
Valencia - Spain
Tel. +34 961 340 860

DAS Audio of America, Inc.
6900 NW 52nd Street
Miami, FL 33166 - U.S.A
Tel. +1 305 436 0521

DAS Audio Asia PTE. LTD.
9 Temasek Boulevard, Suntec
City Tower2,31/F
Singapore 038989
Tel. +65 6559 6200

DAS do Brasil
Rua Dos Andradas, 382 SL
Santa Efigênia, São Paulo
Brasil. CEP: 01208-000
Tel. +551133330764



SOUND WITH SOUL

THE NEW DESIGN

ENGINEERED TO SIMPLIFY
GREAT SOUND.

BUILT SMALL.
DESIGNED BIG.

A NEW ICON
IS BORN.

The EVENT-26A was conceived to simplify the complex. We have invested many hours of work optimizing different variables of the electronics and the distribution of the components to create a small system that sounds really big. The FSS™ system allows you to set cabinet angles while still stacked on the dolly, saving time and hassle.

Just connect, select preset and enjoy.

Thanks to FIR filters, waveguide design and the distribution of the components, EVENT-26A provides a surprisingly uniform horizontal coverage of 100° and flat phase response. Additionally, the efficiency of the Class D amplifier ensures that the rest of the components achieve exceptional performance.

The series is born to succeed.

The ideal work tool. The EVENT-26A array is so small that you can easily transport it virtually in any car, so powerful that if you close your eyes, you wouldn't believe the sound is coming out of it and so intuitive that if you take more than 15 minutes to configure it, we would like you to tell us how that happened.

GO BIG

Key features EVENT-26A

- Ultra-compact, lightweight powered line array
- High-efficiency Class D amplifier with SMPS
- Easy system configuration thanks to DAScontrol™
- High-end 24-bit DSP with LCD screen
- FIR processing technology for constant phase response
- FSS™ Fast Set Splay rigging for quick deployment
- Dual voltage mains

Key features EVENT-115A

- Active front-loaded subwoofer system
- 1 x 15" DAS 15FW4 loudspeaker
- High-efficiency Class D amplifier with SMPS
- Easy system configuration thanks to DAScontrol™
- High-end 24-bit DSP with LCD screen
- EVENT-26A compatible rigging hardware
- Dual voltage mains



SMALL,
STRONG AND
INTUITIVE

EVENT-26A

Model	EVENT-26A
Nominal Amplifier Power	800 Wpeak - 400 Wcontinuous Class D, Biampified
Input Type	Balanced
Input Impedance	Line: 20 kohms
Input Sensitivity	6.2 V (+18dBu)
Frequency Range (-10 dB)	76 Hz - 19 kHz
Horizontal Coverage (-6 dB)	100° Nominal
Vertical Coverage	Splay Dependent
Rated Maximum Peak SPL at 1 m	131 dB
Transducers/Replacemnt Parts	HF: M-60/GM-M-60N LF: 6MI
Enclosure Geometry	Trapezoidal
Enclosure Material	Polypropylene
Color/Finish	Black Textured
Connectors	INPUT: 1 x Female XLR LOOP THRU: 1 x Male XLR AC INPUT: 1 x powerCON AC OUTPUT: powerCON
AC Power Requierements	115 V, 1.6 A, 50 Hz/60 Hz 230 V, 0.8 A, 50 Hz/60 Hz
Dimensions (H x W x D)	225 x 480 x 485 mm 8,86 x 18,9 x 19,09 in
Weight	16,5 kg (36,5 lb)
Accessories	AX-EV26 - Rigging System AXS-EV26 - Stacking Base TRD-2 - Speaker stand TRD-6 - Pole Mount TRD-7 - Adjustable Pole Mount AXC-ZT - Top Hat FUN-4-EV26 - Transport Cover FUN-6-EV26 - Transport Cover PL-EV26S - Stacking Dolly

EVENT-115A

Model	EVENT-115A
Nominal Amplifier Power	1200 Wpeak - 600 Wcontinuous Class D amplifier
Input type	Balanced
Input Impedance	Line: 20 kohms
Input Sensitivity	1.95 V (+8dBu)
Frecuency Range (-10dB)	40 Hz - 125 Hz
Rated Maximum Peak SPL at 1m	131 dB
Transducers/Replacements Parts	15FW4 / GM-15FW4
Enclosure Material	Birch plywood
Color/finish	ISO-flex Paint
Rigging System	Integrated in box design
Connectors	INPUT: 2 x Female XLR OUTPUT: 2 x Male XLR AC INPUT: powerCON AC OUTPUT: powerCON
AC Power Requirements	115 V, 2.8 A 50Hz /60 Hz 230 V, 1,4 A 50Hz /60 Hz
Dimensions (HxWxD)	481 x 485 x 770 mm 18,9 x 19,1 x 30,3 in
Weight	37 Kg (81,5 lb)
Accessories	AX-EV26 - Rigging System AXS-EV26 - Stacking Base TRD-2 - Speaker stand TRD-6 - Pole Mount TRD-7 - Adjustable Pole Mount FUN-2-EV115 - Transport Cover PL-EV115S - Stacking Dolly JP-EV26 - Joining plate



EVENT ADAPTS
TO YOUR NEEDS



ACCESSORIES



PL-EV115S

PL-EV26S

AXS-EV26

JP-EV26

AX-EV26

AXC-ZT