

Processors Units

DSP-4080A 4 In/8 Out fully configurable DSP, 9 full bandwidth parametric band EQ on each Channel, AudioCore equipped 1

DASnet-Rack

DASnet-Rack 99 Rack w/ 1 x DASnet-Patch-99 + 1 x DASnet-Patch-PowerCon + 32A power distro 1

USB-485 KK Systems USB to RS-485 convertor 1

Speaker cabling

eCPK-20 20m CAT7 Integrated etherCON (Data + Audio) + powerCON TRUE1 cable 10

eC-09 0.9m CAT7 etherCON (Data + Audio) link cable 12

Plink1-09 0.9m powerCON TRUE1 link cable 12

Rigging frames

AX-Aero20 Rigging Bumper for aero 20A (max 20units) 2

Dollies

PL-UX221S Caster frame for stacking UX-221A (max 3 units) 2

PL-20S Metallic caster frame for stacking aero 20A (max 4 units) 4


Covers

FUN-4-AERO-20A Black protective transport cover for 4 units of aero 20A on PL-20Saero20 4

FUN-3-UX-221 Black protective transport cover for 3 UX-221A on PL-UX221S 2


Truck Configurations

Euro truck




243cm / 96"

American Truck 90" x 232"




228cm / 90"

American Truck 99" x 232"



251cm / 99"

DASnet-Rack 99 Connections




LOAD PER PHASE

PHASE 1: 16A

PHASE 2: 18A

PHASE 3: 9A

DASnet Rack 99



LOAD PER PHASE

PHASE 1: 16A

PHASE 2: 18A

PHASE 3: 9A

DASnet Rack 99