UNIGLOVES NITREX

HAND PROTECTION RANGE

285PR

INSTRUCTIONS FOR USE

285PR-06 6
285PR-07 7
285PR-08 8
285PR-09 9
285PR-10 10
285PR-11 11

EN388:2016+A1:2018

1	2	3	4	5
4	100	500	2000	8000
1	b	1.2	2.5	10
3	c	10	25	50
2	100	200	150	-
X	A	B	C	D

EN511:2006

1	2	3
2	2	4
1	2	4
X	2	4
X	2	4

ENISO 374-1:2016+A1:2018

EN ISO 374-1	EN ISO 374-2	EN ISO 374-4	EN ISO 374-5
X	X	X	X

EN ISO 374-1	EN ISO 374-4 (%)
A	X
B	X
C	X
D	X
E	X
F	X
G	X
H	X
I	X
J	X
K	X
L	X
M	X
N	X
O	X
P	X
Q	X
R	X
S	X
T	X

EN407:2020

1	2	3	4	5	6
X	100	500	150	35	X
1	k	100	250	350	20
1	4	24	27	210	18
X	m	27	27	250	35
1	n	210	315	325	35
X	30	60	120	200	200

1	2	3	4	5
0.10 x LTR	0.15 x LTR	0.22 x LTR	0.30 x LTR	
g	0.025 x9 <0.050	0.050 x9 <0.100	0.100 x9 <0.150	0.150 x9
X	h			

Complies with EU Regulation 2016/425 for PPE, as brought to UK Law and amended, through European standards EN ISO 21420:2020; EN388:2016+A1:2018 and EN407:2020. Category II

The EU type examination conducted by: CTC, 4 Rue Hermann Frenkel, 69007 Lyon, FR (notified body number 0075).

EN ISO 374-1:2016+A1:2018 When the marked level is X it indicates that the glove has not been tested or the test method is not adequate. Gloves have been tested in the palm area. You are advised to retain this packaging for reference. Contains accelerators which may cause allergic reactions. This information does not reflect the actual duration of protection in the workplace and the manufacturer recommends a risk assessment be carried out before the intended use. Gloves are considered under laboratory conditions from samples taken from the palm only (except in cases where the glove is equal to or over 400 mm - where the sleeve is tested under cuffs) for the purpose of this test. Glove size can be different if the chemical is used in a mixture. It is recommended to check that the gloves are suitable for the intended use because the conditions at the workplace may differ from those under which the chemical resistance has been tested. Depending on the chemical, exposed gloves may provide less resistance to the dangerous chemical due to changes in physical properties. Movements, abrasion, bending, contamination of the glove surface, temperature, etc. may reduce the protection time. For mixtures or complex chemicals, degradation can be the most important factor to consider in selection of chemical resistant gloves. Before usage, inspect the gloves for any defect or imperfections. EN ISO 374-4:2019 Degradation levels indicate the change in physical properties of the material after contact with the chemical. Gloves with degradation levels should be inspected under laboratory conditions and relates only to the tested specimen. You are advised to retain this packaging for reference.

EN 388:2016+A1:2018 Mechanical risk(s) Abrasion resistance [cycles]; Cut resistance (c) Tearing resistance [N] (d) Puncture resistance [N] Coup test (Cut) Protection level. Note: Cut test: Gloves with a level of performance 1 for cut test in cuff or cuff area cuse test results are only indicative while the TDM cut resistance is the reference performance results (applicable to products with ISO 13997 cut test). Abrasion: Results of abrasion resistance are based on laboratory test results and may not be suitable for protection against sharply pointed objects such as hypodermic needles. For impact protection, the protection level is the lowest of the two. **Warning:** protection does not apply to the finger. Padding on the back of the hand and fingers offer no protection.

EN 511:2006 Cold Protection (f) Resistance to convective cold [Thermal Insulation I_{clo} in m^2 K/W] (g) Resistance to contact cold [Thermal Insulation I_{clo} in m^2 K/W] (h) Resistance to cold penetration. **Notes:** Gloves may take their insulative properties when wet. Contact the manufacturer for more information on determining maximum permissible user exposure. **Warning:** For multi-layer gloves, performance levels are applicable to the whole glove including all layers. Please consider environmental temperature, atmospheric conditions, wind speed, health and well-being of the person, effect of other protective clothing, the type of activity, the type of equipment, activity level, dexterity requirement, contact with cold items and contact with wet or dry objects when selecting this PPE.

EN 407:2020 Thermal risks (i) Limited flame spread [After flame - seconds] (j) Limited flame spread [Glow time - seconds] (k) Convective heat (l) Contact heat [Thermal Transfer - seconds] (m) Small Splashes of Molten Metal [Number of droplets] (n) Large Splashes of Molten Metal [Molten mass - grams] **Note:** The glove comes into contact with a heat source. Gloves that performance are designed against "small splashes of molten metal" are not suitable for welding activities. For gloves tested against large quantities of molten metal, (n), the glove must not ignite, melt, shrink or separate in a way that would expose the wearer's skin after cut off the glove. In the event of a molten metal splash, the glove may not eliminate all risks of burn. Due to the application of the glove, it cannot be ruled out that there is a need of pain or other medical treatment or removal of the product requires the intervention of another person. The glove is not intended for use in wet conditions.

Recommendations: Do not use in those jobs where the level of mechanical risk to cover exceeds the levels of benefits indicated. **Warning:** These gloves are designed for use in low risk mechanical hazards. Do not use in those jobs where the level of mechanical risk to cover exceeds the levels of benefits indicated. Gloves should always be inspected by the user before use to ensure no damage is present. For gloves with two or more layers the overall classification may be necessarily reflect the performance of outmost layer. **Obsolescence:** When stored properly, will not suffer changes in the mechanical properties up to 3 years from the date of manufacture. **Cleaning:** Wash gloves with mild soap and lukewarm water before first use to remove any residue from the glove. **Storage:** Store in a dry and cool place, protected from sunlight and any other sources of heat and ignition. Storage conditions in the premises do not change from the date of manufacture. No special packaging is required for transport and conservation, but product must remain flat. **Cleaning instructions:** Washing is not recommended as gloves may lose their initial performance. For cleaning you can use a damp cloth. **Note:** The information contained herein and the results of the laboratory tests are intended to help the user select the PPE. However, it should be understood that the actual conditions of use are beyond the control of the manufacturer and therefore it is the responsibility of the user to make the final decision on the suitability of the glove. **Use:** protective gloves only for the intended use and use the right size. **Inspection:** Check for any defects before each use. **Tactile:** Tactile sensitivity and dexterity reduce with your fitting of gloves and fatigue in hands and finger. Wrong size and poor fitting leads to poor hand protection. **Glove donning:** Ensure the selection of appropriate glove size. Pull the glove on the hand and adjust for comfort. **Glove doffing:** Pinch the glove at the wrist area and pull it off the hand, ensure that the inner side of the gloves is worn out or is damaged. When contaminated is not removable or presents a potential hazard, it is advisable to remove left and right gloves alternately using the gloved hand so that gloves are removed without the contaminant touching the hand. **Hand Hygiene:** Wash hands before use, after use and periodically during use with mild soap and lukewarm water. Dry thoroughly. Use a moisturizer if desired. Avoid use of products containing oils or petroleum products. Please dispose according to local authority regulations. **Leaflet:** Keep the leaflet with the product. For additional information consult your supplier.

Conformity: Conformity to the EU Regulation 2016/425 for PPE, as brought to UK Law and amended, through European standards EN ISO 21420:2020; EN388:2016+A1:2018 and EN407:2020. Category II

Notified Body: CTC, 4 Rue Hermann Frenkel, 69007 Lyon, FR (notified body number 0075).

Manufacturer: Uniglovs Nitrex Ltd, Unit 1 Ashfield Industrial Estate, Ashfield Road, Chesham, Buckinghamshire, HP5 3QT, UK

Storage: Store in a dry and cool place, protected from sunlight and any other sources of heat and ignition. Storage conditions in the premises do not change from the date of manufacture. No special packaging is required for transport and conservation, but product must remain flat. **Cleaning instructions:** Washing is not recommended as gloves may lose their initial performance. For cleaning you can use a damp cloth. **Note:** The information contained herein and the results of the laboratory tests are intended to help the user select the PPE. However, it should be understood that the actual conditions of use are beyond the control of the manufacturer and therefore it is the responsibility of the user to make the final decision on the suitability of the glove. **Use:** protective gloves only for the intended use and use the right size. **Inspection:** Check for any defects before each use. **Tactile:** Tactile sensitivity and dexterity reduce with your fitting of gloves and fatigue in hands and finger. Wrong size and poor fitting leads to poor hand protection. **Glove donning:** Ensure the selection of appropriate glove size. Pull the glove on the hand and adjust for comfort. **Glove doffing:** Pinch the glove at the wrist area and pull it off the hand, ensure that the inner side of the gloves is worn out or is damaged. When contaminated is not removable or presents a potential hazard, it is advisable to remove left and right gloves alternately using the gloved hand so that gloves are removed without the contaminant touching the hand. **Hand Hygiene:** Wash hands before use, after use and periodically during use with mild soap and lukewarm water. Dry thoroughly. Use a moisturizer if desired. Avoid use of products containing oils or petroleum products. Please dispose according to local authority regulations. **Leaflet:** Keep the leaflet with the product. For additional information consult your supplier.

EN

Entsprycht dyr EU-Verordnung 2016/425 fy PSA, dr durch die europäischen Normen EN ISO 21420:2020; EN388:2016+A1:2018 und EN407:2020 in britisches Recht umgesetzt und geändert wurde. Kategorie II

Dur EU-Baumusterprüfung wurde durchgeführt von: CTC, 4 Rue Hermann Frenkel, 69007 Lyon, FR (zugelassene Stelle Nummer 0075).

EN 374-1:2016+A1:2018 Wenn der markierte Wert X ist, bedeutet dies, dass der Handschuh nicht getestet wurde oder die Testmethode nicht angemessen ist. Die Handschuhe wurden im Bereich der Handfläche getestet. Es wird empfohlen, diese Verpackung zum Nachschlagen aufzubewahren. Der Handschuh enthält Beschleuniger, die allergische Reaktionen verursachen können. Diese Informationen spiegeln nicht die tatsächliche Dauer des Schutzes am Arbeitsplatz und die Unterschreitung zwischen Gemischen und reinen Chemikalien wider. Die chemische Beständigkeit wurde unter Laborbedingungen an Proben mit einer Dicke von 400 mm - zu einer Ausnahme bei Handschuhen mit einer Länge

BG Съответства на Регламент 2016/425 на ЕС за личните предпазни средства, както е въведен в законодателството на Обединеното кралство и на Европейския съюз, чрез европейските стандарти EN ISO 21420:2020; EN388:2016+A1:2018 и EN407:2020. Категория II

Изследователска на тип ЕО, извършено от: CTC, 4 Rue Hermann Frenkel, 69007 Lyon, FR (одобрено орган № 0075).

EN ISO 374-1:2016+A1:2018 Когатоماركирането е в X, тоа означава, че въведената е на бета тестови или не методи/ти на тестови не е подходящ. Лабораторите се тестират и одобряват за дадена производствена или дадените такива операции за справка. Съдържа уксусна киселина, която може да предизвикат алергични реакции. Съдържа ментоксиметан, който може да предизвикат алергична реакция. Съдържа 1,2-бензизотиазолин-3-он, който може да предизвикат алергична реакция. Съдържа 2-октилизотиазолин-3-он, който може да предизвикат алергична реакция. Съдържа 5-хлоро-2-метилизотиазолин-3-он [и] 2-метилизотиазолин-3-он (3:1),