UNI NITREX
HAND PROTECTION RANGE
3 ORF
INSTRUCTIONS FOR USE

3400RF-06 6
3400RF-07 7
3400RF-08 8
3400RF-09 9
3400RF-10 10
3400RF-11 11

EN388:2016+A1:2018

	1	2	3	4	5
a	100	500	2000	8000	5
b	0.5	1.2	2.5	5	10
c	10	25	50	75	5
d	60	200	400	150	–
e	A	B	C	D	–

EN511:2006

	1	2	3
X	0.10 x1TR ≤0.15	0.15 x1TR <0.22	0.22 x1TR <0.30
Y	0.025 x9 <0.050	0.050 x9 <0.100	0.100 x9 <0.150
Z	h	h	h

EN407:2020

	1	2	3	4	5
X	≥15	≥10	≥3	≥2	≥1
Y	≥35	≥25	≥15	≥5	P
Z	k	100	250	350	500
A	h	≥4	≥7	≥10	≥18
B	m	≥7	≥20	≥50	≥95
C	n	≥10	≥15	≥25	≥35
D	o	30	60	120	200

EN 374-1 / EN 374-2 / EN 374-3

	1	2	3	4	5	6
AQL	4.0	1.5	0.65	0.25	0.10	0.04

EN 374-4

	1	2	3	4	5
Time	30 min	60 min	120 min	240 min	480 min

EN 374-5

	1	2	3
Time	30 min	60 min	120 min

Complies with EU Regulation 2016/425 for PPE, as brought to UK Law and amended, through European standards EN ISO 21420:2020; EN388:2016+A1:2018 and EN407:2020. Category II

The EU type examination conducted by: SATRA, Bracetown Business Park, Clonee, D15 YN2P, IRL (notified body number 2777).

EN ISO 374-1:2016+A1:2018 When the marked level is X it indicates that the glove has not been tested or the test method is not adequate. Gloves have been tested in the palm area. You are advised to retain this packaging for reference. Contact accelerators which may cause allergic reactions. This information does not reflect the actual duration of protection in the workplace and the manufacturer recommends a risk assessment be carried out under your conditions of use. It is recommended under laboratory conditions from samples taken from the palm only (except in cases where the glove is equal to or over 400 mm - where the cuff is also tested). Gloves of the same model but of a different size or colour may offer a different level of protection. Chemicals, degradation can be the most important factor to consider in selection of chemical resistant gloves. Before usage, inspect the gloves for any defect or imperfections. EN ISO 374-4:2019 Degradation levels indicate the change in puncture resistance after immersion in the chemical. Gloves should be tested under laboratory conditions and retested under laboratory conditions and relates only to the tested specimen. You are advised to retain this packaging for reference.

EN 388:2016+A1:2018 Mechanical risk(s) Abrasion resistance [cycles]; Cut resistance (c) Tearing resistance [N] Puncture resistance [N] Cut resistance (d) Coup Test [N]. Note: Cut resistance is the reference performance results applicable to products with levels 2 and 3 only. Cut resistance (d) Coup Test: Cut resistance is the reference performance results applicable to products with levels 2 and 3 only. Alternatively, Alternatively, cut resistance can be measured using a test method that may not be suitable for protection against sharply pointed objects such as hypodermic needles. For impact protection, the protected area of the hand, the **Marking**: protection does not apply to the finger. Padding on the back of the hand and fingers offer no protection.

EN 511:2006 Cold Protection (1) Resistance to convective cold [Thermal Insulation I_{clo} in m^2 K/W] (g) Resistance to contact cold [Thermal Insulation I_{clo} in m^2 K/W] (h) Resistance to cold water penetration. **Notes**: Gloves may have their insulative properties wear well. Contact the manufacturer for more information on determining maximum permissible user exposure. **Warning**: For cuffs when protective gloves are applicable to the whole glove including all layers. Please consider environmental temperature, atmospheric conditions, wind speed, health and well-being of the person, effect of other protective clothing, the type of work, the duration of the exposure, activity level, dexterity requirement, contact with cold items and contact with wet or dry objects when selecting this PPE.

EN 407:2020 Thermal risks (1) Limited flame spread [After flame - seconds] (2) Limited flame spread [Glow time - seconds] (3) Contact heat [Transfer time - seconds] (4) Convective heat [Time - seconds] (5) Radiant heat [Heat Transfer T_{50} - seconds] (6) Small Splashes of Molten Metal [Number of droplets] (7) Large Splashes of Molten Metal [Molten mass - grams]. **Note**: The glove comes into contact with a heat source. Gloves that performance are against "small splashes of molten metal" are not suitable for welding activities. For gloves tested against large quantities of molten metal, it is the duty of the user to assess the risk of burns from molten metal splash and shall leave the remainder of the glove. In the event of a molten metal splash, the glove may not eliminate all risks of burn. Due to the application of the glove, it cannot be ensured that it will be possible to remove the glove without removal of the product requires the intervention of another person. The glove is not intended for use in wet conditions.

Recommendations: Do not use in those jobs where the level of mechanical risk to cover exceeds the levels of benefits indicated. **Warning:** These gloves are designed for use in low risk mechanical hazards. Do not use in those jobs where the level of mechanical risk to cover exceeds the levels of benefits indicated. Gloves should always be inspected by the user before use to ensure no damage is present. For gloves with two or more layers the overall classification may not necessarily reflect the performance of outmost layer. **Obsolescence:** When stored properly, will not suffer changes in the mechanical properties up to 3 years from the date of manufacture. **Cleaning:** Do not dry clean, do not bleach, do not tumble dry, do not iron, do not immerse in solvents. **Disposal:** Use protective gloves only for the intended use and use the right size. **Inappropriate glove:** Tactile sensitivity and dexterity reduce with your fitting of gloves fatigue in hands and finger. Wrong size and poor fitting leads to poor hand protection. **Glove donning:** Ensure the selection of appropriate glove size. Check the glove for any damage before donning. Ensure hands are dry before donning gloves. Donning gloves with wet or damp hands may cause the gloves to wear out or is damaged. When contaminated is not removable or presents a potential hazard, it is advisable to remove left and right gloves alternately, using the gloved hand so that gloves are removed without the contaminant touching the hand. **Hand Hygiene:** Wash hands before use, after use and periodically during use. **Disposal:** Used gloves may be contaminated with infectious or harmful substances. Handle and dispose of contaminated gloves in accordance with local authority regulations. **Storage:** Store in a dry and cool place, protected from sunlight and strong chemicals. Storage conditions: Keep in the original packaging. Storage temperature: Do not exceed 50°C. **Sterilization:** Sterilizing is not recommended as gloves may have their initial performance. Sterilizing may cause a decrease in the mechanical properties do not change from the date of manufacture. No special packaging is required for transport and conservation, but product must remain flat. **Cleaning instructions:** Wash

Съответства на Регламент (ЕО) 1907/2006 относно REACH за Личните предпазни средства, както е изменен в законодателната уредба на Европейския съюз, чрез европейските стандарти EN ISO 21420:2020; EN388:2016+A1:2018 и EN407:2020. Категория II

Обозначаването на типа на ЕС, извършено от: SATRA, Bracetown Business Park, Clonee, D15 YN2P, IRL (продуктови групи № 2777).

EN ISO 374.1:2016+A1:2018 Когатоماركирането е ясно К, тоа означава, че ръкавицата не е била тестована или не матрицата е по-малка от тестваме не е подходна. Ръкавицата се тестваме и дефектите не се допускат. Препоръчваме ви да запазите тази опаковка за справка. Съхранете ръкавиците, когато могат да предпазяват алергичните реакции. Тази информация е предоставена от производителя на ръкавиците. Ако имате алергична реакция, трябва да потърсите медицинска помощ веднага и да спрете използването на ръкавиците. Хемикалиите устойчивост и оценка в лабораторни условия от проби, взети от доставки от дистрибутори, не е 400 min - ръка на ръкавицата. Ръкавиците не трябва да бъдат изпитвани при по-ниски от 14 °C и/или с по-ниска от тестваните химикали. Тя може да бъде различна, ако химикатите с изпитвания в Спец. Температура на ръцете. Производителят не предоставя данни ръкавицата, не е подходяща, ръцете. Ръкавиците не трябва да се използват на работното място могат да доведат до изгаряния на тялото и замърсяват от температурата, основаващата се на ръцете. Ръкавиците трябва да бъдат изхвърлени, ако е видимо замърсени с вещество, с което е в контакт, или ако замърсяването може да бъдат изхвърлени, ако е видимо замърсени с вещество, с което е в контакт с химикалка, и т.н. могат значително да намалят действителното време на употреба. При проникване на химикали, които представляват риск за здравето, е по-вероятно, че ръцете ви ще бъдат изложени на по-високи концентрации на опасни химически устройства ръкавици. Преди употребата проверете ръкавиците за всякакви дефекти или нескъсващи. Ако е по-вероятно, че ръцете ви ще бъдат изложени на опасни химикали, е по-вероятно, че ръцете ви ще бъдат изложени на по-високи концентрации на опасни химикали