UNIGLOVES® NITREX

HAND PROTECTION RANGE

INSTRUCTIONS FOR USE

Instructions Anleitung Instructions Istruzioni Instrucciones Instrukcja Użytkowania Інструкція Instrucțiuni Instructies Talimatlar Οδηγίες Utasítások Instruktioner Pokyny Instruções Упутства Инструкции Upute Vejledning Ohjeet Bruksanvisning Pokyny Instrukcijos Navodila Instrukcijas Инструкции Juhised

245RP

245RP - 18" (45cm) L

EN388:2016+A1:2018

		1	2	3	4	5	
3	a	100	500	2000	8000	-	-
X	b	1.2	2.5	5	10	20	-
4	c	10	25	50	75	-	-
X	d	20	60	100	150	-	-
F	e	A	B	C	D	E	F

EN511:2006

		1	2	3	4
X	f	0.10 ≤ ITR <0.15	0.15 ≤ ITR <0.22	0.22 ≤ ITR <0.30	0.30 ≤ ITR
X	g	0.025 ≤R <0.050	0.050 ≤R <0.100	0.100 ≤R <0.150	0.150 ≤R
X	h				

EN407:2020

		1	2	3	4
X	i	≤15	≤10	≤3	≤2
X	k	100	250	350	500
X	l	≥4	≥7	≥10	≥18
X	m	≥7	≥20	≥50	≥95
X	n	≥10	≥15	≥25	≥35
X	o	30	60	120	200

EN ISO 15797

5 x 75°c 5 x

EN ISO 374-1:2016+A1:2018

EN ISO 374-1	EN ISO 374-2	EN ISO 374-4	EN ISO 374-5
X	X	X	X

EN ISO 374-1	EN ISO 374-1	EN ISO 374-4 (%)
A	X	X
B	X	X
C	X	X
D	X	X
E	X	X
F	X	X
G	X	X
H	X	X
I	X	X
J	X	X
K	X	X
L	X	X
M	X	X
N	X	X
O	X	X
P	X	X
Q	X	X
R	X	X
S	X	X
T	X	X

EN

Complies with EU Regulation 2016/425 for PPE, as brought to UK Law and amended, through European standards EN ISO 21420:2020 and EN388:2016+A1:2018. Category II

The EU type examination conducted by: Eurofins Textile Testing Spain, S.L.U. C/ Germán Bernácer 4 03203 Elche (Alicante), ES (notified body number 2865).

EN ISO 374-1:2016+A1:2018 When the marked level is X it indicates that the glove has not been tested or the test method is not adequate. Gloves have been tested in the palm area. You are advised to retain this packaging for reference. Contains accelerators which may cause allergic reactions. This information does not reflect the actual duration of protection in the workplace and the differentiation between mixtures and pure chemicals. The chemical resistance has been assessed under laboratory conditions from samples taken from the palm only (except in cases where the glove is equal to or over 400 mm - where the cuff is tested also) and relates only to the chemical tested. It can be different if the chemical is used in a mixture. It is recommended to check that the gloves are suitable for the intended use because the conditions at the workplace may differ from the type test depending on temperature, abrasion and degradation. When used, protective gloves may provide less resistance to the dangerous chemical due to changes in physical properties. Movements, snagging, rubbing, degradation caused by the chemical contact etc. may reduce the actual use time significantly. For corrosive chemicals, degradation can be the most important factor to consider in selection of chemical resistant gloves. Before usage, inspect the gloves for any defect or imperfections. EN ISO 374-4:2019 Degradation levels indicate the change in puncture resistance of the gloves after exposure to the challenge chemical. The penetration resistance has been assessed under laboratory conditions and relates only to the tested specimen. You are advised to retain this packaging for reference.

EN 388:2016+A1:2018 Mechanical risks(a) Abrasion resistance [cycles] (b) Cut resistance (c) Tearing resistance [N] (d) Puncture resistance [N] (e) Resistance to TDM cut test [N]. **Notes:** For dulling during the cut resistance test, the coupe test results are only indicative while the TDM cut resistance is the reference performance results (applicable to products with both EN and TDM cut results presented). Gloves meeting the requirement for resistance to puncture may not be suitable for protection against sharply pointed objects such as hypodermic needles. For impact protection, the protected area is the back of the hand. **Warning:** protection does not apply to the finger. Padding on the back of the hand and fingers offer no protection.

EN 511:2006 Cold Protection (f) Resistance to convective cold [Thermal Insulation I_{TR} in m^2 K/W] (g) Resistance to contact cold [Thermal resistance R in m^2 K/W] (h) Permeability to water [water penetration]. **Notes:** Gloves may lose their insulative properties when wet. Contact the manufacturer for more information on determining maximum permissible user exposure. **Warning:** For multi-layer gloves, performance levels are applicable to the whole glove including all layers. Please consider environmental temperature, atmospheric conditions, wind speed, health and well-being of the person, effect of other protective clothing worn by the person, time of exposure, activity level, dexterity requirement, contact with cold items and contact with wet or dry objects when selecting this PPE.

EN 407:2020 Thermal risks (i) Limited flame spread [After flame - seconds] (j) Limited flame spread [Glow time - seconds] (k) Contact Heat [contact temperature °C] (l) Convective Heat [Heat Transfer HTI - seconds] (m) Radiant Heat [Heat Transfer t_{24} - seconds] (n) Small Splashes of Molten Metal [Number of droplets] (o) Large Splashes of Molten Metal [Molten metal - grams]. **Notes:** The glove should not come into contact with a naked flame. Gloves only tested against "small splashes of molten metal" are not suitable for welding activities. For gloves tested against large quantities of molten metal, in the event of a molten metal splash the user shall leave the working place immediately and take off the glove. In the event of a molten metal splash, the glove may not eliminate all risks of burn. Due to the application of the glove, it cannot easily be removed in case of an emergency. Glove removal of the product requires the intervention of another person. The glove is not intended for use in wet conditions.

Recommendations: Do not use in those jobs where the level of mechanical risk to cover exceeds the levels of benefits indicated. **Warning:** These gloves should not be used when there is a risk of entanglement by moving parts of machines. **Warning:** contains accelerators which may cause allergic reactions. Glove should always be inspected by the user before use to ensure no damage is present. For gloves with two or more layers the overall classification does not necessarily reflect the performance of outmost layer. **Obsolescence:** When stored properly, will not suffer changes in the mechanical properties up to 5 years from the date of manufacture. **Service life:** Cannot be specified and depends on application and responsibility of the user to ascertain suitability of the gloves for its intended use. **Storage:** Store in a dry and cool place, protected from sunlight and any other aggressive agents. With proper storage, the mechanical properties do not change from the date of manufacture. No special packaging is required for transport and conservation, but product must remain flat. **Cleaning instructions:** Washing is not recommended as gloves may lose their initial performance, for cleaning you can use a damp cloth. **Note:** The information contained herein and the results of the laboratory tests are intended to help the user select the PPE. However, it should be understood that the actual conditions of use cannot be similar. It is therefore the responsibility of the end user and not the manufacturer, to ensure the suitability of the glove for the intended use. **Use:** protective gloves only for the intended use and use the right size. **Inappropriate glove use:** Tactile sensitivity and dexterity reduce with poor fitting of glove cause fatigue in hands and finger. Wrong size and poor fitting leads to poor hand protection. **Glove donning:** Ensure the selection of appropriate glove size. Check for any physical damage or contamination prior to use. Discard if there is any damage or contaminant. **Glove doffing:** Remove the glove as soon as it wears out or is damaged. When contaminant is not removable or presents a potential hazard, it is advisable to remove left and right gloves alternately using the gloved hand so that gloves are removed without the contaminant touching the hand. **Hand Hygiene:** Wash hands before use, after use and periodically during use. **Disposal:** Used gloves may be contaminated with infectious or other hazardous materials. Please dispose according to local authority regulations. Landfill or incinerate under controlled conditions. For additional information consult your supplier.

PT

Cumpre o Regulamento da UE 2016/425 para PPE, tal como transposto para a legislação do Reino Unido e alterado, através das normas europeias EN ISO 21420:2020 e EN388:2016+A1:2018. Categoria II

O exame de tipo UE realizado por: Eurofins Textile Testing Spain, S.L.U. C/ Germán Bernácer 4 03203 Elche (Alicante), ES (organismo aprovado número 2865).

NL

Voldoet aan EU-verordening 2016/425 voor persoonlijke beschermingsmiddelen, zoals omgezet in Britse wetgeving en gewijzigd, via de Europese normen EN ISO 21420:2020 en EN388:2016+A1:2018. Categorie II

Het EU-typeonderzoek wordt verricht door: Eurofins Textile Testing Spain, S.L.U. C/ Germán Bernácer 4 03203 Elche (Alicante), ES (erkend organisatienummer 2865).

PL

Zgodność z rozporządzeniem UE 2016/425 dla środków ochrony indywidualnej, wprowadzonym do prawa brytyjskiego i zmienionym, poprzez normy europejskie EN ISO 21420:2020 i EN388:2016+A1:2018. Kategoria II

Badanie typu UE przeprowadzone przez: Eurofins Textile Testing Spain, S.L.U. C/ Germán Bernácer 4 03203 Elche (Alicante), ES (numer jednostki zatwierdzonej 2865).

245RP

13 gauge green cut resistant sustainable sleeve 45cm	13-kanalni zeleni trajnostni rokav odporen na rezanje 45 cm
45cm nachhaltiges 13-Gauge-Material, grüner schnittbeständiger Ärmel	13 gauge grøn skærebestandig bæredygtig ærme 45 cm
Manchon durable résistant aux coupures, de calibre 13, vert, 45 cm	13 gaugen vihreä viiltosuojattu kestävä hiha 45 cm
Manguito anti-corte verde sostenible galga 13 - 45 cm	13 gabariit roheline lõikekindel jätkusuutlik varrukas 45cm
Manicotto sostenibile resistente al taglio verde calibro 13 calibro 45cm	13 gauge yeşil kesilmeye dayanıklı sürdürülebilir kılıf 45cm
Manga anti-cortes verde sustentável malha galga 13 - 45 cm	13 gauge zöld vágásálló fenntartható ujj 45cm
13 gauge groene snijbestendige duurzame hoes 45 cm	Rukáv odolný proti proříznutí, 13 gauge, zelený, 45 cm
zarękawek antyprzecięciowy, zielony, 13gg, dł. 45 cm, przyjazny dla środowiska	Udržateľný rukáv zelenej farby odolný voči prerezaniu 45 cm
13 gauge grön skärbeständig hållbar ärm 45cm	13 collu zaļa, pret griešanu izturīga, ilgtspējīga piedurkne 45cm
13 gauge grønn kuttbestandig, bærekraftig erme 45 cm	Πράσινο μανίκι ανθεκτικό στην κοπή, οικολογικά, 13 gauge (πυκνότητα πλέξης), 45 εκατοστά
13 storio žalia pjovimui atspari tvari rankovė 45cm	Зелена, отпорна на сечење, одржлива ракавка од 13 калибар 45 см
Rukav otporan na sečenje, zeleni, 45 cm, kalibar 13	
13 gauge verde tăiat rezistent manșon durabil 45cm	
13 гага зелено противосрезни ръкавели 45 см	
Rukav otporan na rezanje, zelena boja 13, 45 cm	
13 калібру зелений стійкий до порізів міцний рукав 45см	

DECLARATION OF CONFORMITY
KONFORMITÄTSERKLÄRUNG
DÉCLARATION DE CONFORMITÉ
DECLARACIÓN DE CONFORMIDAD
DICHIARAZIONE DI CONFORMITÀ
DECLARAÇÃO DE CONFORMIDADE
CONFORMITEITSVERKLARING
DEKLARACJA ZGODNOŚCI
FÖRSÄKRAN OM ÖVERENSSTÄMMELSE
SAMSVARSERKLÆRING
ATITIKTIES DEKLARACIJA
IZJAVA O SUKLADNOSTI
DECLARAȚIE DE CONFORMITATE
ДЕКЛАРАЦИЯ ЗА СЪОТВЕТСТВИЕ
ДЕКЛАРАЦИЈА О УСАГЛАШЕНОСТИ
ДЕКЛАРАЦІЯ ВІДПОВІДНОСТІ
IZJAVA O SKLADNOSTI
OVERENSSTEMMELSESERKLÆRING
VAATIMUSTENMUKAISUUSVAKUUTUS
VASTAVUSDEKLARATSIOON
UYGUNLUK BEYANI
MEGFELELŐSÉGI NYILATKOZAT
PROHLÁŠENÍ O SHODĚ
VYHLÁSENIE O ZHODE
ATBILSTĪBAS DEKLARĀCIJA
ΔΗΛΩΣΗ ΣΥΜΜΟΡΦΩΣΗΣ
ДЕКЛАРАЦИЈА ЗА СООБРАЗНОСТ

CE www.nitrex.es/es/245RP/

UNIGLOVES®
Registered office: 37 St. Margaret's Street, Canterbury, Kent, CT1 2TU, UK
Tel. +44 (0)800 049 6602 • uk.unigloves.com

UG NITREX SL
Ezurriki, 13 - 20305 IRUN - España
Tel. + 34 943 633282 • Fax +34 943 633261 • nitrex.es

UNIGLOVES®
Arzt- & Klinikbedarf Handelsgesellschaft mbH, Camp-Spich-Straße 71,
D-53842 Troisdorf, Germany • Tel. +49 (0)2241 9323 0 • de.unigloves.com