




### DIMENSIONS



### ACCESSORIES



SWAP IP54 ACCESSORY



SWAP ADD-ON BEZEL

### AWARDS


reddot design award  
winner 2015

GERMAN  
DESIGN  
AWARD  
NOMINEE  
2016

### PRODUCT

|           |                                   |
|-----------|-----------------------------------|
| Name      | SWAP ASYM M 7W DIM PH.CUT 4000K W |
| Reference | A2162222W                         |
| Color     | Matt white                        |
| Category  | CEILING RECESSED                  |

### LIGHTING INFORMATION

|                                                   |                                       |
|---------------------------------------------------|---------------------------------------|
| Light source                                      | LED                                   |
| Gross luminous flux                               | 960 Lm                                |
| Power                                             | 7 W                                   |
| Power values of the system                        | 9,33 W                                |
| Colour temperature                                | 4000 K                                |
| Colour Rendering Index                            | CRI>90                                |
| Chromatic stability                               | Mac Adam Step 2                       |
| Light beam angle                                  | 45°                                   |
| Lighting efficiency                               | 86%                                   |
| Efficacy                                          | 137 Lm/W                              |
| Current intensity                                 | 200 mA                                |
| Dimming                                           | Phase Cut - Other DIM, please consult |
| Driver                                            | Incl. - Fast Connect                  |
| Fast connection of the driver to the mains supply | Please Consult                        |
| Emergency power supply                            | Please Consult                        |
| Electrical insulation class                       | □                                     |
| Voltage                                           | 220 V/240 V                           |
| Frequency                                         | 50/60 Hz                              |
| Energy efficiency                                 | A++                                   |
| LED lifespan                                      | L80B10 (Tj=85°C) >60.000h             |


### OTHER DATA

|                     |                           |
|---------------------|---------------------------|
| Ingress Protection  | IP20                      |
| Recess measurements | Ø75 mm.                   |
| Weight              | 215 g.                    |
| Packaged weight     | 256 g.                    |
| Units per package   | 20                        |
| Materials           | Aluminium / Polycarbonate |





Swap is a ceiling recessed LED spotlight whose main features are its minimalist aspect, its perfect integration into the ceiling, and considerable visual comfort, thanks to the small reflector that is set back with respect to the ceiling plane. When it is switched on, its matte finish shade generates an attractive effect, a discrete circle of light. It includes an add-on bezel that can be used optionally to cover larger recess diameters.

POLAR DIAGRAM



CONICAL DIAGRAM





| PRODUCT                                                                                                              |                  |
|----------------------------------------------------------------------------------------------------------------------|------------------|
| Model                                                                                                                | IP54 Accessory M |
| Reference                                                                                                            | A2122054         |
| Category                                                                                                             | Accessories      |
| <p>PRE-ASSEMBLED. NOT SOLD SEPARATELY.<br/>NOT COMPATIBLE WITH EXTRA BEZEL.<br/>AFFECTS THE LIGHTING PARAMETERS.</p> |                  |
| <p>EXCL   ACC. 45°</p>                                                                                               |                  |

To make the difference, Swap IP54 reaches a high sealing level, maintaining at the same time the same aesthetics as a standard Swap. The insulating property is obtained thanks to a protection placed just over the LED, and a silicone joint on the internal part of the bezel. In this way, the external aspect of Swap IP54 is identical to any other Swap IP20. Swap offers the possibility of requesting any of its models with IP54-rated weather resistance, which converts it into an optimal luminaire to be installed in atmospheres where the product may suffer from the impact of water or frequent presence of humidity.



| PRODUCT  |                                |
|----------|--------------------------------|
| Model    | Swap M Asymmetric Add-On Bezel |
| Colour   | W □   Matt white               |
| Category | Accessories                    |



Ⓡ 75-79  
+

Ⓡ 79-91

Accessory always included but for optional use. It extends the piece's bezel to cover larger recesses, keeping Swap's minimalism and its perfect integration into the ceiling. Easy to fit. Ideal for reforms to replace the light spot, with the already existing holes, without altering the ceiling or repainting. Swap is the best option for updating to LED technology by means of a real light fixture with incorporated LED, in contrast to just a retrofit lamp that only implies a less efficient update of the light source.