




DIMENSIONS



ACCESSORIES



SWAP IP54 ACCESSORY



SWAP ADD-ON BEZEL

AWARDS


reddot design award
winner 2015

GERMAN
DESIGN
AWARD
NOMINEE
2016

PRODUCT

Name	SWAP M SUPERCRI 7W 2700K W
Reference	A3122210W
Color	Matt white
Category	CEILING RECESSED

LIGHTING INFORMATION

Light source	LED
Gross luminous flux	770 Lm
Power	7 W
Power values of the system	8,75 W
Colour temperature	2700 K
Colour Rendering Index	CRI>97
Chromatic stability	Mac Adam Step 2
Light beam angle	42°
Unified Glare Rating	UGR<19
Lighting efficiency	86%
Efficacy	110 Lm/W
Current intensity	200 mA
Dimming	No Dim - Other DIM, please consult
Driver	Incl. - Fast Connect
Fast connection of the driver to the mains supply	Please Consult
Emergency power supply	Please Consult
Electrical insulation class	□
Voltage	220 V/240 V
Frequency	50/60 Hz
Energy efficiency	A+
LED lifespan	L80B10 (Tj=85°C) >60.000h


OTHER DATA

Ingress Protection	IP20
Recess measurements	Ø75 mm.
Weight	215 g.
Packaged weight	255 g.
Units per package	20
Materials	Aluminium / Polycarbonate




Swap is a ceiling recessed LED spotlight whose main features are its minimalist aspect, its perfect integration into the ceiling, and considerable visual comfort, thanks to the small reflector that is set back with respect to the ceiling plane. When it is switched on, its matte finish shade generates an attractive effect, a discrete circle of light. It includes an add-on bezel that can be used optionally to cover larger recess diameters.

POLAR DIAGRAM




CONICAL DIAGRAM



UGR

Glare Evaluation According to UGR												
p Ceiling		70	70	50	50	30	70	70	50	50	30	
p Walls		50	30	50	30	30	50	30	50	30	30	
p Floor		20	20	20	20	20	20	20	20	20	20	
Room Size X Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis					
2H	2H	15.0	15.7	15.2	15.9	16.1	15.0	15.7	15.2	15.9	16.1	
	3H	16.8	17.5	17.1	17.7	17.9	16.8	17.5	17.1	17.7	17.9	
	4H	17.6	18.2	17.9	18.5	18.8	17.6	18.2	17.9	18.5	18.8	
	6H	18.3	18.9	18.7	19.2	19.5	18.3	18.9	18.7	19.2	19.5	
	8H	18.7	19.3	19.0	19.6	19.9	18.7	19.3	19.0	19.6	19.9	
	12H	19.0	19.6	19.4	19.9	20.2	19.0	19.6	19.4	19.9	20.2	
4H	2H	15.5	16.2	15.8	16.5	16.7	15.5	16.2	15.8	16.5	16.7	
	3H	17.6	18.2	18.0	18.5	18.8	17.6	18.2	18.0	18.5	18.8	
	4H	18.6	19.1	19.0	19.4	19.8	18.6	19.1	19.0	19.4	19.8	
	6H	19.5	19.9	19.9	20.3	20.7	19.5	19.9	19.9	20.3	20.7	
	8H	20.0	20.3	20.4	20.7	21.1	20.0	20.3	20.4	20.7	21.1	
	12H	20.4	20.7	20.8	21.1	21.5	20.4	20.7	20.8	21.1	21.5	
8H	4H	19.0	19.3	19.4	19.7	20.1	19.0	19.3	19.4	19.7	20.1	
	6H	20.1	20.4	20.5	20.8	21.3	20.1	20.4	20.5	20.8	21.3	
	8H	20.7	20.9	21.1	21.4	21.8	20.7	20.9	21.1	21.4	21.8	
	12H	21.3	21.5	21.8	21.9	22.4	21.3	21.5	21.8	21.9	22.4	
12H	4H	19.0	19.4	19.5	19.8	20.2	19.0	19.4	19.5	19.8	20.2	
	6H	20.2	20.5	20.7	20.9	21.4	20.2	20.5	20.7	20.9	21.4	
	8H	20.9	21.1	21.4	21.5	22.0	20.9	21.1	21.4	21.5	22.0	
Variation of the observer position for the luminaire distances S												
S = 1.0H S = 1.5H S = 2.0H		+1.0 / -0.3 +2.1 / -0.5 +3.2 / -0.8					+1.0 / -0.3 +2.1 / -0.5 +3.2 / -0.8					
Standard table		BK06					BK06					
Correction Summand		3.8					3.8					
Corrected Glare Indices referring to 770lm Total Luminous Flux												



PRODUCT	
Model	IP54 Accessory M
Reference	A2122054
Category	Accessories
PRE-ASSEMBLED. NOT SOLD SEPARATELY. NOT COMPATIBLE WITH EXTRA BEZEL. AFFECTS THE LIGHTING PARAMETERS.	
EXCL. I ACC. 	

To make the difference, Swap IP54 reaches a high sealing level, maintaining at the same time the same aesthetics as a standard Swap. The insulating property is obtained thanks to a protection placed just over the LED, and a silicone joint on the internal part of the bezel. In this way, the external aspect of Swap IP54 is identical to any other Swap IP20. Swap offers the possibility of requesting any of its models with IP54-rated weather resistance, which converts it into an optimal luminaire to be installed in atmospheres where the product may suffer from the impact of water or frequent presence of humidity.



PRODUCT	
Model	Swap M Add-On Bezel
Colour	W □ Matt white
Category	Accessories



① 75-79
+

② 79-91

Accessory always included but for optional use. It extends the piece's bezel to cover larger recesses, keeping Swap's minimalism and its perfect integration into the ceiling. Easy to fit. Ideal for reforms to replace the light spot, with the already existing holes, without altering the ceiling or repainting. Swap is the best option for updating to LED technology by means of a real light fixture with incorporated LED, in contrast to just a retrofit lamp that only implies a less efficient update of the light source.