


SWAP SQUARE ASYM SUPERCRI 7W DIM DALI/PUSH



## DIMENSIONS



## ACCESSORIES





SWAP IP54 ACCESSORY

SWAP ADD-ON BEZEL

11010101100	7,000020277
Color	Matt white
Category	CEILING RECESSED
	LIGHTING INFORMATION
Light source	LED
Gross luminous flux	820 Lm
Power	7 W
Power values of the system	7,95 W
Colour temperature	4000 K
Colour Rendering Index	CRI>97
Chromatic stability	Mac Adam Step 2
Light beam angle	52°
Lighting efficiency	86%
Efficacy	117 Lm/W
Current intensity	200 mA
Dimming	DALI / Push - Other DIM, please consult
Driver	Incl Fast Connect
Fast connection of the driver to the mains supply	Please Consult
Emergency power supply	Please Consult
Electrical insulation class	
Voltage	220 V/240 V

PRODUCT

4000K W A3553232W

Name

Reference

Ingress Protection
Recess measurements
Weight
Packaged weight
Units per package

Materials

Frequency
Energy efficiency
LED lifespan

OTHER DATA

IP20

85 × 85 mm.

297 g. 20 Aluminium / Polycarbonate

L80B10 (Tj=85°C) >60.000h

50/60 Hz

250 g.

(€

AWARDS






Swap is a ceiling recessed LED spotlight whose main features are its minimalist aspect, its perfect integration into the ceiling, and considerable visual comfort, thanks to the small reflector that is set back with respect to the ceiling plane. When it is switched on, its matte finish shade generates an attractive effect, a discrete circle of light. It includes an add-on bezel that can be used optionally to cover larger recess diameters.






## POLAR DIAGRAM




## CONICAL DIAGRAM









\_

Model Reference

Category

PRODUCT

IP54 Accessory Square

A2543054

Accessories

PRE-ASSEMBLED. NOT SOLD SEPARATELY. NOT COMPATIBLE WITH EXTRA BEZEL. AFFECTS THE LIGHTING PARAMETERS.





To make the difference, Swap IP54 reaches a high sealing level, maintaining at the same time the same aesthetics as a standard Swap. The insulating property is obtained thanks to a protection placed just over the LED, and a silicone joint on the internal part of the bezel. In this way, the external aspect of Swap IP54 is identical to any other Swap IP20. Swap offers the possibility of requesting any of its models with IP54-rated weather resistance, which converts it into an optimal luminaire to be installed in atmospheres where the product may suffer from the impact of water or frequent presence of humidity.







	PRODUCT
Model	Swap Square Asymmetric Add-On Bezel
Colour	W □   Matt white
Category	Accessories



Accessory always included but for optional use. It extends the piece's bezel to cover larger recesses, keeping Swap's minimalism and its perfect integration into the ceiling. Easy to fit. Ideal for reforms to replace the light spot, with the already existing holes, without altering the ceiling or repainting. Swap is the best option for updating to LED technology by means of a real light fixture with incorporated LED, in contrast to just a retrofit lamp that only implies a less efficient update of the light source.

