

## DATOS TÉCNICOS TECHNICAL DATA

|                                   |                                                               |
|-----------------------------------|---------------------------------------------------------------|
| <b>Referencia de producto</b>     | <b>19089L</b>                                                 |
| Product reference                 | 19089L                                                        |
| <b>Descripción</b>                | <b>Pulsador con led de superficie<br/>10A 250V IP55</b>       |
| Description                       | Push button with surface led 10A<br>250V IP55                 |
| <b>Peso neto (Kg)</b>             | <b>0.14</b>                                                   |
| Net weight (Kg)                   | 0.14                                                          |
| <b>ETIM 9.0</b>                   | <b>EC000029</b>                                               |
| <b>Intensidad (A)</b>             | <b>10</b>                                                     |
| Intensity (A)                     | 10                                                            |
| <b>Voltaje (V)</b>                | <b>250</b>                                                    |
| Voltage (V)                       | 250                                                           |
| <b>Frecuencia (Hz)</b>            | <b>(50/60Hz)</b>                                              |
| Frequency (Hz)                    | (50/60Hz)                                                     |
| <b>Material</b>                   | <b>Termoplástico</b>                                          |
| Material                          | Thermoplastic                                                 |
| <b>Color</b>                      | <b>Gris claro / Gris antracita</b>                            |
| Colour                            | Light gray / Anthracite gray                                  |
| <b>Grado de protección IP</b>     | <b>IP55</b>                                                   |
| Degree of protection IP           | IP55                                                          |
| <b>Uso</b>                        | <b>Exterior</b>                                               |
| Use                               | Outdoor                                                       |
| <b>Tipo de instalación</b>        | <b>Superficie</b>                                             |
| Type of installation              | Surface                                                       |
| <b>Resistencia de aislamiento</b> | <b>&gt;5MΩ@500Vdc</b>                                         |
| Insulation resistance             | >5MΩ@500Vdc                                                   |
| <b>Regidez dieléctrica (kV)</b>   | <b>2</b>                                                      |
| Dielectric strength (kV)          | 2                                                             |
| <b>Hilo incandescente</b>         | <b>850°C soportes partes activas /<br/>650°C otras partes</b> |
| Glow wire                         | 850°C active parts supports /<br>650°C other parts            |
| <b>Ensayo de bola</b>             | <b>125°C soportes partes activas /<br/>70°C otras partes</b>  |
| Ball pressure test                | 125°C housings active parts / 70°C<br>other parts             |
| <b>Alto / Height</b>              | <b>80</b>                                                     |
| <b>Ancho / Width</b>              | <b>80</b>                                                     |
| <b>Profundo / Depth</b>           | <b>59</b>                                                     |



## DATOS LOGÍSTICOS LOGISTICS

|                               |                       |
|-------------------------------|-----------------------|
| <b>Unidad mínima de venta</b> | <b>10</b>             |
| Minimum sales unit            | 10                    |
| <b>EAN Unitario</b>           | <b>8429760853800</b>  |
| EAN Unit                      | 8429760853800         |
| <b>Cantidad estuche</b>       | <b>10</b>             |
| Quantity inner box            | 10                    |
| <b>EAN Estuche</b>            | <b>18429760853807</b> |
| EAN Inner box                 | 18429760853807        |
| <b>Cantidad caja</b>          | <b>80</b>             |
| Quantity master box           | 80                    |
| <b>EAN Caja</b>               | <b>28429760853804</b> |
| EAN Master box                | 28429760853804        |
| <b>Partida arancelaria</b>    | <b>85366990</b>       |
| HS code                       | 85366990              |

## NORMATIVAS Y CERTIFICACIONES APPLIED AND CERTIFICATIONS

|                                                   |                                              |
|---------------------------------------------------|----------------------------------------------|
| <b>Normativa</b>                                  | <b>EN 60669-1</b>                            |
| Applied                                           | EN 60669-1                                   |
| <b>Directiva baja tensión</b>                     | <b>Low Voltage Directive 2014/35/UE</b>      |
| Low Voltage Directive                             | Low Voltage Directive 2014/35/UE             |
| <b>Directiva Rohs</b>                             | <b>RoHS 2011/65/UE and<br/>modifications</b> |
| Rohs Directive                                    | RoHS 2011/65/UE and modifications            |
| <b>Certificado de producto</b>                    | <b>-</b>                                     |
| Product certificate                               | -                                            |
| <b>Reglamento electrotécnico<br/>baja tensión</b> | <b>REBT 2002</b>                             |
| Low voltage electrotechnical<br>regulations       | REBT 2002                                    |