

DATOS TÉCNICOS

TECHNICAL DATA

Referencia de producto	9/406
Product reference	9/406
Descripción	Base múltiple de 6 tomas 2P+T. Protección infantil. Tensión nominal 250V~.
Description	Multiple base of 6 sockets 2P+T. Child protection. Nominal voltage 250V~.
Peso neto (Kg)	0.304
Net weight	0.304
ETIM 9.0	EC000330
Intensidad (A)	16
IEC-Amperage (A)	16
Polos	2P+T
Poles	2P+T
Frecuencia	50Hz
Frequency	50Hz
Voltaje (V)	250
Voltage (V)	250
Color	Blanco
Colour	White
RAL	9003
Interruptor	No
Switch	No
Material	Termoplástico
Material	Thermoplastic
Grado de protección	IP20
Protection degree	IP20
Resistencia al impacto	IK07
Impact resistance	IK07
Uso	Interior
Use	Indoor
Prueba hilo incandescente	850°C soporte partes activas/ 650°C otras partes
Glow wire test	850°C supports active parts / 650°C other parts
Ensayo de bola	125°C soporte partes activas/ 70°C otras partes
Ball pressure test	125°C supports active parts/ 70°C other parts
Resistencia al aislamiento	5MΩ@500Vdc
Insulating resistance	5MΩ@500Vdc
Potencia max.	3680
Max. power	3680
Rigidez dieléctrica (kV)	2
Dielectric Strength (kV)	2
Temperatura de funcionamiento	-5°C / 40°C
Operating temperature	-5°C / 40°C
Temperatura de transporte y almacenaje	-25°C/ 70°C
Transport and storage temperature	-25°C/ 70°C
Alto / High	55
Ancho / Width	326
Profundo / Deep	41



DATOS LOGÍSTICOS

LOGISTICS

Unidad mínima de venta	6
Minimum sales unit	6
EAN Unitario	8429760846031
EAN Unit	8429760846031
Cantidad estuche	6
Quantity inner box	6
EAN Estuche	18429760846038
EAN Inner box	18429760846038
Cantidad caja	18
Quantity master box	18
EAN Caja	28429760846035
EAN Master box	28429760846035
Partida arancelaria	85366990
HS code	85366990

NORMATIVAS Y CERTIFICACIONES

APPLIED AND CERTIFICATIONS

Normativa	UNE 20315-1-1, UNE 20315-1-2, IEC 60884-1 CEE7 SS III
Applied	UNE 20315-1-1, UNE 20315-1-2, IEC 60884-1 CEE7 SS III
Directiva baja tensión	-
Low Voltage Directive	-
Directiva Rohs	RoHS 2011/65/UE and modifications
Rohs Directive	RoHS 2011/65/UE and modifications
Certificado de producto	-
Product certificate	-