

Manufacturer:
Amphenol Fiber Optic Products

Product Name:
Amphenol 905 SMA Connector, 200µm (micron) Stainless Steel Ferrule, 3mm Boot

Manufacturer Part Number:
905-150-5074



▶ Click here for more details on the Amphenol 905 SMA Connector, 200µm (micron) Stainless Steel Ferrule, 3mm Boot

SMA Classic 905 Series



- ▶ The original industry-standard SMA optical connector, designed by Amphenol
- ▶ Known for its precision in fiber alignment for reliable performance
- ▶ Versatile design, widely used in high-power and rugged applications


The 905-150-5XXXX series is available but for new designs, opt for the 905-160-5XXXX series which uses a more intelligent numbering system. The 905-150-5XXXX remains listed due to its prevalence in existing bills of materials.

Bulk Packing Options for Existing Part Numbers

Bulk Quantity	Suffix to Add
100	-P
500	-Y
1000	-Z

Contact the professionals at Fiber Optic Center for a quote or to get more details.

23 Centre Street • New Bedford, MA 02740 USA • focenter.com • 508-992-6464 • (800) 473-4237 • sales@focenter.com



Manufacturer:
Amphenol Fiber Optic Products

Product Name:
Amphenol 905 SMA Connector, 200µm (micron) Stainless Steel Ferrule, 3mm Boot

Manufacturer Part Number:
905-150-5074



▶ Click here for more details on the Amphenol 905 SMA Connector, 200µm (micron) Stainless Steel Ferrule, 3mm Boot


SMA Classic 905 Series

Classic Part Number	New Part Number	Ferrule Hole Size and Tolerance	Ferrule Length	Ferrule OD	Crimp Ferrule	Coupling Nut Material	Coupling Nut Type	Boot Diameter-Rear ID	Boot Logo	Boot Color	Cap Type	Cap Color	Tether Loop	Cap Slit	Cap Logo
905-150-5001	905-160-50128	128 µm (+5/-0 µm)	9.855 mm (.388")	3.167 mm (.1247")	Yes	Nickel Plated Brass	Knurled	2.8 mm	Yes	Black	T-Style	Black	No	No	No
905-150-5079	905-160-50150	150 µm (+10/-0 µmm)	9.855 mm (.388")	3.167 mm (.1247")	Yes	Nickel Plated Brass	Knurled	2.8 mm	Yes	Black	T-Style	Black	No	No	No
905-150-5061	905-160-50175	175 µmm (+10/-0 µmm)	9.855 mm (.388")	3.167 mm (.1247")	Yes	Nickel Plated Brass	Knurled	2.8 mm	Yes	Black	T-Style	Black	No	No	No
905-150-5041	905-160-50206	206 µm (+10/-0 µm)	9.855 mm (.388")	3.167 mm (.1247")	Yes	Nickel Plated Brass	Knurled	2.8 mm	Yes	Black	T-Style	Black	No	No	No
905-150-5003	905-160-50231	231 µm (+10/- 0 µm)	9.855 mm (.388")	3.167 mm (.1247")	Yes	Nickel Plated Brass	Knurled	2.8 mm	Yes	Black	T-Style	Black	No	No	No
905-150-5009	905-160-50245	245 µm (+10/-0 µm)	9.855 mm (.388")	3.167 mm (.1247")	Yes	Nickel Plated Brass	Knurled	2.8 mm	Yes	Black	T-Style	Black	No	No	No
905-150-5049	905-160-50310	310 µm (+15/-0 µm)	9.855 mm (.388")	3.167 mm (.1247")	Yes	Nickel Plated Brass	Knurled	2.8 mm	Yes	Black	T-Style	Black	No	No	No
905-150-5192-P (Bulk)	none	430 µm (+5/-0 µm)	9.855 mm (.388")	3.167 mm (.1247")	Yes	None	None	2.8 mm	Yes	Black	T-Style	Black	No	No	No
905-150-5098	905-160-50455	455 µm (+15/-0 µm)	9.855 mm (.388")	3.167 mm (.1247")	Yes	Nickel Plated Brass	Knurled	2.8 mm	Yes	Black	T-Style	Black	No	No	No
905-150-5052	905-160-50480	480 µm (+15/-0 µm)	9.855 mm (.388")	3.167 mm (.1247")	Yes	Nickel Plated Brass	Knurled	2.8 mm	Yes	Black	T-Style	Black	No	No	No
905-150-5016	905-160-50490	490 µm (+15/-0 µm)	9.855 mm (.388")	3.167 mm (.1247")	Yes	Nickel Plated Brass	Knurled	2.8 mm	Yes	Black	T-Style	Black	No	No	No
905-150-5153	905-160-50584	584 µm (+15/-0 µm)	9.855 mm (.388")	3.167 mm (.1247")	Yes	Nickel Plated Brass	Knurled	2.8 mm	Yes	Black	T-Style	Black	No	No	No

Contact the professionals at Fiber Optic Center for a quote or to get more details.

23 Centre Street • New Bedford, MA 02740 USA • focenter.com • 508-992-6464 • (800) 473-4237 • sales@focenter.com

Product specifications and data are subject to change without notice. FOC last update 2/25/2026.



Manufacturer:
Amphenol Fiber Optic Products

Product Name:
Amphenol 905 SMA Connector, 200µm (micron) Stainless Steel Ferrule, 3mm Boot

Manufacturer Part Number:
905-150-5074



▶ Click here for more details on the Amphenol 905 SMA Connector, 200µm (micron) Stainless Steel Ferrule, 3mm Boot


SMA Classic 905 Series

Classic Part Number	New Part Number	Ferrule Hole Size and Tolerance	Ferrule Length	Ferrule OD	Crimp Ferrule	Coupling Nut Material	Coupling Nut Type	Boot Diameter-Rear ID	Boot Logo	Boot Color	Cap Type	Cap Color	Tether Loop	Cap Slit	Cap Logo
905-150-5151	905-160-50641	641 µm (+15/-0 µm)	9.855 mm (.388")	3.167 mm (.1247")	Yes	Nickel Plated Brass	Knurled	2.8 mm	Yes	Black	T-Style	Black	No	No	No
905-150-5005	905-160-50150	150 µm (+10/-0 µm)	9.855 mm (.388")	3.167 mm (.1247")	Yes	Nickel Plated Brass	Knurled	2.8 mm	Yes	Black	T-Style	Black	No	No	No
905-150-5158	905-160-50690	690 µm (+15/-0 µm)	9.855 mm (.388")	3.167 mm (.1247")	Yes	Nickel Plated Brass	Knurled	2.8 mm	Yes	Black	T-Style	Black	No	No	No
905-150-5091	905-160-50710	710 µm (+15/-0 µm)	9.855 mm (.388")	3.167 mm (.1247")	Yes	Nickel Plated Brass	Knurled	2.8 mm	Yes	Black	T-Style	Black	No	No	No
905-150-5083	905-160-50750	750 µm (+15/-0 µm)	9.855 mm (.388")	3.167 mm (.1247")	Yes	Nickel Plated Brass	Knurled	2.8 mm	Yes	Black	T-Style	Black	No	No	No
905-150-5170	None-2nd body	850 µm (+15/-0 µm)	9.855 mm (.388")	3.167 mm (.1247")	Yes	Nickel Plated Brass	Knurled	2.8 mm	Yes	Black	T-Style	Black	No	No	No
905-150-5027	905-160-51020	1020 µm (+15/-0 µm)	9.855 mm (.388")	3.167 mm (.1247")	Yes	Nickel Plated Brass	Knurled	2.8 mm	Yes	Black	T-Style	Black	No	No	No
905-150-5080	905-160-51100	1100 µm (+15/-0 µm)	9.855 mm (.388")	3.167 mm (.1247")	Yes	Nickel Plated Brass	Knurled	2.8 mm	Yes	Black	T-Style	Black	No	No	No
905-150-5078	905-160-51300	1300 µm (+15/-0 µm)	9.855 mm (.388")	3.167 mm (.1247")	Yes	Nickel Plated Brass	Knurled	2.8 mm	Yes	Black	T-Style	Black	No	No	No
905-150-5002	905-160-50144	144 µm (+5/-0 µm)	9.855 mm (.388")	3.167 mm (.1247")	Yes	Nickel Plated Brass	Knurled	2.8 mm	Yes	Black	T-Style	Black	No	No	No
905-150-5058	905-160-50172	172 µm (+10/-0 µm)	9.855 mm (.388")	3.167 mm (.1247")	Yes	Nickel Plated Brass	Knurled	2.8 mm	Yes	Black	T-Style	Black	No	No	No
905-150-5074	905-160-50200	200 µm (+10/-0 µm)	9.855 mm (.388")	3.167 mm (.1247")	Yes	Nickel Plated Brass	Knurled	2.8 mm	Yes	Black	T-Style	Black	No	No	No

Contact the professionals at Fiber Optic Center for a quote or to get more details.

23 Centre Street • New Bedford, MA 02740 USA • focenter.com • 508-992-6464 • (800) 473-4237 • sales@focenter.com

Product specifications and data are subject to change without notice. FOC last update 2/25/2026.



Manufacturer:
Amphenol Fiber Optic Products

Product Name:
Amphenol 905 SMA Connector, 200µm (micron) Stainless Steel Ferrule, 3mm Boot

Manufacturer Part Number:
905-150-5074



▶ Click here for more details on the Amphenol 905 SMA Connector, 200µm (micron) Stainless Steel Ferrule, 3mm Boot


SMA Classic 905 Series

Classic Part Number	New Part Number	Ferrule Hole Size and Tolerance	Ferrule Length	Ferrule OD	Crimp Ferrule	Coupling Nut Material	Coupling Nut Type	Boot Diameter-Rear ID	Boot Logo	Boot Color	Cap Type	Cap Color	Tether Loop	Cap Slit	Cap Logo
905-150-5008	905-160-50225	225 µm (+10/-0µm)	9.855 mm (.388")	3.167 mm (.1247")	Yes	Nickel Plated Brass	Knurled	2.8 mm	Yes	Black	T-Style	Black	No	No	No
905-150-5086	905-160-50240	240 µm (+10/-0 µm)	9.855 mm (.388")	3.167 mm (.1247")	Yes	Nickel Plated Brass	Knurled	2.8 mm	Yes	Black	T-Style	Black	No	No	No
905-150-5056	905-160-50250	250 µm (+15/-0 µm)	9.855 mm (.388")	3.167 mm (.1247")	Yes	Nickel Plated Brass	Knurled	2.8 mm	Yes	Black	T-Style	Black	No	No	No
905-150-5040	905-160-50284	284 µm (+15/-0 µm)	9.855 mm (.388")	3.167 mm (.1247")	Yes	Nickel Plated Brass	Knurled	2.8 mm	Yes	Black	T-Style	Black	No	No	No
905-150-5015	905-160-50330	330 µm(+15/-0 µm)	9.855 mm (.388")	3.167 mm (.1247")	Yes	Nickel Plated Brass	Knurled	2.8 mm	Yes	Black	T-Style	Black	No	No	No
905-150-5195-P (Bulk)	905-160-50420-P	420 µm (+15/-0 µm)	9.855 mm (.388")	3.167 mm (.1247")	Yes	Nickel Plated Brass	Knurled	2.8 mm	Yes	Black	T-Style	Black	No	No	No
905-150-5004	905-160-50436	436 µm (+15/-0 µm)	9.855 mm (.388")	3.167 mm (.1247")	Yes	Nickel Plated Brass	Knurled	2.8 mm	Yes	Black	T-Style	Black	No	No	No
905-150-5095	905-160-50470	470 µm (+15/-0 µm)	9.855 mm (.388")	3.167 mm (.1247")	Yes	Nickel Plated Brass	Knurled	2.8 mm	Yes	Black	T-Style	Black	No	No	No
905-150-5064	905-160-50485	485 µm (+15/-0 µm)	9.855 mm (.388")	3.167 mm (.1247")	Yes	Nickel Plated Brass	Knurled	2.8 mm	Yes	Black	T-Style	Black	No	No	No
905-150-5073	905-160-50521	521 µm (+15/-0 µm)	9.855 mm (.388")	3.167 mm (.1247")	Yes	Nickel Plated Brass	Knurled	2.8 mm	Yes	Black	T-Style	Black	No	No	No
905-150-5152	905-160-50610	610 µm (+15/-0 µm)	9.855 mm (.388")	3.167 mm (.1247")	Yes	Nickel Plated Brass	Knurled	2.8 mm	Yes	Black	T-Style	Black	No	No	No
905-150-5172	905-160-50630	630 µm (+15/-0 µm)	9.855 mm (.388")	3.167 mm (.1247")	Yes	Nickel Plated Brass	Knurled	2.8 mm	Yes	Black	T-Style	Black	No	No	No

Contact the professionals at Fiber Optic Center for a quote or to get more details.

23 Centre Street • New Bedford, MA 02740 USA • focenter.com • 508-992-6464 • (800) 473-4237 • sales@focenter.com

Product specifications and data are subject to change without notice. FOC last update 2/25/2026.



Manufacturer:
Amphenol Fiber Optic Products

Product Name:
Amphenol 905 SMA Connector, 200µm (micron) Stainless Steel Ferrule, 3mm Boot

Manufacturer Part Number:
905-150-5074



Learn More

► Click here for more details on the Amphenol 905 SMA Connector, 200µm (micron) Stainless Steel Ferrule, 3mm Boot

SMA Classic 905 Series

Classic Part Number	New Part Number	Ferrule Hole Size and Tolerance	Ferrule Length	Ferrule OD	Crimp Ferrule	Coupling Nut Material	Coupling Nut Type	Boot Diameter-Rear ID	Boot Logo	Boot Color	Cap Type	Cap Color	Tether Loop	Cap Slit	Cap Logo
905-150-5090	905-160-50225	672 µm (+15/-0 µm)	9.855 mm (.388")	3.167 mm (.1247")	Yes	Nickel Plated Brass	Knurled	2.8 mm	Yes	Black	T-Style	Black	No	No	No
905-150-5059	905-160-50700	700 µm (+15/-0 µm)	9.855 mm (.388")	3.167 mm (.1247")	Yes	Nickel Plated Brass	Knurled	2.8 mm	Yes	Black	T-Style	Black	No	No	No
905-150-5084	906-160-50735	735 µm (+15/-0 µm)	9.855 mm (.388")	3.167 mm (.1247")	Yes	Nickel Plated Brass	Knurled	2.8 mm	Yes	Black	T-Style	Black	No	No	No
905-150-5179	None, 2nd body	820 µm (+15/-0 µm)	9.855 mm (.388")	3.167 mm (.1247")	Yes	Nickel Plated Brass	Knurled	2.8 mm	Yes	Black	T-Style	Black	No	No	No
905-150-5033	905-160-50960	960 µm (+15/-0 µm)	9.855 mm (.388")	3.167 mm (.1247")	Yes	Nickel Plated Brass	Knurled	2.8 mm	Yes	Black	T-Style	Black	No	No	No
905-150-5057	905-160-51055	1055 µm (+15/-0 µm)	9.855 mm (.388")	3.167 mm (.1247")	Yes	Nickel Plated Brass	Knurled	2.8 mm	Yes	Black	T-Style	Black	No	No	No
905-150-5034	905-160-51120	1210 µm (+15/-0 µm)	9.855 mm (.388")	3.167 mm (.1247")	Yes	Nickel Plated Brass	Knurled	2.8 mm	Yes	Black	T-Style	Black	No	No	No
905-150-5162	905-160-61650	1650 µm (+25/-0 µm)	9.855 mm (.388")	3.167 mm (.1247")	Yes	Nickel Plated Brass	Knurled	2.8 mm	Yes	Black	T-Style	Black	No	No	

Contact the professionals at Fiber Optic Center for a quote or to get more details.

23 Centre Street • New Bedford, MA 02740 USA • focenter.com • 508-992-6464 • (800) 473-4237 • sales@focenter.com

Product specifications and data are subject to change without notice. FOC last update 2/25/2026.